

Yealink T20E IP Phone



Product Name: Yealink T20E IP Phone

Manufacturer: -

Model Number: SIP-T20E

Yealink T20E - Value Entry Level IP Phone

Please Note: The Yealink T20E has been discontinued. For an alternative, we highly recommend the Yealink T20P PoE version.

The Yealink T20E IP Phone is a competitively priced quality IP phone. It has the same functionality as the popular Yealink T20P / T20PN models including the same Auto Provisioning engine. However, as there is no POE support it is supplied as standard with a UK PSU. Yealink T20E Key Features

- 2 SIP Accounts
- 2 Line, 2x16 LCD Display
- 2 Programmable Keys
- 5 Hard Function Keys
- 3 Way Conference Calls
- Speakerphone
- Call Hold, Waiting and Transfer.
- Wall mountable

The T20E features a 2 line LCD display and 9 function keys for simple integration into various SIP based network solutions where basic business feature requirements and demanding budgets are the main influences on buying decisions.

Yealink T20E Technical Specifications

Network Features

- SIP v1(RFC2543), v2(RFC3261)
- 3 User accounts
- NAT Transverse: STUN mode
- IP Assignment: Static/DHCP/PPPoE
- In-Band DTMF, Out-of-Band DTMF, SIP Info
- Proxy mode and Peer-to-peer SIP link mode
- TFTP/DHCP/PPPoE client
- Telnet/HTTP server
- DNS client
- NAT/DHCP server
- Support VLAN, QoS
- VPN Support

Voice Features

- Wideband Codec: G.722, voice spectrum between 50-7000Hz
- Narrowband Codecs: G.711, G.726, G.723.1/ILBC, G.729AB and GSM VAD, CNG, AEC, PLC, AEC, AGC
- Full-duplex hands-free speakerphone

Telephony Features

- Call Hold, Call Waiting, Call Transfer,

Yealink T20E IP Phone

• Call Forward 300 name/number phonebook
• Caller ID, Call List, DND, Redial
• Flash 3-way Conference, Speed Dial
• Personal Ring Tone, Voicemail
• Volume Adjustment, Mute, Speakerphone

IP PBX System Integration

• Dial Plan, Dial-now, Paging
• Downloadable enterprise phonebook
• Call Park, Call Pickup, Distinctive Ringtone Auto-answer, intercom

Config, Upgrade and Usage

• OpenVPN support Firmware
• Upgrade: TFTP/Console/ Auto-provision Auto-provision: TR069, https, http, ftp, tftp, PnP
• Direct IP call without SIP proxy
• Dial number via SIP server Dial URL via SIP server

Security

• Secure RTP
• Digest authentication using MD5/MD5-sess
• Secure configuration file via AES encryption

TI Titan Chipset

• LCD: 2 Lines, 2x16
• 2 programmable keys
• 23 hard keys,
• 2 indication LEDs Headset port:
• RJ9 Network Interface: 2xRJ45 10/100M ports
• Dimension: 185 X 200 X 90 mm
• Net Weight: 1.22 kg Power adapter:
• Input: AC 100~240V Output: DC 5V/1A
• Operating humidity: 10~95%
• Storage temperature: up to 60 C

Please Enquire