

Polycom VVX Camera



Product Name: Polycom VVX Camera

Manufacturer: -

Model Number: 2200-46200-025

Please Note: This product has been discontinued. Please see the Polycom IP Phone range for an alternative.

Polycom VVX Camera

The Polycom VVX Camera turns your VVX Business Media Phone into a desktop video conferencing solution. Video Conferencing is proven to enhance communications and collaboration between individuals and groups within and across organisations.

Polycom VVX Camera Key Features

- Physical privacy shutter
- Adjustable tilt control
- Plug and Play setup
- Uncompressed local loopback video
- Normal, Full, Crop video screen modes
- Local side-by-side, PIP window modes
- Autostart video option
- Adjustable levels and frame rate
- Anti-Flicker compensation
- 2 color / 4 state status LED

Whether your employees work from an office, a cubicle or directly from their home, give them the power of video conferencing right from their desktop with the new Polycom VVX Camera. The Polycom VVX Camera is a high quality video camera, designed as an easy add-on that complements the Polycom VVX 500 or VVX 600 desktop phones. The Polycom VVX Camera turns your VVX Business Media Phones into a true high definition, yet cost effective, desktop video conferencing solution in seconds.

Polycom VVX Camera - Technical Specifications

User Interface Features

- Privacy shutter
- Adjustable tilt
- Plug and Play setup
- Uncompressed local video loopback
- Normal, Full, Crop video screen modes
- Side-by-side, PIP window modes
- Autostart video option
- Adjustable levels and frame rate
- Anti-Flicker compensation
- 2 color/4 state status LED

Video standards and protocols

- H.263, H.264 encoding
- Decodable H.263 Annexes: A & H
- Decodable H.263 Image Sizes: SQCIF, QCIF, CIF
- Decodable H.264 Baseline Levels: 1, 1b, 1.1, 1.2, 1.3, 2
- Decodable H.264 Image Sizes: SQCIF, QCIF, SCIF, QVGA, SIF, WQVGA, CIF

Polycom VVX Camera

Bandwidth

- 2 Mbps max transmit bitrate

Content video resolution

- 24-bit true color
- Supports up to 720p30 transmit video (H.264)
- Supports up to 4CIF/30 transmit video (H.263)
- Supports CIF (352 x 288) receive video

Camera

- f/2.0 aperture
- Vertical tilt angle adjustable from 0° to 30°
- 55° FOV min
- Automatic exposure and white balance

Network and Provisioning

- H.323 or SIP Signaling
- Polycom CMA Provisioning

Video Calling Interoperability

- All Polycom UC infrastructure and video solutions including:
 - Polycom VVX1500
 - Polycom VVX500/600 Business Media Phones
 - Polycom RMX Conference Platforms
 - Polycom HDX Series
 - Microsoft Lync-enabled clients
 - Other Standards-based (H.264/H.263) endpoints

Accessory Compatibility

- Polycom VVX 600
- Polycom VVX 500

Interface

- USB 2.0 (UVC 1.1 compliant)

Power

- 5V <500mA via USB port

Approvals

- FCC Part 15 (CFR 47) Class B
- ICES-003 Class B
- EN55022 Class B
- CISPR22 Class B
- VCCI Class B
- EN55024

Polycom VVX Camera

• Korea KC
• ROHS compliant
• Brazil ANATEL
• Australia C Tick

Safety

• UL 60950-1
• CE Mark
• CAN/CSA-C22.2 No. 60950-1-03
• EN 60950-1
• IEC 60950-1
• AS/NZS 60950-1

Operating Conditions

• Temperature: (+32 to 104°F (0 to 40°C)
• Relative Humidity: 5% to 95%, noncondensing

Storage Conditions

• 40 to +160°F (-40 to +70°C)

Polycom VVX Camera Comes with

• VVX Camera unit
• Quick Start Guide

Country of Origin

• China

Warranty

• One (1) year

Part Number

• 2200-46200-001-WW

Please Enquire
