Polycom VVX Camera



Product Name: Polycom VVX Camera
Manufacturer: -
Model Number: 2200-46200-025

Please Note: This product has been discontinued. Please see the Polycom IP Phone range for an alternative.

Polycom VVX Camera
The Polycom VVX Camera turns your VVX Business Media Phone into a desktop video conferencing solution Video Conferencing is proven to enhance communications and collaboration between individuals and groups within and across organisations.
Polycom VVX Camera Key Features

ï¿½ Physical privacy shutter
ï¿½ Adjustable tilt control
ï¿½ Plug and Play setup
ï¿½ Uncompressed local loopback video
ï¿½ Normal, Full, Crop video screen modes
ï¿½ Local side-by-side, PIP window modes
ï¿½ Autostart video option
ï¿½ Adjustable levels and frame rate
ï¿½ Anti-Flicker compensation
ï¿½ 2 color / 4 state status LED

Whether your employees work from an office, a cubicle or directly from their home, give them the power of video conferencing right from their desktop with the new Polycom VVX Camera. The Polycom VVX Camera is a high quality video camera, designed as an easy add-on that complements the Polycom VVX 500 or VVX 600 desktop phones. The Polycom VVX Camera turns your VVX Business Media Phones into a true high definition, yet cost effective, desktop video conferencing solution in seconds.

Polycom VVX Camera - Technical Specifications
User Interface Features

ï¿½ Privacy shutter
ï¿½ Adjustable tilt
ï¿½ Plug and Play setup
ï¿½ Uncompressed local video loopback
ï¿½ Normal, Full, Crop video screen modes
ï¿½ Side-by-side, PIP window modes
ï¿½ Autostart video option
ï¿½ Adjustable levels and frame rate
ï¿½ Anti-Flicker compensation
ï¿½ 2 color/4 state status LED

Video standards and protocols

ï¿½ H.263, H.264 encoding
ï¿½ Decodable H.263 Annexes: A – H
ï¿½ Decodable H.263 Image Sizes: SQCIF, QCIF, CIF
ï¿½ Decodable H.264 Baseline Levels: 1, 1b, 1.1, 1.2, 1.3, 2
ï¿½ Decodable H.264 Image Sizes: SQCIF, QCIF, SCIF, QVGA, SIF, WQVGA, CIF

Polycom VVX Camera

Bandwidth

ï¿½ 2 Mbps max transmit bitrate

Content video resolution

ï¿½ 24-bit true color
ï¿½ Supports up to 720p30 transmit video (H.264)
ï¿½ Supports up to 4CIF/30 transmit video (H.263)
ï¿½ Supports CIF (352 x 288) receive video

Camera

ï¿½ f/2.0 aperture
ï¿½ Vertical tilt angle adjustable from 0° to 30°
ï¿½ 55° FOV min
ï¿½ Automatic exposure and white balance

Network and Provisioning

ï¿½ H.323 or SIP Signaling
ï¿½ Polycom CMA™ Provisioning

Video Calling Interoperability

ï¿½ All Polycom UC infrastructure and video solutions including:
ï¿½ PolycomVVX1500
ï¿½ PolycomVVX500/600 Business Media Phones
ï¿½ Polycom RMXConference Platforms
ï¿½ PolycomHDXSeries
ï¿½ Microsoft Lync-enabled clients
ï¿½ Other Standards-based (H.264/H.263) endpoints

Accessory Compatibility

ï¿½ Polycom VVX 600
ï¿½ Polycom VVX 500

Interface

ï¿½ USB 2.0 (UVC 1.1 compliant

Power

ï¿½ 5V <500mA via USB port

Approvals

ï¿½ FCC Part 15 (CFR 47) Class B
ï¿½ ICES-003 Class B
ï¿½ EN55022 Class B
ï¿½ CISPR22 Class B
ï¿½ VCCI Class B
ï¿½ EN55024

Polycom VVX Camera

ï¿½ Korea KC
ï¿½ ROHS compliant
ï¿½ Brazil ANATEL
ï¿½ Australia C Tick

Safety

ï¿½ UL 60950-1
ï¿½ CE Mark
ï¿½ CAN/CSA-C22.2 No. 60950-1-03
ï¿½ EN 60950-1
ï¿½ IEC 60950-1
ï¿½ AS/NZS 60950-1

Operating Conditions

ï¿½ Temperature: (+32 to 104°F (0 to 40°C)
ï¿½ Relative Humidity: 5% to 95%, noncondensing

Storage Conditions

ï¿½ 40 to +160°F (-40 to +70°C)

Polycom VVX Camera Comes with

ï¿½ VVX Camera unit
ï¿½ Quick Start Guide

Country of Origin

ï¿½ China

Warranty

ï¿½ One (1) year

Part Number

ï¿½ 2200-46200-001-WW

Please Enquire