

Polycom VVX Expansion Module



Product Name: Polycom VVX Expansion Module

Manufacturer: -

Model Number: 2200-46300-025

Please Note: This expansion module is intended for use with the VVX 300, 310, 400, 410, 500 and 600

Polycom VVX Expansion Module Paper Directory (2200-46300-025)

The Polycom VVX Expansion Module is a cost-effective solution for telephone attendants, receptionists, administrative staff, and other dispatchers who manage multiple simultaneous telephone calls on a daily basis. The Polycom VVX Expansion Module extends the functionality of Polycom VVX business media phones with multifunctional line keys that can be set up as line registrations, call appearances, speed-dials, direct station select or busy lamp field keys. The VVX Expansion Module seamlessly matches the look and feel of VVX business media phones. Polycom VVX business media phones can be fully equipped with up to three VVX Expansion Modules. With VVX Expansion Modules, users can reduce the number of lost customer calls, shorten transaction times, and increase the accuracy of call routing by promptly accepting, accurately screening, efficiently dispatching and effortlessly monitoring calls.

The VVX Expansion Module is a true plug-and-play device that requires no separate set-up as power and signaling are provided by the host VVX business media phone. The VVX Expansion Module provides an easy transition from traditional PBX features and functionality into the world of Voice over IP with familiar paper directory cards and intuitive LED visualization that matches the VVX business media phone. Like all Polycom VoIP products, the VVX Expansion Module is standards-based and fully interoperable with Polycom partners' IP telephony server solutions.3 With the greatest breadth and depth of integrated video, voice, and web solutions, only Polycom delivers the ultimate communications experience.

VVX Expansion Key Features

- ½ Increase productivity—The VVX Expansion Module provides cost-effective call handling capabilities using directory cards that simplifies monitoring/dispatching of a high number of static contacts

- ½ Ease of use—Bi-color LEDs offer flexible and intuitive call visualization matching VVX phones

- ½ Extended compatibility—Supports all VVX business media phones for maximum flexibility

- ½ Flexible paper directory—Quickly generate and print PDF template containing line key assignments

- ½ Leverage previous IT infrastructure investment—Get the most out of your Polycom VVX business media phones by turning them into cost-effective attendant solutions

VVX Expansion - Technical Specifications

VVX Expansion Module specifications

- ½ 40 multifunctional line keys configurable as line registration, call appearance, speed dial, DSS, or BLF

- ½ Dual-color (red or green) illuminated LEDs for line status information

Compatible Polycom® VVX® business media phone models1

- ½ Polycom® VVX® 300/310

- ½ Polycom® VVX® 400/410

- ½ Polycom® VVX® 500

- ½ Polycom® VVX® 600

Polycom VVX Expansion Module

Communication with host phone and/or other modules

- 2 auxiliary ports over (RJ-11)

Expandability

- Up to three VVX Expansion Modules can be attached to any VVX phone²

Feature support³

- Additional line registrations (up to 34 total)

- Shared call appearance, bridged line appearance (Key system emulation)

- Call transfer

- Busy lamp field

- Speed dial

- Fully programmable line appearances

Power

- Provided by Polycom VVX host phone

- Host phone powering options: IEEE 802.3(af/at) PoE or using a compatible external AC adapter

- Powering starts automatically upon auxiliary port connection

- No additional power source is required²

Approvals

- CE Mark

- VCCI

- C-Tick

Safety

- UL 60950-1

- CAN/CSA-C22.2 No. 60950-1

- EN 60950-1

- IEC 60950-1

- AS/NZS 60950-1

Operating conditions

- Temperature: 0°C (+32°F) to 40°C (104°F) Relative Humidity: 5% to 95%, noncondensing

Storage Temperature

- -40°C (-40°F) to 70°C (160°F) VVX Expansion Module ships with

- VVX Expansion Module console

- VVX Expansion Module desk stand

- Attachment bracket with hand screws (2)

- Auxiliary cable

- Quick start guide

Dimensions

Polycom VVX Expansion Module

• 5 in x 5 in x 6.5 in (12.5 cm x 12.5 cm x 16 cm) (W x H x D)

Weight

Physical: 1 lb (0.4 kg)

Unit box dimensions

11 in x 6 in x 3.5 in (27.9 cm x 15.2 cm x 8.9 cm)

Unit box weight

1.32 lb (0.6 kg)

Master carton quantity

Ten (10)

Country of origin

China

Warranty

One (1) year

Part number/UPC code

2200-46300-025 / 610807781479

Please Enquire
