

Yealink T41P IP Phone (SIP-T41P)



Product Name: Yealink T41P IP Phone (SIP-T41P)

Manufacturer: -

Model Number: SIP-T41P

Yealink T41P IP Phone (SIP-T41P)

Please Note: The Yealink T41P IP Phone has now been discontinued and replaced by the Yealink SIP-T41S IP Phone.

The Yealink T41P is a 6 Line IP Phone designed to pursue ease of use, in even the tiniest details. The T41P has superb HD sound quality as well as rich visual experience. With programmable keys, along with support for vast productivity-enhancing features, the Yealink T41P uses standard encryption protocols to perform highly secure remote provisioning and software upgrades.
Yealink T41P IP Phone Features

- Revolutionarily new design
- Yealink Optima HD voice
- 2.7" 192x64-pixel graphical LCD with backlight
- Up to 6 SIP accounts
- Paper label free design
- PoE support
- Headset, EHS support
- Integrated stand with 2 adjustable angles
- Wall mountable

The SIP-T41P supports vast productivity-enhancing feature such as SCA, BLF List, call forward, call transfer, 3-way conference. Three pages of 6 flexible buttons are shown on the display can be programmed up to 15 various features. Support Yealink YHS32, With EHS36 user can control phone through wireless headset.

Note: Please refer to the Yealink VoIP Phone Range Detailed Comparison Table for more information.

Yealink T41P IP Phone - Technical Specifications
Audio Features

- HD voice: HD handset, HD speaker
- Wideband codec: G.722
- Narrowband codec: G.711(Aμ), G.723, G.729AB, G.726, GSM
- DTMF: In-band, Out-of-band(RFC 2833) and SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJB, AGC

Phone features

- 6 VoIP accounts
- One-touch speed dial, redial
- Call forward, Call waiting, Call transfer, Call hold
- Call return, Group listening
- Mute, Auto answer, DND
- Call history: dialed/received/missed/forwarded
- 3-way confernece call
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Hotline, Emergency call

Yealink T41P IP Phone (SIP-T41P)

- Set date time manually or automatically
- Dial Plan, Push XML, Action URL

Directory

- Local phonebook up to 300 entries
- Broadsoft Contacts: Custom/Enterprise/Personal/Common/Search/Speed Dial
- Black list
- XML/LDAP remote phonebook
- Intelligent search method
- Phonebook search/import/export

IP-PBX and BroadSoft features

- Busy lamp field (BLF), BLF list
- Bridged line appearance(BLA)/SCA
- Anonymous call, Anonymous call rejection
- DND & forward synchronization
- BroadWorks Anywhere
- N-Way Calling, Remote Office
- Network Call Logs - Basic
- Broadsoft call center features
- Message waiting indicator (MWI)
- Voice mail, Call park, Call pickup
- Intercom, paging, Music on hold
- Call recording

Display and Indicator

- 2.7" 192x64-pixel 4-level grayscale graphical LCD with backlight
- LED for call and message waiting indication
- Dual-color (red or green) illuminated LEDs for line status information
- Intuitive user interface with icons and soft keys
- National language selection
- Caller ID with name, number
- Stand with 2 adjustable angles
- Wall mountable
- External Universal AC Adapter (optional) AC 100~240V input and DC 5V/1.2A output
- Power consumption (PSU): 1.4W-3.9W
- Dimension(W*D*H*T):212mm*189mm*175mm*54mm
- Operating humidity: 10~95%
- Storage temperature: -10~50°C

Feature keys

- 6 line keys with LED
- 6 line keys can be programmed up to 15 various features (3-page view)
- 5 features keys: Message, Headset, Mute, Redial, Hands-free speakerphone
- 4 context-sensitive "soft" keys
- 6 navigation keys
- 2 volume control keys
- Illuminated mute key
- Illuminated headset key
- Illuminated hands-free speakerphone key

Yealink T41P IP Phone (SIP-T41P)

Interface

- 2xRJ45 10/100M Ethernet ports
- 1xRJ9 (4P4C) handset port
- 1xRJ9 (4P4C) headset port
- Power over Ethernet (IEEE 802.3af), Class 2

Other Physical Features

- Stand with 2 adjustable angles
- Wall mountable
- External Universal AC Adapter (optional)：AC 100~240V input and DC 5V/1.2A output
- Power consumption (PSU): 1.4W-3.9W
- Dimension(W*D*H*T):212mm*189mm*175mm*54mm
- Operating humidity: 10~95%
- Storage temperature: -10~50°C

Package Features

- Qty/CTN: 5 PCS
- N.W/CTN: 6.9 kg
- G.W/CTN: 7.6 kg
- Giftbox size: 241mm*236mm*138mm
- Carton Meas: 707mm*253mm*244mm

Management

- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- BroadSoft device management
- Zero-sp-touch, SNMP
- Provisioning server redundancy supported
- Reset to factory, Reboot
- Package tracing export, System log

Network Security

- SIP v1 (RFC2543), v2 (RFC3261)
- NAT transverse: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- SRTP for voice and video
- Transport Layer Security (TLS)
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess

Yealink T41P IP Phone (SIP-T41P)

- OpenVPN, IEEE802.1X
- IPv6

Management

- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- BroadSoft device management
- Zero-sp-touch, SNMP
- Provisioning server redundancy supported
- Reset to factory, Reboot
- Package tracing export, System log

Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- NAT transverse: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- SRTP for voice and video
- Transport Layer Security (TLS)
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess
- OpenVPN, IEEE802.1X
- IPv6

Please Enquire

Options available for Yealink T41P IP Phone (SIP-T41P) :

Power Supply Required?

UK PSU required (+£3.99), EU PSU required (+£3.99), None - Using PoE.

RPS Extension ID

TEXT.

RPS Extension Password

TEXT.

RPS Display Name

TEXT.

RPS PBX URL

TEXT.

RPS NAT Enabled

Yealink T41P IP Phone (SIP-T41P)

TEXT.

RPS Outbound Proxy

TEXT.

RPS SIP Port

TEXT.

RPS Enable Outbound Proxy

RPS Own Server URL

RPS Own Server Name

T4x Wall Mount Bracket

Required (+£5.44), Not Required.

Skype For Business License

Required, Not Required.

Compatible Headsets

Not Required, VXI ProSet QD1027 10V (+£74.00), VXI Passport QD1027 10V (+£66.20), VXI ProSet QD1027 21V (+£87.00), Yealink YHS33 IP Headset (+£35.10), VXI Passport QD1027 21V (+£79.20).

Compatible Wireless Headsets

Plantronics CS540 EHS Wireless headset (+£190.06), Not Required.

Headset Adapter

Yealink EHS36 (+£36.70), Not Required.