

Yealink EXP40 IP Phone Expansion Module



Product Name: Yealink EXP40 IP Phone Expansion Module

Manufacturer: Yealink Model Number: EXP40

Yealink EXP40 IP Phone Expansion Module

The Yealink EXP40 Expansion Module is for all compatible SIP-T4x Yealink phones (check

product compatibility on phone page).

Yealink EXP40 IP Phone Expansion Module Key Features

آذِ1⁄2 160x320 graphic LCD with 16-level grayscales

ï¿1/2 LCD Backlight

17.1/2 20 physical keys each with a dual-colour LED

آزٰء Wall mountable

� Supports up to 6 modules daisy-chain

The EXP40 expands the functional capability of your SIP phone to a whole new level. Featuring a large graphic LCD, the EXP40 comes with two pages of 20 flexible buttons that are shown on the display. These can be programmed up to 40 various features, the productivity-enhancing features include BLF/BLA, speed dialing, call forward, transfer, park, pickup, etc.Revolutionary new design New design pursuing tiniest details for matching elegantly with the look and feel of T46G, rubber covers on the feet that contact the desk surface help prevent the phone from sliding. The new foot stand allows two positions for the device, support application of wall mountable, the backlit display eliminates the need for external light.

A rich visual experience for applications

Equipped with a 160x320 graphic LCD with Backlight. 20 physical keys each with a dual-colour LED and two page views are possible, this allows 40 additional programmable keys that can be used for speed dialing, BLF/BLA, call forward, transfer, park, pickup, etc. 2 independent control keys are used for fast switch pages.

Expandability

Supports up to 6 Expansion Modules for an attendant console application, adding up to 240 additional buttons. It must be powered by a conventional power supply (5V/1.2A) if exceeding 3 connections.

Yealink EXP40 IP Phone Expansion Module - Technical Specifications Display

า๊¿½ 160x320 graphic LCD with 16-level grayscales

ï¿1/2 LCD Backlight

� Two page views are possible

าั¿½ Different icons for each function shown on the LCD

Feature Keys and Indicator

� 20 physical keys each with a dual-colour LED

� 20 additional keys through page switch

ī సై 2 independent control keys are used for fast switch pages

آذِ½ Programmable for shared line, BLF List, call park, conference, forward, group pickup, group listening, LDAP, pick UP, XML Browser

Physical Features

ï¿1/2 Wall mountable

ï¿1/2 Stand with 2 adjustable angles

آذِرُ Expansion module (≤2) is powered by the host phone

� Supports up to 6 modules daisy-chain



Yealink EXP40 IP Phone Expansion Module

� 2xRJ12(6P6C)ports for data in and out

آزا 2 Dimensions (W*D*H*T): 127mm*213mm*167mm*45mm Applies to Yealink IP Phone

 \ddot{i} ¿½ Operating temperature: -10~50°C

� Operating humidity: 10-95%

Please Enquire