

Konftel 250 Conferencing Phone



Product Name: Konftel 250 Conferencing Phone

Manufacturer: Konftel

Model Number: 910101065

Konftel 250 Conference Phone

The Konftel 250 Conference Phone delivers excellent user experience without compromising sound quality. It is equipped with Konftel's patented OmniSound 2.0 audio technology, for clear, uninterrupted sound.

Konftel 250 Conference Phone Key Features

- Expandable with additional microphones
- Recording on memory card
- Guide for multiparty calls
- Meeting size: up to 20 people
- OmniSound®

Save your contacts in the phone book and use the conference guide to easily set up multi-party calls or pre-programmed group calls. The Konftel 250 also has a built-in recording function that enables you to record your calls on an SD memory card.

Expandable ConferencingWith it's sleek design, the Konftel 250 fits into any conference room. It's also ideal in larger settings with the addition of optional expansion microphones. Hold productive telephone conference meetings that not only save time, but cut costs too!

Konftel 250 Phone - Technical Specifications

Audio Features

- omniSound® 2.0.
- Microphone : omni-directional, 360°.
- Pickup range: up to 30 m2, > 10 persons.
- Volume: 90 db SPL 0.5 m (RMS).
- frequency response: 200-3400 Hz.
- equalizer: soft, neutral and bright

Connections

- Analogue phone connection: Modular 6/6 RJ11 to a public analogue telecommunication network or an analogue PBX.
- Power supply: AC adapter 100-240 V AC/14 V DC.
- Expansion microphones: modular 4/4.

Directory

- Phonebook: 50 contacts.
- Call groups: 20 groups.

Recording

- Supports SD memory cards up to 2 GB

Anti-Theft protection

- Anti-theft protection: Kensington security slot.

Dimensions

Konftel 250 Conferencing Phone

Size: Diameter 240 mm, height 77 mm

Weight: 1 kg.

Color: Charcoal black.

Display and Keypad

Display: Illuminated graphics ICD, 128x64.

Keypad: Alphanumeric 0-9, *, #, off/R, on, mute, hold, volume up, volume down, 5 buttons for menu navigation, phone book, conference guide.

Regulatory Compliance

Telecommunication: TBR21, 47 CFR Part 68/TIA, IC

CS-03 Issue 1999/01/01.

eMC: en301 489-1,3. en 300 220-1,2, fCC subparts

B and C.

electrical safety: UI 60950-1, en 60950-1:2001.

Environmental Conditions

Temperature: 5° – 40°C.

Relative humidity: 20-80% condensation free.

Warranty

Two years

Price: £306.80