

Polycom CX5100 Unified Conference Station for Microsoft Lync



Product Name: Polycom CX5100 Unified Conference Station for Microsoft Lync

Manufacturer: -

Model Number: 2200-63890-102

Please Note: This item has been discontinued. See the Poly G40-T for an alternative.

Polycom CX5100 Unified Conference Station for Microsoft Lync

The Polycom CX5100 unified conference station offers powerful collaboration capabilities through a unique 360 degree panoramic view of the entire room. Sent at 1080p resolution, and using advanced technology that automatically focuses on the current speaker, the CX5100 enables a richer, more interactive communication.

Polycom CX5100 Key Features

- 360° 1080p USB camera with active speaker detection

- Certified for Skype for Business

- Active speaker and panoramic video stream output

- 20 ft (6 m) microphone pickup range

- 160 Hz – 22 kHz audio processing

- Plug and play

Designed with Skype for Business and Microsoft Lync users in mind, the hands-free, plug and play Polycom CX5100 unified conference station is a truly unique around-the-table video collaboration solution.

Polycom CX5100 - Technical Specifications

Dimensions

• Table Console:

- Footprint (W x D): 369 x 325 mm

- Height: 348 mm (privacy cap closed), 401 mm (privacy cap extended)

- Weight: 2.3 kg (exclusive of cables)

• Power Data Box:

- Size (W x H x D): 209.5 x 300 x 56 mm (excluding stand)

- Weight: 2.9 kg

• Shipping:

- Size (W x H x D): 520 x 430 x 430 mm

- Weight: 9.07 kg

• Power:

- Power consumption: 110 watts, typical

- Universal power supply 100 – 240 V AC, 50 – 60 Hz

Polycom CX5100 Unified Conference Station for Microsoft Lync

Video Performance

• Panoramic video resolutions supported:

• 1920 x 288 pixels (requires USB 3.0 and Lync 2013 or Skype for Business)

• 1280 x 192 pixels (requires USB 3.0 and Lync 2013 or Skype for Business)

• 1056 x 144 pixels

• Active speaker video resolutions supported:

• HD 1080: 1920 x 1080 pixels (requires USB 3.0 & Lync 2013 or Skype for Business)

• HD 720: 1280 x 720 pixels

• VGA: 640 x 480 pixels

• CIF: 352 x 288 pixels

• Frame rate for panoramic and active speaker video, maximum

• 30 frames per second with 60 Hz AC power

• 25 frames per second with 50 Hz AC power

• Maximum frame rates with systems prior to Lync 2013 will be limited to 15 fps (12.5 @ 50 Hz)

Audio Performance

• Console Loudspeaker

• Frequency response: 160 Hz–22 kHz

• Volume: adjustable to 88 dBA SPL (peak) volume at 0.5 meters

• Console microphones -3 microphones for omnidirectional coverage -Frequency response: 160 Hz–22 kHz

• Full Duplex (Class 1) with noise suppression

User Interface

• 3 mute buttons with mute/in-call indication lamps

• Camera on/off indication lamp

• Captive privacy cap with integrated on/off switch for client synch

Console Connectivity

• Proprietary system port for connection to Power Data Box

• USB 3.0 Type A port for proprietary connection to Power Data Box

• USB 3.0 Type B port for connection to PC

• USB 2.0 Type A port for diagnostics/ software update

• 2 extension microphone ports

Polycom CX5100 Unified Conference Station for Microsoft Lync

Power Data Box Connectivity

- Proprietary system port for connection to console
- USB 3.0 Type A interface for proprietary connection to console or to Lync appliance
- USB 2.0 Type A for diagnostics/software update
- Ethernet: RJ-45 10/100/1000 Mbit
- Audio RCA jacks (reserved for future use)
- AC power input

Physical Security

- Kensington-style lock slot on Console and Power Data Box

Extension Microphones (Optional Accessory)

- Frequency response: 160 Hz–22 kHz
- Mute button and indicator lamp Regulatory compliance

Regulatory

- Frequency response: 160 Hz–22 kHz
- Mute button and indicator lamp
- Regulatory compliance
- Safety:

- UL 60950-1
- EN 60950-1
- CSA C22.2 60950-1
- IEC 60950-1
- AS/NZS 60950-1
- GB4943-2011 (China)
- KCC approval (Korea)

EMC:

- CISPR 22 Class B (FCC, ICES, AS/NZS)
- VCCI Class B
- EN 55022 Class B
- EN 55024
- GB9254:2008, YD/T993-1998 (China)
- KCC approval (Korea)
- ANATEL (Brazil)

Environmental Requirements

- Operating temperature: 0–40ºC
- Relative humidity: 15–85% (non-condensing)
- Storage temperature: -40–60ºC
- Recommended room conditions:

Polycom CX5100 Unified Conference Station for Microsoft Lync

- Room reverberation time: RT60 <0.600 seconds
- Ambient noise level: <50 dBA SPL
- Optimal lighting conditions: 300 lux, with a single lighting temperature (no mixed lighting)

Warranty

- 12 months

Included

- Tabletop console with integrated 360° camera
- Power data box with stand
- Quick setup card
- Cables

Price: £4,182.60
