

Yealink T48G IP Phone Skype for Business (SIP-T48G-SFB)



Product Name: Yealink T48G IP Phone Skype for Business (SIP-T48G-SFB)

Manufacturer: Yealink

Model Number: SIP-T48G-SFB

Yealink T48G IP Phone Skype for Business (SIP-T48G-SFB)

Please Note: This product has a lead time of 1-2 days.

Please Note: Yealink T48G IP Phones are PoE (Powered-Over-Ethernet) and do not include a mains Power Supply. If mains power is required, this can be added via the drop down menu above.

The Yealink T48G is an elegant high-level IP Phone that is ideal executives and busy professionals. The Yealink SFB Phone is an exceptional member of the Yealink T4x Series and an excellent choice for professionals who need the features of a high-end modern phone. Yealink T48G IP Phone Key Features

- Dual-port Gigabit Ethernet, Power over Ethernet
- 800 x 480-pixel colour touchscreen with backlight
- HD Voice: HD Codec, HD speaker, HD handset
- 6 VoIP accounts, BLF/BLA, IPV6, Open VPN
- Supports Bluetooth Headsets
- Easy collaboration with Microsoft Skype for Business / Lync

Features include easy collaboration with Microsoft Skype for Business / Lync and outstanding HD audio performance. The Yealink T48G incorporates a USB port allowing Bluetooth headsets to be connected via the Yealink BT40 Bluetooth dongle. Autoprovisioning and manual programming follow the same format as the rest of the Yealink range, making life simpler for installers and technicians.

The Yealink T48GN is a Skype For Business Phone and is certified compatible with 3CX, Asterisk and BroadSoft BroadWorks, along with many more IP PBX and hosted platforms, making it the ideal choice for busy managers.

Please refer to the Yealink VoIP Phone Range Detailed Comparison Table to compare Yealink IP Phones.

Yealink SIP-T48GN Technical Specifications

Audio Features

- HD voice: HD handset, HD speaker
- Codecs: G.722, G.711(Aμ), G.723.1, G.729AB, G.726, iLBC
- DTMF: In-band, Out-of-band(RFC 2833) and SIP INFO Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJB, AGC

Phone Features

- 6 VoIP accounts
- Call hold, mute, DND
- One-touch speed dial, hotline
- Call forward, call waiting, call transfer
- Group listening, emergency call

Yealink T48G IP Phone Skype for Business (SIP-T48G-SFB)

- Redial, call return, auto answer
- 3-way conferencing
- Direct IP call without SIP proxy
- Ringtone selection/import/delete
- Set date time manually or automatically
- Dial plan, XML Browser, action URL/URI

Directory

- Local phonebook up to 1000 entries
- Blacklist
- XML/LDAP remote phonebook
- Intelligent search method
- Phonebook search/import/export
- Call history: dialled/received/missed/forwarded

IP-PBX Features

- Busy Lamp Field (BLF)
- Bridged Line Appearance(BLA)
- Anonymous call, anonymous call rejection
- Remote office, hot-desking
- Message Waiting Indicator (MWI)
- Voicemail, call park, call pickup
- Intercom, paging, music on hold
- Call completion, call recording

Display and Indicator

- 7" 800 x 480-pixel colour touch screen with backlight
- 24 bit depth colour
- LED for call and message waiting indication
- Wallpaper
- Intuitive user interface with icons and soft keys
- National language selection
- Caller ID with name, number and photo

Feature keys

- 29 one-touch DSS keys
- 7 feature keys: message, headset, hold, mute, transfer, redial, hands-free speakerphone
- 6 navigation keys
- Volume control keys
- Illuminated mute key
- Illuminated headset key
- Illuminated hands-free speakerphone key

Interface

- Dual-port Gigabit Ethernet
- Power over Ethernet (IEEE 802.3af), class 3
- Built-in a USB port, support Bluetooth
- headset (Through USB Dongle)
- 1xRJ9 (4P4C) handset port
- 1xRJ9 (4P4C) headset port

Yealink T48G IP Phone Skype for Business (SIP-T48G-SFB)

- 1XRJ12 (6P6C) EXT port:
- Supports up to 6 Expansion Modules for a receptionist console application

Other Physical Features

- Wall mountable (optional)
- External universal AC adapter (optional):
- AC 100~240V input and DC 5V/2A output
- Power consumption (PSU): 2.0-6.4W
- Power consumption (PoE): 2.4-10.5W
- Dimension(W*D*H*T):
- 266mm*226mm*185mm*54mm
- Operating humidity: 10~95%
- Storage temperature: -10~50°C

Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- Call server redundancy supported
- NAT transverse: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP/PPPoE
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- SRTP for voice
- Transport Layer Security (TLS)
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess
- OpenVPN, IEEE802.1X
- IPv6

Price: £157.85

Options available for Yealink T48G IP Phone Skype for Business (SIP-T48G-SFB) :

Power Supply Required?

[UK PSU 10V Required \(+£10.00\)](#), [None - Using PoE](#), [EU PSU required \(+£10.00\)](#).

RPS Extension ID

[TEXT.](#)

RPS Extension Password

[TEXT.](#)

RPS Display Name

[TEXT.](#)

RPS PBX URL

[TEXT.](#)

Yealink T48G IP Phone Skype for Business (SIP-T48G-SFB)

RPS NAT Enabled

[TEXT.](#)

RPS Outbound Proxy

[TEXT.](#)

RPS SIP Port

[TEXT.](#)

RPS Enable Outbound Proxy

RPS Own Server URL

RPS Own Server Name

T4x Wall Mount Bracket

[Not Required,](#) [Required \(+£7.00\).](#)

Compatible Headsets

[Yealink YHS33 IP Headset \(+£35.10\),](#) [Not Required.](#)

Compatible Wireless Headsets

[Not Required,](#) [Plantronics CS540 EHS Wireless headset \(+£190.06\).](#)

Headset Adapter

[Not Required,](#) [Yealink EHS36 \(+£36.70\).](#)

Bluetooth Module Required?

[Not Required,](#) [Yealink BT40 Bluetooth Module \(+£31.40\).](#)

Wi-Fi USB Dongle

[Not Required,](#) [Yealink WF50 WiFi USB Dongle \(+£26.00\).](#)