

# Konftel 300Wx Wireless Conference Phone



Product Name: Konftel 300Wx Wireless Conference Phone

Manufacturer: Konftel Model Number: 910101078

Konftel 300Wx Wireless Conference Phone

The Konftel 300Wx Wireless Conference Phone allows you to hold conference calls where and when it is convenient – without worrying about phone jacks and power outlets. The rechargeable battery ensures superior performance, with up to 60 hours of talk time, lasting up to a week without recharging.

Konftel 300Wx Key Features

� Rechargeable battery

� Charging cradle

ï¿1/2 Line selector

� Expandable with microphones

� Built-in bridging function

� SD call recording

The Konftel 300Wx supports DECT with GAP/CAT-Iq standard for less interference and clearer conversations. In addition, the 300Wx is easily integrated with existing DECT systems for complete coverage. This device can also be easily connected to your mobile phone or computer via a USB for VoIP calls over the internet.

The built-in conference guide helps you dial multi-party calls, store call groups, and initiate reoccurring meetings. The Konftel 300Wx is expandable with microphones, equipped with Konftel's patented OmniSound audio technology for crystal clear sound. Its elegant design makes it a welcome addition in any conference room.

Konftel 300Wx - Technical Specifications Language

آذِ½ Menu and quick guides in Danish, English, Finnish, French, Italian, Dutch, Norwegian, Polish, Spanish, Swedish, Turkish, German and Russian.

# Connections

ī¿½ Konftel 300Wx. DECT 6.0: GAP/CAT-iq compatible, range up to 200 m in open space, 50 m in buildings.

ï¿1/2 Mobile/cell phone: 6/6.

� USB 2.0.

آذًا Konftel DECT base: Analog PBX or PSTN, RJ-11, GAP/CAT-iq compatible.

#### Contacts

� 200 contacts

### Recording

i¿½ Supports recording on SD memory cards up to 2 GB.

# Anti-Theft Protection

� Kensington® security slot.



# Konftel 300Wx Wireless Conference Phone

### Power Supply

آزا Konftel 300Wx. Size: Diameter 9.4 in./240 mm, height 3 in./77 mm. Weight: 2.20lb.

� Konftel DECT base. Size 6.8x6.3 in (175x160 mm), weight 0.53 lb, (240 g).

� Colour: Liquorice black.

#### Display and Keypad

ï¿1/2 Display screen: LCD, 128x64 px (5x2.5").

 $\"{i}\ \emph{\i}\ \emph{\i}$ 

buttons for menu navigation, line mode, conference guide.

#### Approvals

ï¿⅓ Electrical safety:

� IEC 60950-1:2005/A1:2009,

� EN 60950-1:2006/A12:2011,

� EN 60950-1:2006/A1:2010

ï¿1/2 Radio/Tele:

� EN301406,

� ES 203021-1,

� ES 203021-2,

� ES 203021-3,

� EN 301 489-1 V1.9.2,

าั¿½ EN 301489-6 V1.3.1 FCC Part 68, FCC Part 15 subpart D.

#### Operating Environment

تزير Temperature: 23°-104°F/5°–40°C.

រ៉េ $^{1}$ 2 Relative humidity: 20-80% condensation free.

 $\ddot{i}$  5200 mAh, up to 60 h talk time/270 h standby.

# **Declaration of Conformity**

� Charging: AC adapter 100-240 V AC/14 V DC, length 6 m.

īస్ట్ Konftel DECT base: AC adapter 100-240 V AC/6 V DC, length

Price: £420.80