

2N Uni - Surface Mount Box (9153003)



Product Name: 2N Uni - Surface Mount Box (9153003)

Manufacturer: 2N Telecommunications

Model Number: 9153003

Please Note: All 2N products come with a 3-year warranty as standard however, this can be extended up to 5 years. Customers have the option to extend their warranty by either one or two years. To find out more, please [click here](#) or call our sales team on 0330 088 0195.

2N Uni - Surface Mount Box (9153003)

The 2N Uni Surface Mount Box (9153003) is an Aluminum Shroud for the 2N IP Helios Uni. The 2N IP Uni offers the advantages of an IP environment and SIP telephone, while its simple installation allows the use of your existing LAN network. 2N Helios Uni - Surface Mount Box (9153003) Key Features

- Simple installation
- Universal switch output
- Use of existing LAN/WAN network
- Web interface for configuration
- Central administration tool

The 2N IP Uni-Mount Box is an ideal solution for door communication in a regular outdoor and indoor environment, for example at the entrance to an office building or family home. The well-designed construction allows simple installation on the surface or recessed in a wall or plasterboard. The use of IP technology and a SIP protocol gives the intercom a broad range of options for connection to telephone systems. Operation and configuration are simplified by a clear web interface or software application that you can also use to manage more extensive installations with a larger number of intercoms. Use the 2N IP Uni as a solution for controlled access to a building, office or complex. You will be pleasantly surprised by the simplicity of installation and operation, the financial advantages and, not least, the new possibilities for reinforcing security of persons and property within the building.

2N Helios Uni - Surface Mount Box (9153003) Technical Specifications

General

- Power supply:
- 802.3af (PoE)
- 48 V / 380 mA DC
- or
- Adapter
- 230 V ± 10%, 50/60 Hz / 12V DC
- DC power supply 12 V / 1A DC

VoIP:

- Signalling protocol
- SIP
- Number of voice channels: 1
- Audio codecs
- G.711 PCM, 64 kbps

Interface:

- Ethernet

2N Uni - Surface Mount Box (9153003)

- Connector – RJ45
- Transmission speed 10/100 BASE-T
- Relay output
- Maximum voltage 30 V DC
- Maximum current 1 A DC

Other:

- Dimensions
- 7,6" x 4,53" x 1,54"
- Operating temperature
- -40 °C - 131 °C
- Cover level

Price: £81.40
