

## Cyberoam CR25wiNG UTM Firewall 3x3 MIMO technology



Product Name: Cyberoam CR25wiNG UTM Firewall 3x3 MIMO technology

Manufacturer: -

Model Number: CR25wiNG

Please Note: This product has been discontinued. Please see the Sophos XG Firewall XG125W Wifi Appliance.

Please note: Total Value Subscription (TVS) includes: Anti Malware Anti-Spam, Web & Application Filter, Intrusion Prevention System, 8 x 5 Support, Hardware Warranty. If you do not want to purchase a (TVS) Licence please contact us for additional options.

Cyberoam CR25wiNG UTM Firewall 3x3 MIMO technology

The Cyberoam CR25wiNG is the Next-Generation Unified Threat Management appliance with Wi-Fi access points that offer "the fastest UTM's made for SMBs" for small offices with high-performance security over WLAN. Cyberoam CR25wiNG appliances come with 3x3 MIMO technology that greatly enhances wireless range and performance. It supports 802.11a/b/g/n wireless standards. Cyberoam CR25wiNG Features

- Faster performance, broader coverage with 3x3 MIMO Technology
- 3G/4G/WiMAX Connectivity
- Application Visibility & Control
- Multiple Link Management
- Instant Messaging Archiving & Controls
- Anti-Virus/Anti-Spyware

Combined with security over wired networks offered by its range of UTM appliances, Cyberoam enables organisations to overcome the physical limitations of securely accessing network resources and offers more user flexibility, user productivity and lower network ownership costs. The best-in-class hardware along with software to match, enables the NG series to offer unmatched throughput speeds, compared to any other UTM appliance in this market segment. This assures support for future IT trends in organisations like high-speed Internet and rising number of devices in organisations - offering future-ready security for small office networks. Cyberoam's Layer 8 technology that treats user-identity as the 8th Layer or the HUMAN layer in the protocol stack, works even in WLAN environments, to allow Identity-based security policies in dynamic IP environment.

Technical Specifications

Interfaces

- 4 Copper GbE Ports
- Configurable
- Internal/DMZ/WAN Ports
- 1 Console Ports (RJ45/DB9)
- 2 USB Ports

Built-in Wireless LAN

- Wireless Standards - IEEE 802.11 a/b/g/n (WEP, WPA, WPA2, 802.11i, TKIP, AES, PSK)
- Antenna, Detachable 3x3 MIMO
- Access Points, Up to 8 bssid
- Transmit Power (EIRP), 11n HT40 : +15dBm 11b CCK: +15dBm 11g OFDM: +15dBm
- Receiver Sensitivity, -68dBm at 300Mbps -70dBm at 54Mbps. -88dBm at 6Mbps
- Frequency Range , 2.412 GHz - 2.472 GHz, 5.200 GHz - 5.825 GHz

## Cyberoam CR25wiNG UTM Firewall 3x3 MIMO technology

• Number of Selectable Channels, USA (FCC) - 11 channels, EU (ETSI) / Japan (TELEC) - 13 channels

• Data Rate, 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11b: 1, 2, 5.5, 11Mbps 802.11n: up to 450Mbps

### System Performance\*

• Firewall Throughput (UDP) (Mbps) 1,500

• Firewall Throughput (TCP) (Mbps) 1,000

• New sessions/second 5,000

• Concurrent sessions 150,000

• IPSec VPN Throughput (Mbps) 210

• No. of IPSec Tunnels 100

• SSL VPN Throughput (Mbps) 75

• WAF Protected Throughput (Mbps) 45

• Anti-Virus Throughput (Mbps) 300

• IPS Throughput (Mbps) 200

• UTM Throughput (Mbps) 110

### Stateful Inspection Firewall

• Layer 8 (User - Identity) Firewall

• Multiple Security Zones

• Access Control Criteria (ACC) - User - Identity, Source & DestinationZone, MAC and IP address, Service

• UTM policies - IPS, Web Filtering, Application Filtering, Anti-Virus, Anti-Spam and Bandwidth Management

• Layer 7 (Application) Control & Visibility

• Access Scheduling

• Policy based Source & Destination NAT

• H.323, SIP NAT Traversal

• 802.1q VLAN Support

• DoS & DDoS Attack prevention

• MAC & IP-MAC filtering and Spoof prevention

### Gateway Anti-Virus & Anti-Spyware

• Virus, Worm, Trojan Detection & Removal  
Spyware, Malware, Phishing protection  
automatic virus signature database update  
Scans HTTP, HTTPS, FTP, SMTP, POP3, IMAP, IM, VPN Tunnels  
Customize individual user scanning  
Scan and deliver by file size  
Block by file types  
Add disclaimer/signature

### Gateway Anti-Spam

• Inbound/Outbound Scanning

• Real-time Blacklist (RBL), MIME header check

• Filter based on message header, size, sender, recipient

• Subject line tagging

• IP address Black list/White list

• Redirect Spam mails to dedicated email address

• Image-based Spam filtering using RPD Technology

• Zero hour Virus Outbreak Protection

• IP Reputation-based Spam filtering

### Intrusion Prevention System

## Cyberoam CR25wiNG UTM Firewall 3x3 MIMO technology

- Signatures: Default (4500+), Custom
- IPS Policies: Multiple, Custom
- User-based policy creation
- Automatic real-time updates from CRProtect networks
- Protocol Anomaly Detection
- DDoS attack prevention
- SCADA-aware IPS with pre-defined category for ICS and SCADA signatures

### Web Filtering

- Inbuilt Web Category Database
- URL, keyword, File type block
- Categories: Default(82+), Custom
- Protocols supported: HTTP, HTTPS
- Block Malware, Phishing, Pharming URLs
- Schedule-based access control
- Custom block messages per category
- Block Java Applets, Cookies, Active X
- CIPA Compliant
- Data leakage control via HTTP, HTTPS upload

### Application Filtering

- Inbuilt Application Category Database
- 11+ Application Categories: e.g. Gaming, IM, P2P, Proxy
- Schedule-based access control
- Block- P2P applications e.g. Skype-Anonymous proxies e.g. Ultra surf- & Phone home&rdquo; activities
- Layer 7 (Applications) & Layer 8 (User - Identity) Visibility
- Securing SCADA Networks- SCADA/ICS Signature-based Filtering for Protocols -Modbus, DNP3, IEC, Bacnet, Omron FINS, SecureDNP3, Longtalk- Control various Commands and Functions

### Web Application Firewall

- Positive Protection model
- Unique "Intuitive Website Flow Detector" technology
- Protection against SQL Injections, Cross-site Scripting (XSS), Session Hijacking, URL Tampering, Cookie Poisoning
- Support for HTTP 0.9/1.0/1.1
- Extensive Logging & Reporting

### Virtual Private Network

- IPSec, L2TP, PPTP
- Encryption - 3DES, DES, AES, Twofish, Blowfish, Serpent
- Hash Algorithms - MD5, SHA-1
- Authentication - Preshared key, Digital certificates
- IPSec NAT Traversal
- Dead peer detection and PFS support
- Diffie Hellman Groups - 1,2,5,14,15,16
- External Certificate Authority support
- Export Road Warrior connection configuration
- Domain name support for tunnel end points

## Cyberoam CR25wiNG UTM Firewall 3x3 MIMO technology

- VPN connection redundancy
- Overlapping Network support
- Hub & Spoke VPN support

### SSL VPN

- TCP & UDP Tunneling
- Authentication - Active Directory, LDAP, RADIUS, Cyberoam
- Multi-layered Client Authentication - Certificate, Username/Password
- User & Group policy enforcement
- Network access - Split and Full tunneling
- Browser-based (Portal) Access - Clientless access
- Lightweight SSLVPN Tunneling Client
- Granular access control to all the Enterprise Network resources
- Administrative controls - Session timeout, Dead Peer Detection, Portal customization
- TCP-based Application Access - HTTP, HTTPS, RDP, TELNET, SSH

### Instant Messaging (IM) Management

- Yahoo and Windows Live Messenger
- Virus Scanning for IM traffic
- Allow/Block Login
- Allow/Block File Transfer
- Allow/Block Webcam
- Allow/Block one-to-one/group chat
- Content-based blocking
- IM activities Log
- Archive files transferred
- Custom Alerts

### Wireless WAN

- USB port 3G/4G and Wimax Support
- Primary WAN link
- WAN Backup link

### Bandwidth Management

- Application and User Identity based Bandwidth Management
- Guaranteed & Burstable bandwidth policy
- Application & User Identity based Traffic Discovery
- Multi WAN bandwidth reporting
- Category-based bandwidth restriction

### User Identity and Group Based Controls

- Access time restriction
- Time and Data Quota restriction
- Schedule based Committed and Burstable Bandwidth
- Schedule based P2P and IM Controls

### Networking

- Failover - Automated Failover/Failback, Multi-WAN failover, 3G Modem failover
- WRR based load balancing

## Cyberoam CR25wiNG UTM Firewall 3x3 MIMO technology

- Policy routing based on Application and User
- IP Address Assignment - Static, PPPoE, L2TP, PPTP & DDNSClient, Proxy ARP, DHCP server, DHCP relay
- Support for HTTP Proxy
- Dynamic Routing: RIP v1& v2, OSPF, BGP, Multicast Forwarding
- Parent Proxy support with FQDN
- &ldquo;IPv6 Ready&rdquo; Gold Logo

### Administration & System Management

- Web-based configuration wizard
- Role-based access control
- Firmware Upgrades via Web UI
- Web 2.0 compliant UI (HTTPS)
- UI Color Styler
- Command Line Interface (Serial, SSH, Telnet)
- SNMP (v1, v2c, v3)
- Multi-lingual support: Chinese, Hindi, French, Korean
- Cyberoam Central Console (Optional)
- NTP Support

### User Authentication

- Internal database
- Active Directory Integration
- Automatic Windows Single Sign On
- External LDAP/RADIUS database integration
- Thin Client support - Microsoft Windows Server 2003
- Terminal Services and Citrix XenApp
- RSA SecurID support
- External Authentication - Users and Administrators
- User/MAC Binding
- Multiple Authentication servers

### Logging/Monitoring

- Graphical real-time logging and monitoring
- Syslog support
- Log Viewer - Firewall, IPS, Web filter, Anti Virus, Anti Spam, Authentication, System and Admin Events

### On-Appliance Cyberoam-i View Reporting

- Integrated Web-based Reporting tool -Cyberoam-iView
- 1000+ drilldown reports
- 45+ Compliance Reports
- Historical and Real-time reports
- Multiple Dashboards
- Username, Host, Email ID specific Monitoring Dashboard
- Reports - Security, Virus, Spam, Traffic, Policy violations, VPN, Search Engine keywords
- Multi-format reports - tabular, graphical
- Exportable formats - PDF, Excel
- Automated Report Scheduling

### IPSec VPN Client\*\*

## Cyberoam CR25wiNG UTM Firewall 3x3 MIMO technology

- Inter-operability with major IPSec VPN Gateways
- Supported platforms: Windows 2000, WinXP 32/64-bit, Windows 2003 32-bit, Windows 2008 32/64-bit, Windows Vista 32/64-bit, Windows 7 RC1 32/64-bit
- Import Connection configuration

### Certification

- Common Criteria - EAL4+
- ICSA Firewall - Corporate
- Checkmark UTM Level 5 Certification
- VPNC - Basic and AES interoperability
- "IPv6 Ready" Gold Logo

### Hardware Specifications

- Memory 2GB
- Compact Flash 2GB
- HDD 250GB or higher

### Compliance

- CE
- FCC

### Dimensions

- H x W x D (inches) - 1.7 x 6 x 9.1
- H x W x D (cms) - 4.4 x 15.3 x 23.2
- Weight - 2.3kg, 5.07 lbs

### Power

- Input Voltage - 100-240 VAC
- Consumption - 33.5w
- Total Heat Dissipation (BTU) 114

### Environmental

- Operating Temperature - 0 to 40 °C
- Storage Temperature 0 to 75 °C
- Relative Humidity (Non condensing) 10 to 90%

## Please Enquire

Options available for Cyberoam CR25wiNG UTM Firewall 3x3 MIMO technology :

### TVS Licence Required?

Not Required, 1 Year License - TVS-PRC-0025wiNG-01 (+£283.60), 2 Year License - TVS-PRC-0025wiNG-02 (+£496.20), 3 Year License - TVS-PRC-0025wiNG-03 (+£652.20).