

## Cyberoam CR35iNG UTM Firewall



Product Name: Cyberoam CR35iNG UTM Firewall

Manufacturer: -

Model Number: CR35iNG

Please Note: This product has been discontinued. Please see the Sophos XG Firewall XG135 Appliance.

Please note: Total Value Subscription (TVS) includes: Anti Malware Anti-Spam, Web & Application Filter, Intrusion Prevention System, 8 x 5 Support, Hardware Warranty. If you do not want to purchase a (TVS) Licence please contact us for additional options.

### Cyberoam CR35iNG UTM Firewall

The Cyberoam CR35iNG UTM Firewall is a Next-Generation network security appliances that include UTM security features and performance required for future networks. The Cyberoam CR35iNG UTM Firewall for SOHO offer "the fastest UTMs made for SMBs"; to small offices. Cyberoam CR35iNG UTM Firewall Features

• Offering "the fastest UTMs made for SMBs"; to Small Offices

• Cyberoam's Layer 8 Technology

• 3G/4G/WiMAX Connectivity

• Application Visibility & Control

• Instant Messaging Archiving & Controls

• HTTPS/SSL Content Security

The best-in-class hardware along with software to match, enables the NG series to offer unmatched throughput speeds, compared to any other UTM appliance in this market segment. This assures support for future IT trends in organizations like high-speed Internet and rising number of devices in organizations – offering future-ready security for small office networks. With Cyberoam CR35iNG, businesses get assured Security, Connectivity and Productivity. The Layer 8 Technology treats User-Identity as the 8th Layer or the HUMAN layer in the protocol stack. It attaches User-Identity to security, which adds speed to an organization's security by offering instant visibility into the source of attacks by username rather than only IP address. Cyberoam's Extensible Security Architecture (ESA) supports feature enhancements that can be developed rapidly and deployed with minimum efforts, offering future-ready security to organizations.

### Technical Specifications

#### Interfaces

• 6 Copper GbE Ports

• Configurable Internal/DMZ/WAN Ports

• 1 Console Ports (RJ45/DB9)

• 2 USB Ports

#### System Performance\*

• Firewall Throughput (UDP) (Mbps) 2,300

• Firewall Throughput (TCP) (Mbps) 2,000

• New sessions/second 12,000

• Concurrent sessions 350,000

• IPSec VPN Throughput (Mbps) 250

• No. of IPSec Tunnels 150

• SSL VPN Throughput (Mbps) 100

## Cyberoam CR35iNG UTM Firewall

- ½ WAF Protected Throughput (Mbps) 65
- ½ Anti-Virus Throughput (Mbps) 525
- ½ IPS Throughput (Mbps) 350
- ½ UTM Throughput (Mbps) 210

### Stateful Inspection Firewall

- ½ Layer 8 (User - Identity) Firewall
- ½ Multiple Security Zones
- ½ Access Control Criteria (ACC) - User - Identity, Source & Destination Zone, MAC and IP address, Service
- ½ UTM policies - IPS, Web Filtering, Application Filtering, Anti-Virus, Anti-Spam and Bandwidth Management
- ½ Layer 7 (Application) Control & Visibility
- ½ Access Scheduling
- ½ Policy based Source & Destination NAT
- ½ H.323, SIP NAT Traversal
- ½ 802.1q VLAN Support
- ½ DoS & DDoS Attack prevention
- ½ MAC & IP-MAC filtering and Spoof prevention

### Gateway Anti-Virus & Anti-Spyware

- ½ Virus, Worm, Trojan: Detection & Removal
- ½ Spyware, Malware, Phishing protection
- ½ Automatic virus signature database update
- ½ Scans HTTP, HTTPS, FTP, SMTP, POP3, IMAP, IM, VPN Tunnels
- ½ Customize individual user scanning
- ½ Self Service Quarantine area
- ½ Scan and deliver by file size
- ½ Block by file types
- ½ Add disclaimer/signature

### Gateway Anti-Spam

- ½ Inbound/Outbound Scanning
- ½ Real-time Blacklist (RBL), MIME header check
- ½ Filter based on message header, size, sender, recipient
- ½ Subject line tagging
- ½ IP address Black list/White list
- ½ Redirect Spam mails to dedicated email address
- ½ Image-based Spam filtering using RPD Technology
- ½ Zero hour Virus Outbreak Protection
- ½ Self Service Quarantine area
- ½ Spam Notification through Digest
- ½ IP Reputation-based Spam filtering

### Intrusion Prevention System

- ½ Signatures: Default (4500+), Custom
- ½ IPS Policies: Multiple, Custom
- ½ User-based policy creation
- ½ Automatic real-time updates from CRProtect networks
- ½ Protocol Anomaly Detection
- ½ DDoS attack prevention

## Cyberoam CR35iNG UTM Firewall

• SCADA-aware IPS with pre-defined category for ICS and SCADA signatures

### Web Filtering

- Inbuilt Web Category Database
- URL, keyword, File type block
- Categories: Default(82+), Custom
- Protocols supported: HTTP, HTTPS
- Block Malware, Phishing, Pharming URLs
- Schedule-based access control
- Custom block messages per category
- Block JavaApplets, Cookies, Active X
- CIPA Compliant
- Data leakage control via HTTP, HTTPS upload

### Application Filtering

- Inbuilt Application Category Database
- 11+ Application Categories: e.g. Gaming, IM, P2P
- Schedule-based access control
- Block
- P2P applications e.g. Skype
- Anonymous proxies e.g. Ultra surf
- "Phone home" activities
- Layer 7 (Applications) & Layer 8 (User - Identity) Visibility
- Securing SCADA Networks
- SCADA/ICS Signature-based Filtering for Protocols
- Modbus, DNP3, IEC, Bacnet, Omron FINS, SecureDNP3, Longtalk
- Control various Commands and Functions

### Web Application Firewall

- Positive Protection model
- Unique "Intuitive Website Flow Detector" technology
- Protection against SQL Injections, Cross-site Scripting
- (XSS), Session Hijacking, URL Tampering, Cookie Poisoning
- Support for HTTP 0.9/1.0/1.1
- Extensive Logging & Reporting

### Virtual Private Network

- IPSec, L2TP, PPTP
- Encryption - 3DES, DES, AES, Twofish, Blowfish, Serpent
- Hash Algorithms - MD5, SHA-1
- Authentication - Preshared key, Digital certificates
- IPSec NAT Traversal
- Dead peer detection and PFS support
- Diffie Hellman Groups - 1,2,5,14,15,16
- External Certificate Authority support
- Export Road Warrior connection configuration
- Domain name support for tunnel end points
- VPN connection redundancy
- Overlapping Network support
- Hub & Spoke VPN support

## Cyberoam CR35iNG UTM Firewall

### SSL VPN

- TCP & UDP Tunneling
- Authentication - Active Directory, LDAP, RADIUS, Cyberoam
- Multi-layered Client Authentication - Certificate, Username/Password
- User & Group policy enforcement
- Network access - Split and Full tunneling
- Browser-based (Portal) Access - Clientless access
- Lightweight SSLVPN Tunneling Client
- Granular access control to all the Enterprise Network resources
- Administrative controls - Session timeout, Dead Peer Detection, Portal customization
- TCP-based Application Access - HTTP, HTTPS, RDP, TELNET, SSH

### Instant Messaging (IM) Management

- Yahoo and Windows Live Messenger
- Virus Scanning for IM traffic
- Allow/Block Login
- Allow/Block File Transfer
- Allow/Block Webcam
- Allow/Block one-to-one/group chat
- Content-based blocking
- IM activities Log
- Archive files transferred
- Custom Alerts

### Wireless WAN

- USB port 3G/4G and Wimax Support
- Primary WAN link
- WAN Backup link

### Bandwidth Management

- Application and User Identity based Bandwidth Management
- Guaranteed & Burstable bandwidth policy
- Application & User Identity based Traffic Discovery
- Multi WAN bandwidth reporting
- Category-based bandwidth restriction

### User Identity and Group Based Controls

- Access time restriction
- Time and Data Quota restriction
- Schedule based Committed and Burstable Bandwidth
- Schedule based P2P and IM Controls

### Networking

- Failover - Automated Failover/Failback, Multi-WAN failover, 3G Modem failover
- WRR based load balancing
- Policy routing based on Application and User
- IP Address Assignment - Static, PPPoE, L2TP, PPTP & DDNS Client, Proxy ARP, DHCP server, DHCP relay
- Support for HTTP Proxy

## Cyberoam CR35iNG UTM Firewall

- Dynamic Routing: RIP v1&v2, OSPF, BGP, Multicast Forwarding
- Parent Proxy support with FQDN
- "IPv6 Ready" Gold Logo

### High Availability

- Active-Active
- Active-Passive with State Synchronization
- Stateful failover
- Alerts on appliance status change

### Administration & System Management

- Web-based configuration wizard
- Role-based access control
- Firmware Upgrades via Web UI
- Web 2.0 compliant UI (HTTPS)
- UI Color Styler
- Command Line Interface (Serial, SSH, Telnet)
- SNMP (v1, v2c, v3)
- Multi-lingual support: Chinese, Hindi, French, Korean
- Cyberoam Central Console (Optional)
- Network Time Protocol Support

### User Authentication

- Internal database
- Active Directory Integration
- Automatic Windows Single Sign On
- External LDAP/RADIUS database integration
- Thin Client support - Microsoft Windows Server 2003
- Terminal Services and Citrix XenApp
- RSA SecurID support
- External Authentication - Users and Administrators
- User/MAC Binding
- Multiple Authentication servers

### Logging/Monitoring

- Graphical real-time logging and monitoring
- Syslog support
- Log Viewer - Firewall, IPS, Web filter, Anti Virus, Anti Spam, Authentication, System and Admin Events

### On-Appliance Cyberoam-i View Reporting

- Integrated Web-based Reporting tool -Cyberoam-iView
- 1000+ drilldown reports
- 45+ Compliance Reports
- Historical and Real-time reports
- Multiple Dashboards
- Username, Host, Email ID specific Monitoring Dashboard
- Reports - Security, Virus, Spam, Traffic, Policy violations, VPN, Search Engine keywords
- Multi-format reports - tabular, graphical
- Exportable formats - PDF, Excel

## Cyberoam CR35iNG UTM Firewall

• Automated Report Scheduling

IPSec VPN Client\*\*

• Inter-operability with major IPSec VPN Gateways

• Supported platforms: Windows 2000, WinXP 32/64-bit, Windows 2003 32-bit, Windows 2008 32/64-bit, Windows Vista 32/64-bit, Windows 7 RC1 32/64-bit

• Import Connection configuration

Certification

• Common Criteria - EAL4+

• ICSA Firewall - Corporate

• Checkmark UTM Level 5 Certification

• VPNC - Basic and AES interoperability

• "IPv6 Ready" Gold Logo

Hardware Specifications

• Memory 2GB

• Compact Flash 2GB

• HDD 250GB or higher

Compliance

• CE

• FCC

Dimensions

• H x W x D (inches) - 1.7 x 6 x 9.1

• H x W x D (cms) - 4.4 x 15.3 x 23.2

• Weight - 2.3kg, 5.07 lbs

Power

• Input Voltage - 100-240 VAC

• Consumption - 47.8w

• Total Heat Dissipation (BTU) 163

Environmental

• Operating Temperature - 0 to 40 °C

• Storage Temperature -25 to 75 °C

• Relative Humidity (Non condensing) 10 to 90%

**Please Enquire**

Options available for Cyberoam CR35iNG UTM Firewall :

**TVS Licence Required?**

## Cyberoam CR35iNG UTM Firewall

Not Required, 1 Year License - TVS-PRC-0035iNG-01 (+£440.00), 2 Year License - TVS-PRC-0035iNG-02 (+£770.00), 3 Year License - TVS-PRC-0035iNG-03 (+£1,012.00).