

CyberData VoIP Indoor Flush Mount Intercom (011272)



Product Name: CyberData VoIP Indoor Flush Mount Intercom (011272)

Manufacturer: -

Model Number: 011272

Please Note: This product has been discontinued. Please see the CyberData VoIP V3 Outdoor Intercom (011186) and CyberData Flush Mount Kit, 1X (011443).

Cyberdata VoIP Indoor Flush Mount Intercom – Signal White RAL 9003 (011272)
The Cyberdata VoIP Indoor Flush Mount Intercom (011272) is fast to set up, a single LAN cable completes the install. These devices are perfect for settings such as commercial/residential facilities, schools and universities, retail establishments, warehouse and manufacturing plants, SMB, parking garages and shipyards and so much more.
Cyberdata VoIP Indoor Flush Mount Intercom – Signal White RAL 9003 Key Features

- 1/2 Dry Wall Mounting
- 1/2 Direct Cert from: Asterisk, Broadsoft, Cisco, Mitel, NEC to name a few
- 1/2 Faster processor
- 1/2 PoE 802.3af enabled (Powered-over-Ethernet)
- 1/2 SIP compliant
- 1/2 Adaptive full-duplex voice operation
- 1/2 Network web management and firmware download
- 1/2 Network adjustable speaker volume
- 1/2 Network configurable microphone input sensitivity adjustment
- 1/2 Concurrent SIP and multicast paging
- 1/2 Control Relay – network configurable auxiliary relay standard on all models
- 1/2 Door closure and tamper alert signal
- 1/2 Downloadable alert, ringtones and callout messages – Add custom audio files to the board
- 1/2 2 x SIP lines, doubles as a Paging IP speaker
- 1/2 An active call is indicated by the Call Button LED blinking at one second intervals
- 1/2 The Intercom can automatically answer an incoming call

Limitless expansion and no other tied in system parts to procure and install. If your secure entry application needs 2 x VoIP door intercoms, you need 2 ports of POE. The device forms parts of the End Users IP Phone System. Integrate to on-site or hosted VoIP platforms. IP and Mobile Phones operate the on-board relay.

Cyberdata VoIP Indoor Flush Mount Intercom – Signal White RAL 9003 - Technical Specifications
General

- 1/2 Ethernet I/F 10/100 Mbps
- 1/2 Protocol SIP RFC 3261 Compatible and InformaCast v4.0 and later
- 1/2 Power Input PoE 802.3af compliant or 8 to 12 VDC at 1000 mA
- 1/2 Payload Types G711, A-law and µ-law
- 1/2 Operating Temperature -40° C to +55° C (-40° F to 131° F)
- 1/2 Dimensions 6.5” x 4.5” x 1.5” (H x W x D)
- 1/2 Boxed Weight 2 lbs.
- 1/2 Warranty 2 years limited
- 1/2 Part Number 011272

Price: £444.60

CyberData VoIP Indoor Flush Mount Intercom (011272)
