

Fanvil C58 IP Phone with PoE



Product Name: Fanvil C58 IP Phone with PoE

Manufacturer: -

Model Number: C58-POE

Fanvil C58 IP Phone with PoE

Please Note: The Fanvil C58 IP Phone has been discontinued. For an alternative, we recommend the Fanvil X3-001 IP Phone .

The Fanvil C58 IP Phone with PoE is highly effective designed for a mid-range phone that can be used as an integrated phone or a standalone. It is a business class SIP phone with an integrated dual Ethernet switch, G.722 codec support, supports SRTP, support BLF, and 4 DSS keys. POE is optional.

Fanvil C58 with PoE Key Features

- Vxworks OS
- Support SIP2.0 (RFC3261) and correlative RFCs
- SIP support 2 SIP servers, and backup SIP proxy servers
- Supports SIP UDP / TCP/ TLS
- SIP support SIP domain, SIP authentication (none, basic, MD5) , DNS name of server, Peer to Peer / IP Call
- Large dot matrix LCD display and soft keys make user easier to use
- Soft keys programmable
- Function keys programmable (each key have 2-color led indication)
- Supports RJ-9 headset
- Multi languages displayed

The C Series IP Phones are a Business Grade IP handset with a huge range of features and flexibility. The C Series was designed and built for Enterprise Businesses with its modern design and ergonomic feel. Fanvil Technology Co., Ltd. is a professional developer and manufacturer of VoIP products. Fanvil provides VoIP communication devices solutions for small and medium sized businesses, as well as large mission-critical enterprise environments.

Fanvil C58 with PoE - Technical Specifications

Display

• Display Resolution: 128x48 with Backlight

Audio Features

- HD voice: HD handset
- Codec: G.711A/u, G.7231 high/low, G.729AB, G.722, G.726-32
- DTMF: In-band, RFC 2833 and SIP INFO
- Full duplex hands-free speaker phone with acoustic echo cancellation
- Voice Activity Detection (VAD)
- Comfort Noise Generation (CNG)
- Background noise suppression
- Adaptive jitter buffers
- Packet loss concealment
- SRTP
- mute

Advanced Features

Fanvil C58 IP Phone with PoE

- Call forwarding (busy/ no answer/ always)
- Call transfer (unattended/ attended/ semi-attended)
- Call holding
- Call waiting
- 3 way call conference
- Capable of 10 way conversation
- BLF list
- Join call
- Call pickup
- Call park
- Redial
- Call back
- Call completion
- Hot desking
- Auto redial
- Predial
- SIP messaging , MWI
- Flexible dial plan
- Barring function for outgoing calls
- Do not disturb
- Auto answer
- Caller ID display
- CLIR(rejects anonymous calls)
- CLIP(to make an anonymous call)
- Dial without registration
- Call logs with missed calls/ incoming calls/outgoing calls. Each support 300 records
- Phonebook 500 records
- Speed Dial (abbreviated dialing)
- Hotline/Warm-line
- Call rejection
- Black List/ White List
- Intercom/Intercom barge
- Password dial, DTMF hidden
- Action URL/ active URI
- Voice codec setting for each SIP line
- Multicast
- LDAP, XML phonebook
- Web dial
- Keypad lock, Emergency call

Network/ Security Features

- WAN / LAN:10/100M Ethernet ports
- Bridge mode and route
- PPPoE for xDSL
- 802.3af POE(optional)
- VLAN(Voice VLAN/Data VLAN)
- 802.1X
- NAT (NAPT)
- NAT transverse :Support STUN client
- DHCP client on WAN/ DHCP server on LAN
- Main DNS and secondary DNS server
- DNS Relay
- SNTP Client

Fanvil C58 IP Phone with PoE

• Firewall and DMZ
• Web management access restricted
• VPN(L2TP/Open VPN)
• ping, tracert, telnet

Maintenance & Management

• WEB ,telnet and LCD menu management
• Management with different account right
• Recover firmware and factory reset through POST mode
• Upgrade firmware via HTTP, HTTPS, FTP, TFTP
• DHCP option66 and custom option for auto provisioning
• Auto Provisioning to upgrade configuration file with AES(256) encryption
• TR-069 and Syslog

Physical features

• Adapter Input: AC 100-240V
• Adapter Output: DC 5V/1A
• WAN Port -10/100 BASE-T RJ-45 for LAN
• LAN Port-10/100 BASE-T RJ-45 for PC
• Headset : RJ9
• Power consumption: IDLE: 2.5W Active: 2.8W
• Display Resolution: 128x48 pixels
• Operation Temperature: 0?40?
• Relative Humidity: 10?65%
• Main Chipset : Broadcom
• SDRAM: 16MB
• FLASH: 4MB
• Weight- Phone:0.99kg
• Dimension:235x225x97 mm

Please Enquire