

CyberData Singlewire-enabled InformaCast IP Indoor Flush Mount Intercom (011306)



Product Name: CyberData Singlewire-enabled InformaCast IP Indoor Flush Mount Intercom (011306)

Manufacturer: -

Model Number: 011306

Please Note: This product has been discontinued. Please see the CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom (011309) and CyberData Flush Mount Kit, 1X (011443).

CyberData Singlewire-enabled InformaCast IP Indoor Flush Mount Intercom (011306)
The CyberData Singlewire-enabled InformaCast IP Indoor Flush Mount Intercom is a Powered over Ethernet (PoE 802.3af) VoIP two-way Singlewire compatible communication device CyberData Singlewire-enabled 011306 Key Features

- ï¿⅓ InformaCast compliant
- ī¿½ Used for Access Control, Door Entry Phone, Emergency Phone, Mass Notification
- � Drywall Mounting
- � PoE 802.3af enabled (Powered-over-Ethernet)
- ï¿1/2 SIP compliant
- ï¿1/2 Adaptive full-duplex voice operation
- � Network web management
- 12.1/2 Network adjustable speaker volume and microphone sensitivity
- ï¿1/2 Network downloadable firmware
- า๊¿½ Doubles as a paging speaker: multicast and InformaCast
- تزير Dry relay contact for auxiliary control(controls external power)
- � Door closure and tamper alert signal
- าั¿½ User downloadable alert, rings tones and call out messages

Now supporting Singlewire InformaCast notification messaging as well as a true SIP endpoint, the CyberData Singlewire InformaCast-enabled VoIP Flush Mount Intercom is perfect for settings requiring two-way communication and secure access.

With InformaCast notification messaging and supported Fail-over redundancy, the Singlewire InformaCast-enabled Flush Mount Intercom can be installed in nursing care facilities, schools and universities, daycare facilities, retail establishments, highway tolls, and more, proving this device is truly a versatile, cost-efficient alternative to old analog Intercoms that has the added benefit of Singlewire InformaCast notifications.

CyberData Singlewire-enabled 011306 - Technical Specifications General

- ፲¿½ Protocol SIP RFC 3261 Compatible and InformaCast v4.0 and later
- � Ethernet I/F 10/100 Mbps
- Ti21/2 Power Input PoE 802.3af or 8 to 12 VDC at 1000 mA
- آذِرًا 2 Operating Temperature -40° C to +55° C (-40° F to 131° F)
- � Payload Types G711 A-Law and u-Law
- i¿1/2 Regulatory Compliance FCC Class A, UL 60950
- � Dimension 6.5" x 4.5" x 1.5" (H x W x D)
- ï¿1/2 Boxed Weight 2 lbs (0.9kg)
- � Warranty 2 Year Limited
- ï¿1/2 Part Number 011306



CyberData Singlewire-enabled InformaCast IP Indoor Flush Mount Intercom (011306)

Price: £470.40