

Yealink T23G IP Phone (SIP-T23G)



Product Name: Yealink T23G IP Phone (SIP-T23G)

Manufacturer: Yealink

Model Number: SIP-T23G

Yealink T23G VoIP Phone (SIP-T23G)

Please Note: The Yealink T23G does not come with a power supply. If you require one, please select this from the drop-down box above.

The Yealink T23G IP Phone features an intuitive user interface and enhanced functionality, making it easy for people to interact and maximise productivity. As a cost-effective IP solution, the T23G helps users to streamline business processes, deliver a powerful, secure and consistent communication experience for small and large office environments.

Yealink T23G Key Features

- Up to 3 SIP accounts
- 132x64-pixel graphical LCD
- Dual-port Gigabit Ethernet
- Yealink HD Voice
- PoE support
- Supports Dual-color LEDs
- Headset support
- Wall mountable
- IPv6 support
- Paperless design
- Simple, flexible and secure provisioning options

The T23G features Yealink HD technology which enables rich, clear, life-like voice communications, outsourced management options, flexible deployment and third-party communications applications.

Yealink T23G VoIP Phone - Technical Specifications

Audio Features

- HD voice: HD handset, HD speaker
- Wideband codec: Opus, G.722
- Narrowband codec: G.711(A/µ), G.729AB, G.726, iLBC
- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJB, AGC

Phone Features

- 3 SIP accounts
- Call hold, mute, DND
- One-touch speed dial, hotline
- Call forward, call waiting, call transfer
- Group listening, SMS
- Redial, call return, auto answer
- Local 3-way conferencing
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Set date time manually or automatically
- Dial plan, off hook hot line

Yealink T23G IP Phone (SIP-T23G)

- XML Browser, Action URL/URI
- Integrated screenshots
- RTCP-XR
- Enhanced DSS Key

Directory

- Local phonebook up to 1000 entries
- Black list
- XML/LDAP remote phonebook
- Smart dialing
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded

IP PBX Features

- Busy Lamp Field (BLF), Bridged Line Appearance (BLA)
- Anonymous call, anonymous call rejection
- Hot-desking, emergency call
- Message Waiting Indicator (MWI)
- Voice mail, call park, call pickup
- Intercom, paging, music on hold
- Call completion, call recording
- Flexible seating
- Executive and Assistant
- Centralized call recording
- Visual voice mail

Display and Indicator

- 132 x 64-pixel graphical LCD with backlight
- LED for call and message waiting indication
- Dual-color (red or green) illuminated LEDs for line status information
- Intuitive user interface with icons and soft keys
- Multilingual user interface
- Caller ID with name and number
- Power saving

Feature Keys

- 3 line keys with LED
- 5 feature keys: message, headset, redial, transfer, hands-free speakerphone
- 6 navigation keys
- Volume control keys

Interface

- Dual-port Gigabit Ethernet
- Power over Ethernet (IEEE 802.3af), class 2
- 1 x RJ9 (4P4C) handset port
- 1 x RJ9 (4P4C) headset port

Other Physical Features

Yealink T23G IP Phone (SIP-T23G)

- Wall mountable
- External Yealink AC adapter (optional)：AC 100~240V input and DC 5V/600mA output
- Power consumption (PSU): 0.7-1.5W
- Power consumption (PoE): 1.0-2.2W
- Dimension (W*D*H*T):209mm*188mm*150mm*41mm
- Operating humidity: 10~95%
- Operating temperature: -10~50°C (+14~122°F)

Management

- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Zero-sp-touch, TR-069
- Phone lock for personal privacy protection
- Reset to factory, reboot
- Package tracing export, system log

Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- Call server redundancy supported
- NAT traversal: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV (RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- SRTP for voice
- Transport Layer Security (TLS)
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess
- OpenVPN, IEEE802.1X
- IPv6
- LLDP/CDP/DHCP VLAN
- ICE

Package Features

- Package content:- Yealink SIP-T23G IP phone- Handset with handset cord- Ethernet Cable (1.5m CAT5E UTP Cable)- Stand- Quick Start Guide- Power Adapter (Optional)

Price: £65.00

Options available for Yealink T23G IP Phone (SIP-T23G) :

Power Supply Required?

EU PSU required (+£3.99), None - Using PoE, UK PSU required (+£3.99).

Yealink T23G IP Phone (SIP-T23G)

RPS Extension ID

TEXT.

RPS Extension Password

TEXT.

RPS Display Name

TEXT.

RPS PBX URL

TEXT.

RPS NAT Enabled

TEXT.

RPS Outbound Proxy

TEXT.

RPS SIP Port

TEXT.

RPS Enable Outbound Proxy

TEXT.

RPS Own Server URL

TEXT.

RPS Own Server Name

TEXT.

Compatible Headsets

Yealink YHS33 IP Headset (+£35.10), Not Required.

Compatible Wireless Headsets

Not Required, Plantronics CS540 EHS Wireless headset (+£190.06).