



Product Name: Grandstream GVR3550 Network Video Recorder NVR

Manufacturer: -

Model Number: GVR3550

Please Note: The GVR3550 has been discontinued. For an alternative, we recommend the GVR3552.

Grandstream GVR3550 Network Video Recorder (NVR)

The Grandstream GVR3550 Network Video Recorder (NVR) offers small to medium businesses (SMBs) and residential users a reliable and easy-to-manage solution for video surveillance recording and monitoring. Grandstream GVR3550 Features

า๊¿½ Up to 24 channels of 720p HD or 12 channels of 1080p HD audio/video real-time recording า๊¿½ Fully customizable recording rules: time based, event based, manual or automatic า๊¿½ Automatic discovery for IP cameras

It provides video recording, indexing, searching and video storage management for up to 24 IP video cameras to allow users to record and monitor their IP video surveillance network using one device. The GVR3550 supports all Grandstream IP Video surveillance cameras and IP Video Encoders/Decoders in addition to all ONVIF compliant IP Cameras. Users can view the live feed of up to 16 cameras simultaneously by connecting the GVR3550 to a TV or computer monitor or through remote access, and can save up to 16TB of video files on the device by connecting up to 4 hard drives.

Grandstream GVR3550 Technical Specifications Video Recording

 $\ddot{i}_{\dot{c}}$ Up to 24 channels (RAID 0 and 7,200rpm HDD) or 16 channels* (RAID 1 or 5,400rpm HDD) of 720p (1280x720) or half the channel density using 1080p Full HD

Total Recording Rate

� Up to 48 Mbps

Recording Modes

ī సైస్ట్ Continuous mode, record by schedule, event triggered or manual

Audio Recording

� Synchronized audio and video recording

Audio Compression

ï¿⅓ G.711 (u-Law and a-Law)

Live View

� Up to 16 channels of VGA, 4 channels of 720p, or 2 channels of 1080p via HDMI or VGA output

Event Trigger

ï¿⅓ Yes



Intelligent Search
تز½ Time & amp; date, motion
Total Storage
� Up to 16TB internally with encryp tion; additional storage available via external eSATA
RAID
� RAID 0 or RAID 1 support
Storage Redundancy
ï¿⅓ Backup to USB
1 x HDMI
Ϊ¿½ 1 x HDMI
VGA Interface
ϊ¿½ 1 x VGA
Network Interface
� 1 x 10/100/1000Mbps auto-sensing RJ45 port
Line-in
Ϊ¿½ 1 x RCA
Line-Out
Ϊ¿½ 1 x RCA
Alarm-In
� Terminal 16 inputs (NO/NC), Vin 2. 5V~12V􀉼lin 2.5mA~30mA
Alarm-Out
ï¿⅓ Terminal 2 outputs (Relay), 0.5A at 125 VAC; 2A at 30 VDC
UPS
� UPS M anagement (pending)
USB Interfaces
� 2 x USB 2.0 host ports
eSATA



� 1 x eSATA port

LED indicators

าั¿1/2 Power, LAN Link/Activity, Hard Drive Activity, fn

Input

រ៉េ្ស 1 IR Remote Control; optional USB m o use and keyboard

RTC

۲¿½ Yes

Internal HDD

าั¿½ Internal HDD Up to 4 3.5" SATA hard drives with maximum 16TB storage (HDD n ot included)

QoS

T¿½ Layer 2 Qo S (802.1Q, 802.1p) (Layer 2 QoS pending) and Layer 3 QoS (ToS, DiffServ, MPLS) coming soon

Network Protocols

ī¿½ TCP/IP/UDP, RTP/RTCP/RTSP, HTTP/HTTPS, ARP, ICMP, DNS/DDNS, DHCP (client and server), Netwo rk Protocols NTP (client and server), SSH, PPPoE, LLDP (pending), 802.1X, ONVIF 2.2

IP Cameras Supported

ï¿⅓ Grandstream GXV36xx cameras, GXV35xx encoders/decoders, & amp; 3rd party ONVIF compliant cameras

Provisioning

آنٰ HTTP, HTTPS, ONVIF

Security

ï¿1/2 HTTPS, 802.1x (pending), SSH

Management

i¿1/2 Syslog, Web Browser, SSH, GSurf Pro (pending)

Universal Power Supply

ï¿1/2 Input:100~240V 50/60Hz Output:12V/5A 60W

Environmental

 \ddot{i} Operation: 0°C to 50°C Storage: -20°C to 60°C (HDDs not included) Humidity: 10% to 90% non-condensing



Physical

� 440mm (W) x 343.5mm (L) x 44mm (H) Package weight: 4052.5g

Mounting

 $\ddot{\imath} \dot{\varsigma} \frac{1}{2}$ 1U rack mount with front brackets

Compliance

 \ddot{i} FCC: Part 15, (CFR 47) Class B CE: EN 55022, EN 55024, EN 61000-3-2, EN 61000-3-3, EN 60950 RCM: AS/NZS CISPR22, AS/NZS CISPR24, AS/NZS 60950 Comply with R & ER, Rohs & ER, Week & Rohs & Roh

Please Enquire