

## Escene Security IP Intercom IS710(v2)



Product Name: Escene Security IP Intercom IS710(v2)

Manufacturer: -

Model Number: IS710

### Escene Security IP Intercom IS710(v2)

The ESCENE IP Intercom IS710 is well developed according to customer requirements and has a classic brushed aluminum casing. It is waterproof, dustproof and extremely tough. Strong compatibility and supporting an extra access swiping card device make it perfect to be used in banks, subways, power plants, mines, prisons, steel companies and so on. It is a highly cost effective choice for customers' projects requirements in this industry.

### Escene Security IP Intercom IS710 Key Features

- IP65 Dustproof and Waterproof
- Aluminium shell and cast iron base for anti-vandalism strength
- High quality voice communication
- Basic VoIP phone functionality
- Support for extra security devices

### Escene Security IP Intercom IS710 - Technical Specifications

#### Phone Features

- Multi-language web support
- 1 SIP account
- Call hold, Call waiting, Call forward
- Call transfer (blind/busy/ask)
- Mute, DnD
- Auto-answer, 3-way conferencing
- 1 DS programmable key (Speedial, Intercom etc.)
- Volume control
- Direct IP call without SIP proxy
- Default Ring tone 1 selection/import/delete
- Custom Warning Ring tone 2
- Selection/import/delete
- Time sting(SNTP/SIP Serv/Manual)
- Support SIP main/standby serv

#### Advanced Features

- 1 key to restore the factory value
- 1 DS programable key(Speedial, Intercom etc.)
- 2 input and 2 output control interfaces to connect other security equipment
- 1 recording interface, 1 custom warning ring tone interface(using Ring tone 2)

#### IP PBX System Integration

- Busy lamp field (BLF), BLF list
- Bridged line appearance (BLA)
- DN & Forward synchronization
- Intercom, Paging, Music on hold
- Call pickup, Dial Plan, Call recording Anonymous call, Anonymous call rejection

#### Physical Features

- 1 DS programable key (Speedial, Intercom etc.)

## Escene Security IP Intercom IS710(v2)

• 1 LED light  
• 1 lighttouch button (Remote factory value)  
• 1x RJ45 10/10M Ethernet port  
• Power adapter: AC 10~240V input and DC 12V/1A output  
• Power over Ethernet, IE 802.3af, class 0  
• Net weight: 0.52KG Gross weight: 0.65KG  
• Dimension: 162x12x40M  
• Operating humidity: 10~95%  
• Storage temperature: up to 60°C

**Please Enquire**

---