

Snom D725 VoIP Phone



Product Name: Snom D725 VoIP Phone

Manufacturer: Snom

Model Number: D725

Please Note: snom IP Phones do not include a mains power supply. If mains power is required, this can be added via the drop down menu above.

Snom D725 VoIP Phone with 12 SIP Accounts

The Snom D725 VoIP Phone supports 4 -line backlit black and white display and has a local directory with 1000 entries. The D725 has 18 programmable keys with multi-colour LEDs for visual call indication providing users increased visibility and efficiency.

Snom D725 VoIP Phone Features

- 12 SIP accounts
- Four-line backlit B/W display
- 18 programmable function keys with built-in LEDs for visual call indication
- Two-port 10/100/1000 Gigabit Ethernet Switch
- PoE support (PSU available separately)
- Local directory with 1000 entries

The USB port opens the D725 up to a choice of functionality enhancing features including the use of a USB corded or Bluetooth headset, connection to the D7 expansion keypad or WiFi. Along with the rest of the snom range, the D715 has an intuitive, user-friendly menu as well as advanced remote management and provisioning capabilities. ConnectivityThe D725 features a Gigabit Ethernet switch to meet the most demanding telephony requirements. Additionally, the USB port enables the use of various accessories, such as USB headsets or WiFi sticks for even more connectivity options. Attaching the D7 expansion module provides users with even more function keys.

Snom D725 - Technical Specifications

Benefits

- Backlit graphical display, 4 lines
- Dual-angle foot stand: 46° and 28°
- Wall mountable (1)
- Wideband hands-free talking (speakerphone)
- Digital Signal Processor (DSP) enhanced audio quality
- 2-port 1-Gigabit Ethernet switch (RJ45) IEEE 802.3
- Power over Ethernet IEEE 802.3af, Class 2
- USB headset-ready (1)
- D7 expansion module-ready (1)
- Support for USB WiFi stick (RT2070/RT3070 chipsets) (1)
- Support for wireless headsets via electronic hook switch (EHS) (1)

Features

- 12 SIP identities / accounts
- XML browser
- Call lists for dialled, received, missed calls
- Local directory with 1000 entries
- Multiple language support
- DTMF in-band / out-of-band / SIP-INFO
- Interoperable with all major IP-PBX platforms

Snom D725 VoIP Phone

Call Features

- Speed dialing
- URL Dialling
- Local dial plan
- Automatic redial on busy
- Call completion (busy/unreachable) (3)
- Caller identification
- Call waiting
- Call blocking (deny list)
- Auto answer
- Hold
- Music on hold (3)
- Handling of up to 12 simultaneous calls
- Blind attend and transfer
- Call forwarding
- 3-way conferencing on the phone
- Extension monitoring, call pickup (3)
- Call park, call unpark (3)
- Multicast paging
- DND mode (do not disturb)
- Keyboard lock
- Client matter code (CMC) (3)
- Unified communications ready

Audio

- Codecs: &middledot; G.711 A-law, μ-law &middledot; G.722 (wideband) &middledot; G.726, G.729AB, GSM 6.10 (FR)
- Built-in assignable ringtones
- Comfort noise generator (CNG)
- Voice activity detection (VAD)

Set-up

- Configurable through web interface
- Provisioning: &middledot; Automatic loading of settings via HTTP/HTTPS/TFTP &middledot; DHCP Options 66/67 &middledot; snom Redirection Service &middledot; Remote management via TR-069 / TR-111

Protocols

- SIP (RFC3261)
- DHCP, NTP
- HTTP / HTTPS / TFTP
- LDAP (Directory)
- Dual Stack IPv4 / IPv6

User Interface

- Localization (language, time, dial tone)
- Red LED for call indication/message waiting
- 4 context-sensitive keys
- 18 programmable line/function keys with multi colour LEDs
- Paper inlay for labelling of function keys

Snom D725 VoIP Phone

- Dedicated keys for: Message, DND, directory, menu, transfer, hold

Security

- HTTPS server/client
- Transport layer security (TLS)
- SRTP (RFC3711), SIPS, RTCP
- VLAN (IEEE 802.1x)
- LLDP-MED, RTCP-XR
- VPN support
- Web interface password protection

Phone features

- Dimensions in millimetres (approx.):
- 238 x 190 x 40 (LxWxD) w/o foot stand
- 238 x 190 x 200/220 mm (LxWxD) with foot stand
- Weight (approx.): device 670g, foot stand 230g
- Input voltage: 5V DC (SELV)
- Power supply: PoE or power adapter 5V DC 10 W (2)
- Handset: 4P4C connector
- Headset connectors:
- Wired: 4P4C connector or USB connector
- Wireless: USB connector or proprietary snom
- 4-pin connector for snom EHS Advanced (1)
- Hearing aid compatible (HAC) handset
- 1 x USB 2.0 host port, Type A, Hi/Full/Low-Speed
- Environmental conditions:
- Ambient temperature: 0°C to 35°C (32°F to 95°F)
- Storage temperature: -10°C to 45°C (14°F to 113°F)
- Humidity: 5% to 95% (non-condensing)
- Included in delivery:
- Base phone unit
- Footstand
- Handset with cord
- Ethernet cable·
- Quick Start Guide

Price: £118.85

Options available for Snom D725 VoIP Phone :

Power Supply Required?

- Not Required -, 1 x UK Power Supply (+£10.00).

Snom D7 Black Expansion Module Required?

Required (+£91.45), - Not Required -.

Snom A100D Wideband Binaural Headset

Required (+£49.10), - Not Required -.

Snom A100M Wideband Monaural Headset

Snom D725 VoIP Phone

Required (+£43.90), - Not Required -.

Snom A170 Wireless DECT Headset

Required (+£183.10), - Not Required -.