

Gigaset T440 PRO IP PBX



Product Name: Gigaset T440 PRO IP PBX

Manufacturer: -

Model Number: T440PRO-PBX

Gigaset T440 PRO IP PBX

The Gigaset T440 PRO is an efficient and flexible all-in-one platform that provides enterprise communication at SMB level. The T440 is the ideal solution for small businesses looking to cover all their communication needs.

Gigaset T440 Key Features

- max. Number of delegates: 15
- Modern communication server with up to 40 integrated user and voicemail licenses and up to 100 end devices
- Carrier-grade hardware
- Integration of fixed line, mobile and Voice-over-IP (VoIP)
- Intuitive user and administrator interface
- Integrated fax server
- Automatic phone provisioning for Gigaset devices
- One-number concept - be reached anywhere at any time via one number
- Up to 20 simultaneous calls

Up to 40 users can choose from a wide range of options including fixed line, ISDN or VOIP. With the converged network approach, you can lower your communication cost by streamlining and simplifying communication processes. With its comprehensive, professional feature set paired with the intuitive operation and management, the Gigaset T440 PRO platform is the ideal solution for your daily business communication.

Gigaset T440 Technical Specification

Phonebook and dialling

- CallerID for incoming, outgoing and missed calls
- Automatic prefix dialing or provider selection
- Cost-optimized call routing
- Separate private and public address books
- Display of names from the phonebook instead of numbers
- Programmable speed-dial keys
- Click and dial address book
- Alphabetical entries in address book

Receiving calls

- Call redirect for users and groups via web interface: to voicemail, internal or external numbers
- Set up and management of call redirect on web interface
- Simple structure: redirect on busy/timeout • Call queues
- Missed call indicator

Presence and UC

- The following information is available in the personal Call Manager:
- Contact with pictures, call status, DND status, call divert status, call divert target, information about who is talking to whom, and presence information

Computer Telephony Integration (CTI)

- Multiline TAPI (interface to third party)

Gigaset T440 PRO IP PBX

- TAPI 2.1
- Voicemail to email
- Telephone operation via the keypad in the personal section of the web interface
- Fax2Mail

Voicemail

- Integrated voicemail
- Voicemail to email
- Unlimited number of license-free voicemail accounts
- Personalized greetings
- Individual announcements for users/groups (unlimited number)
- Voicemail check via web interface or directly on the phone
- Intuitive menu structure and easy setup

Special features

- Sound quality by G.729, G.711, G.722
- Auto provisioning of Gigaset phones
- Hot desking: login on different telephones with PIN protection
- Music on hold
- Automatic greeting before answer
- Interactive call manager with auto attendant
- Call pick-up
- Time controlled day/night switch
- Presence Status
- Professional User Rights Management
- Centralized PBX features for Gigaset PRO phones: directory, call list, visual voice mail, call divert settings, DND, and more
- Hot Desking
- PBX Call Lists
- Display Number

Fax

- Integrated fax server
- Fax to email (PDF attachment)
- Fax journal
- View fax report via web interface or via email

Conference rooms

- Integrated voicemail
- Voicemail to email
- Unlimited number of license-free voicemail accounts
- Personalized greetings
- Individual announcements for users/groups (unlimited number)
- Voicemail check via web interface or directly on the phone
- Intuitive menu structure and easy setup

Configuration of IP phones

- Programmable function keys
- Central phonebook lookup
- Auto-configuration of Gigaset PRO phones and Polycom® conference phones (IP

Gigaset T440 PRO IP PBX

Soundstation 5000/6000/7000)

Hardware

• 19" 1U casing for easy installation

• 310 mm (L) x 205 mm (D) x 43 mm (H)

• Weight: 2.9 kg

• 100-240 V, max. 260 W internal power supply & Green IT

• Intel® Atom™ N270 1.6GHz, 1 GB RAM, 500 GB HDD SATA for 24/7 use

• 12 LAN Ports incl. PoE, 2 BRI ports, 2 FXS ports, VGA port

• Two year warranty

Environmental conditions

• Operating temp: 5°C to +40°C

• Storage temp: -20°C to +55°C

• Relative Humidity: 10 % - 90 % noncondensing

Please Enquire
