Snom M25 DECT Handset



Product Name: Snom M25 DECT Handset
Manufacturer: -
Model Number: M25

Please Note: This product is end of life. For an alternative, see the Snom DECT Phones.

Please Note: The Snom M25 DECT Handset comes with a EU Power Supply and not a UK one.

Snom M25 DECT Handset
The Snom M25 DECT Handset is designed for professional business use. The M25 DECT handset is a hard-working, high quality device that represents an excellent price-performance ratio. Reliable, compact and comfortable to use, the handset relies on easy-to-change and recharge AAA standard batteries providing up to 75 hours on standby and up to 7 hours talk-time. For added ease of use, the new snom cutting-edge user interface is streamlined for speedy and intuitive navigation. The handset can be deployed in both snom DECT solutions with easy configuration on the M700 multicell solution with seamless handover and the M300 single cell base station for flexibility and scalability.
Snom M25 Key Features

ï¿½ TFT colour display
ï¿½ Up to 75 hours standby and 7 hours talktime
ï¿½ Configurable signal LED
ï¿½ Intuitive user interface
ï¿½ 3.5 mm headset jack

Snom M25 - Technical Specifications
Hardware

ï¿½ TFT colour display 1,44” 128 x 128 pixels
ï¿½ 3,5 mm headset jack
ï¿½ Hands-free talking (speakerphone)
ï¿½ Up to 75 hours standby time and 7 hours talktime
ï¿½ 2 x AAA standard batteries
ï¿½ Message LED

Firmware Features

ï¿½ Call lists for dialed, received, missed calls
ï¿½ Directory with 50 entries
ï¿½ Central directory on the base station
ï¿½ Multiple language support
ï¿½ Interoperable with M300 and M700 base stations
ï¿½ Over-the-air firmware update

Call features

ï¿½ Caller identification
ï¿½ Call waiting
ï¿½ Auto answer
ï¿½ Lists of missed, received and dialed calls
ï¿½ Hold
ï¿½ Handling of up to 2 simultaneous calls

Snom M25 DECT Handset

ï¿½ Blind and attended transfer
ï¿½ Keyboard lock
ï¿½ Key tones
ï¿½ Coverage warning

Audio

ï¿½ Codecs: G722 (wideband) G726
ï¿½ 6 built-in assignable ringtones

User Interface

ï¿½ 21 keys (including navigation)
ï¿½ Configurable high-visibility red LED for call indication / message waiting / battery warning
ï¿½ Menu driven interface
ï¿½ Localization (language, time, dial tone)

Security

ï¿½ DECT wireless encryption

Phone Features

ï¿½ Dimensions 134 x 42 x 23 mm
ï¿½ Input voltage: 5V
ï¿½ Hearing aid compatible

Environmental conditions

ï¿½ Ambient temperature: 0° to 40° C (32° to 104°F)
ï¿½ Non-operating temperature: -10° to 45° C
ï¿½ Relative humidity: 5% to 95% noncondensing

Included in delivery

ï¿½ M25 handset with 2 x AAA batteries
ï¿½ M25 charging cradle with power supply
ï¿½ Safety sheet
ï¿½ Color: black
ï¿½ Part number: EU 00003987 US 00003988 AU 00004160

Type approval

ï¿½ EN 301406 (TBR6)
ï¿½ IEC60950 -1 (Safety)
ï¿½ CSA c-CSA-us / UL60950 - 1
ï¿½ EN 301489 (EMC, ESD)
ï¿½ RF (EMF, SAR)
ï¿½ FCC part 15D, conducted & radiated
ï¿½ FCC part 15B
ï¿½ RSS213

Part numbers for compatible base stations

ï¿½ M700: EU 00003928 US 00003929

Snom M25 DECT Handset

ï¿½ M300 (available in M325 single-cell bundle) EU 00003955 US 00003954 AU 00004161

Please Enquire

Options available for Snom M25 DECT Handset :

Need Product Setup / Training / Support?

Required - 1 Hour (+£65.00), Not Required, Required - 30 minutes (+£40.00).