



Product Name: Grandstream GXP1628 Small Business HD IP Phone

Manufacturer: Grandstream Model Number: GXP1628

#### Grandstream GXP1628 Small Business HD IP Phone

The GXP1628 enhances any desktop with an efficient call environment, featuring a user-friendly interface and simple design. It includes a 132x48 backlit LCD screen, 2-line/SIP account keys, and 8 dual-color LCD BLF/speed-dial keys. With dual Gigabit ports and integrated PoE, the GXP1628 is adaptable to various deployment scenarios. Its built-in HD audio and 3 XML programmable soft keys offer additional customization and usability. Grandstream GXP1628 Key Features:

 $\ddot{1}_{2}$  2 SIP accounts, 2 line keys, 3-way conferencing, 3 XML programmable context-sensitive soft keys

121/2 HD audio on speakerphone and handset

� Dual-switched Gigabit ports, integrated PoE

Like all Grandstream IP phones, the GXP1628 is equipped with advanced security encryption technology (SRTP and TLS). It supports a range of automated provisioning options, including zero-configuration with Grandstream's UCM series IP PBXs, encrypted XML files, and TR-069, making mass deployment effortless.

Efficient and User-Friendly Design

The GXP1628 offers an efficient call experience with its simple and easy-to-use interface, featuring a 132x48 backlit LCD screen, 2-line/SIP account keys, and 8 dual-color BLF/speed-dial keys. Its streamlined design makes it perfect for any desktop, providing essential features for smooth communication in a professional setting.

### **Enhanced Connectivity and Audio**

Equipped with dual Gigabit ports and integrated PoE, the GXP1628 ensures fast, reliable connections, making it suitable for a variety of deployment scenarios. The phone also includes HD audio for crystal-clear sound quality and 3 XML programmable soft keys, giving users the flexibility to customize their call experience for improved productivity.

## Secure and Easy Deployment

As with all Grandstream IP phones, the GXP1628 includes advanced security encryption (SRTP and TLS) to safeguard communications. It supports a range of automated provisioning options, such as zero-configuration with Grandstream's UCM series IP PBXs, encrypted XML files, and TR-069, making mass deployment easy and efficient for businesses.

Grandstream GXP1628 Technical Specification Protocols/Standards

ϊ¿½ SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP/RARP, ICMP, DNS (A record,S- RV, NAPTR), DHCP, PPPoE, SSH, TFTP, NTP, STUN, SIMPLE, LLDP-MED, LDAP, TR-069, 802.1x, TLS, SRTP, CDP/SNMP/RTCP-XR

**Network Interfaces** 

Title Dual switched auto sensing 10/100/1000 Mbps ethernet ports, integrated PoE

Graphic Display

ï¿1/2 132 x 48 backlit graphical LCD Display



## Feature Keys

- 17.1/2 2 line keys with dual-colour LED and 2 SIP accounts
- ï¿1/2 3 XML programmable content sensitive soft keys
- � 5 navigation menu keys
- ï¿⅓ 8 BLF keys
- � 13 dedicated function keys for:
- � Mute
- ï¿⅓ Headset
- تز½ Transfer
- � Conference
- ï¿⅓ Send
- � Redial
- ï¿⅓ Speakerphone
- ï¿⅓ Message
- Hold ½';ï
- ï¿1/2 Page/Intercom
- � Record
- ï¿⅓ Home

## Voice Codecs

� Support for G.711μ/a, G.722 (wide-band), G.723, G.726-32, G.729 A/B, iLBC, in-band and out-of-band DTMF (In audio, RFC2833, SIP INFO), VAD, CNG, AEC, PLC, AJB, AGC

## **Telephony Features**

� Hold, transfer, forward (unconditional/no-answer/busy), call park/pickup, 3-way conference, shared-call-appearance (SCA) / bridged-line-appearance (BLA), downloadable phone book (XML, LDAP, up to 1000 items), call waiting, call history (up to 200 records), off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot desking, personalized music ringtones, server redundancy & amp; fail-over

## Headset Jack

تزير RJ9 headset jack (allowing EHS with Plantronics headsets)

#### HD Audio

� Yes, HD Handseet and speakerphone with support for wideband audio.

#### Base Stand

� Yes, 2 angled positions available, wall mountable

## Wall Mountable

ï¿⅓ Yes

## QoS

ï¿1/2 Layer 2 QoS (802.1Q, 802.1P)



ï¿1/2 Layer 3 QoS (ToS, DiffServ, MPLS)

#### Security

� User and administrator access control

� MD5 and MD5-sess based on authentication

ï¿1/2 256-bit AES encrypted configuration file

۲£% TLS ي∕′خï

ï¿⅓ SRTP

ï¿⅓ HTTPS

� 802.1x media access control

### Multi-Language

ī¿½ English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, simplified and traditional Chinese, Korean, Japanese and more

### Upgrade/Provisioning

� Firmware upgrade via TFTP / HTTP / HTTPS, mass provisioning using TR-069 or AES, FTP/FTPS

#### Power & amp; Green Energy Efficiency

� Universal Power Supply Input 100-240VAC 50-60Hz; Output +5VDC, 600mA; PoE: IEEE802.3af Class 2, 3.84W-6.49W; IEEE802.3az (EEE)

#### Physical

آذِ½ Dimension - 220.5mm (L) x 192.5mm (W) x 76mm (H) (with handset)

ï¿⅓ Unit Weight - 0.8kg

ï¿1/2 Package Weight - 1.2kg

### Temperature and Humidity

 $\ddot{\imath}_{\dot{\epsilon}}$  Operation: 0°C to 40°C, Storage: -10°C to 60°C , Humidity: 10% to 90% Non-condensing

## Package Content

T¿½ GXP1628 phone, handset with cord, base stand, network cable, Quick installation guide, brochure and GPL License

## Compliance

ī¿½ FCC: Part 15 (CFR 47) Class B CE: EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, EN60950-1 RCM: AS/ACIF S004; AS/NZS CISPR22/24; AS/NZS 60950; AS/ NZS 60950.1

Price: £49.30



Options available for Grandstream GXP1628 Small Business HD IP Phone :

## **Need Product Setup / Training / Support?**

Required - 1 Hour (+£65.00), Required - 30 minutes (+£40.00), Not Required.

## **Compatible Headsets**

Grandstream GUV3000 HD USB headset (+£35.00), JPL Connect-1 monaural headset and disconnect cord (+£65.20), Grandstream GUV3005 HD USB headset with busy-light (+£68.00), JPLConnect-2 binaural headset and disconnect cord (+£76.25), Not Required.

## **Compatible Wireless Headsets**

Plantronics CS540 EHS Wireless headset (+£190.06), Plantronics CS520 Binaural wireless EHS headset (+£235.89), Not Required.