

Grandstream GXP1615 IP Phone



Product Name: Grandstream GXP1615 IP Phone

Manufacturer: Grandstream Model Number: GXP1615

Grandstream GXP1615 IP Phone

The Grandstream GXP1615 IP Phone is a user-friendly PoE IP phone with an array of features making it a perfect choice small-to-medium businesses (SMBs) and home offices.

Grandstream GXP1615 Key Features

าั¿½ 1 SIP account, 2 line keys, 3-way conferencing, 3 XML programmable context-sensitive soft keys

� Dual-switched 10/100/1000 mbps PoE ports

� EHS support for Plantronics headsets

ï¿1/2 Up to 500 contacts

� Call history up to 200 records

With a 132 x 48 LCD screen, up to 2 call appearances and 3-way conferencing, This IP phone is a trustworthy Linux-based model. Other important specifications such as dual switched 10/100 Mbps ports, multi-language support, Electronic Hook Switch support for Plantronics headsets, call-waiting and 3-way conferencing make up the superb GXP1615 IP Phone. Simple and Efficient Design

The GXP1615 is an easy-to-use IP phone tailored for small business users who need a reliable VoIP solution. It supports 1 line and 2 call appearances, featuring a 2.95-inch LCD screen and 3 XML programmable soft keys for quick customisation. This design ensures a user-friendly experience, making it a great option for everyday communication.

Productivity and Connectivity

The GXP1615 boosts productivity with 3-way voice conferencing, allowing users to collaborate seamlessly. It comes equipped with 10/100 Mbps network ports and integrated PoE, offering flexibility and ease of installation. The phone also supports EHS for Plantronics headsets, enhancing its versatility for different office setups.

Ideal for Small Business Needs

Perfect for small businesses, the GXP1615 combines essential features with simplicity, providing a high-quality and efficient communication tool. With its intuitive interface and practical capabilities, it delivers a cost-effective VoIP solution that enhances daily operations without unnecessary complexity.

Grandstream GXP1615 - Technical Specifications Protocols/Standards

T¿½ SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP/RARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, PPPoE, SSH, TFTP, NTP, STUN, SIMPLE, LLDPMED, LDAP, TR-069, 802.1x, TLS, SRTP, CDP/SNMP/RTCP-XR

Network Interfaces

าั¿½ Dual switched auto-sensing 10/100 Mbps Ethernet ports, integrated PoE (GXP1615 only)

Graphic Display

ï¿1/2 132 x 48 LCD display

Feature Keys



Grandstream GXP1615 IP Phone

� 2 line keys with dual-color LED and 1 SIP account, 3 XML programmable context sensitive soft keys, 5 (navigation, menu) keys. 13 dedicated function keys for PAGE/INTERCOM, PHONEBOOK, MESSAGE, HOME, HOLD, RECORD, MUTE, HEADSET, TRANSFER, CONFERENCE, SEND and REDIAL, SPEAKERPHONE, VOLUME

Voice Codecs

 \ddot{i} Support for G.711µ/a, G.722 (wide-band), G.723,G.726-32, G.729 A/B, iLBC, in-band and out-of-band DTMF (In audio, RFC2833, SIP INFO), VAD, CNG, AEC, PLC, AJB, AGC

Telephony Features

ī¿½ Hold, transfer, forward (unconditional/no-answer/busy), 3-way conferencing, call park/pickup, downloadable phone book (XML, LDAP, up to 500 items), call waiting, call history (up to 200 records), off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot desking, personalized music ringtones, server redundancy & to a superior fail-over

Headset Jack

آذِيً RJ9 headset jack (allowing EHS with Plantronics headsets)

Base Stand

12.1/2 Yes, 2 angled positions available, wall mountable

Wall Mountable

Yes

QoS

آزٰ Layer 2 QoS (802.1Q, 802.1P) and Layer 3 (ToS, DiffServ, MPLS) QoS

Security

� User and administrator level access control, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, TLS, SRTP, HTTPS, 802.1x media access control

Multi-language

 $\ddot{\imath}_{\dot{c}}$ English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, simplified and traditional Chinese, Korean, Japanese and more

Upgrade/Provisioning

� Firmware upgrade via TFTP / HTTP / HTTPS, mass provisioning using TR069 or AES encrypted XML configuration file, FTP/FTPS

Power & amp; Green Energy Efficiency

T¿½ Universal Power Supply Input 100-240VAC 50-60Hz; Output +5VDC, 600mA; PoE: IEEE802.3af Class 2, 3.84W-6.49W; IEEE802.3az (EEE) (GXP1615 Only)

Physical



Grandstream GXP1615 IP Phone

� Dimension: 209mm (L) x 184.5mm (W) x 76.2mm (H) (with handset)

� Unit weight: 0.74kg � Package weight: 1.1kg

Temperature and Humidity

 \ddot{i} Operation: 0°C to 40°C, Storage: -10°C to 60°C , Humidity: 10% to 90% Non-condensing

Package Content

� GXP1610/1615 phone, handset with cord, base stand, universal power supply, network cable, Quick Installation Guide, brochure, GPL License

Compliance

ī¿½ FCC: Part 15 (CFR 47) Class B CE: EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, EN60950-1 RCM: AS/ACIF S004; AS/NZS CISPR22/24; AS/NZS 60950; AS/NZS 60950.1

Price: \$43.79

Options available for Grandstream GXP1615 IP Phone:

Need Product Setup / Training / Support?

Required - 1 Hour (+\$85.48), Required - 30 minutes (+\$52.61), Not Required.

Compatible Headsets

Grandstream GUV3000 HD USB headset (+\$46.03), JPL Connect-1 monaural headset and disconnect cord (+\$85.75), Grandstream GUV3005 HD USB headset with busy-light (+\$89.43), JPLConnect-2 binaural headset and disconnect cord (+\$100.28), Not Required.

Compatible Wireless Headsets

Jabra Pro 920 Mono with remote handset lifter (+\$181.23), Plantronics CS540 EHS Wireless headset (+\$249.95), Jabra GN1000 headset lifter (+\$23.67), Plantronics CS520 Binaural wireless EHS headset (+\$310.23), Not Required.