

## Grandstream GXP1615 IP Phone



Product Name: Grandstream GXP1615 IP Phone

Manufacturer: Grandstream

Model Number: GXP1615

### Grandstream GXP1615 IP Phone

The Grandstream GXP1615 IP Phone is a user-friendly PoE IP phone with an array of features making it a perfect choice small-to-medium businesses (SMBs) and home offices.

### Grandstream GXP1615 Key Features

- 1 SIP account, 2 line keys, 3-way conferencing, 3 XML programmable context-sensitive soft keys
- Dual-switched 10/100/1000 mbps PoE ports
- EHS support for Plantronics headsets
- Up to 500 contacts
- Call history up to 200 records

With a 132 x 48 LCD screen, up to 2 call appearances and 3-way conferencing, This IP phone is a trustworthy Linux-based model. Other important specifications such as dual switched 10/100 Mbps ports, multi-language support, Electronic Hook Switch support for Plantronics headsets, call-waiting and 3-way conferencing make up the superb GXP1615 IP Phone.

### Simple and Efficient Design

The GXP1615 is an easy-to-use IP phone tailored for small business users who need a reliable VoIP solution. It supports 1 line and 2 call appearances, featuring a 2.95-inch LCD screen and 3 XML programmable soft keys for quick customisation. This design ensures a user-friendly experience, making it a great option for everyday communication.

### Productivity and Connectivity

The GXP1615 boosts productivity with 3-way voice conferencing, allowing users to collaborate seamlessly. It comes equipped with 10/100 Mbps network ports and integrated PoE, offering flexibility and ease of installation. The phone also supports EHS for Plantronics headsets, enhancing its versatility for different office setups.

### Ideal for Small Business Needs

Perfect for small businesses, the GXP1615 combines essential features with simplicity, providing a high-quality and efficient communication tool. With its intuitive interface and practical capabilities, it delivers a cost-effective VoIP solution that enhances daily operations without unnecessary complexity.

### Grandstream GXP1615 - Technical Specifications

#### Protocols/Standards

• SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP/RARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, PPPoE, SSH, TFTP, NTP, STUN, SIMPLE, LLDPMED, LDAP, TR-069, 802.1x, TLS, SRTP, CDP/SNMP/RTCP-XR

#### Network Interfaces

• Dual switched auto-sensing 10/100 Mbps Ethernet ports, integrated PoE (GXP1615 only)

#### Graphic Display

• 132 x 48 LCD display

#### Feature Keys

## Grandstream GXP1615 IP Phone

• 2 line keys with dual-color LED and 1 SIP account, 3 XML programmable context sensitive soft keys, 5 (navigation, menu) keys. 13 dedicated function keys for PAGE/INTERCOM, PHONEBOOK, MESSAGE, HOME, HOLD, RECORD, MUTE, HEADSET, TRANSFER, CONFERENCE, SEND and REDIAL, SPEAKERPHONE, VOLUME

### Voice Codecs

• Support for G.711, G.722 (wide-band), G.723, G.726-32, G.729 A/B, iLBC, in-band and out-of-band DTMF (In audio, RFC2833, SIP INFO), VAD, CNG, AEC, PLC, AJS, AGC

### Telephony Features

• Hold, transfer, forward (unconditional/no-answer/busy), 3-way conferencing, call park/pickup, downloadable phone book (XML, LDAP, up to 500 items), call waiting, call history (up to 200 records), off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot desking, personalized music ringtones, server redundancy & fail-over

### Headset Jack

• RJ9 headset jack (allowing EHS with Plantronics headsets)

### Base Stand

• Yes, 2 angled positions available, wall mountable

### Wall Mountable

• Yes

### QoS

• Layer 2 QoS (802.1Q, 802.1P) and Layer 3 (ToS, DiffServ, MPLS) QoS

### Security

• User and administrator level access control, MD5 and MD5-session based authentication, 256-bit AES encrypted configuration file, TLS, SRTP, HTTPS, 802.1x media access control

### Multi-language

• English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, simplified and traditional Chinese, Korean, Japanese and more

### Upgrade/Provisioning

• Firmware upgrade via TFTP / HTTP / HTTPS, mass provisioning using TR069 or AES encrypted XML configuration file, FTP/FTPS

### Power & Green Energy Efficiency

• Universal Power Supply Input 100-240VAC 50-60Hz; Output +5VDC, 600mA; PoE: IEEE802.3af Class 2, 3.84W-6.49W; IEEE802.3az (EEE) (GXP1615 Only)

### Physical

## Grandstream GXP1615 IP Phone

½ Dimension: 209mm (L) x 184.5mm (W) x 76.2mm (H) (with handset)

½ Unit weight: 0.74kg

½ Package weight: 1.1kg

### Temperature and Humidity

½ Operation: 0&deg;C to 40&deg;C, Storage: -10&deg;C to 60&deg;C , Humidity: 10&#65285; to 90% Non-condensing

### Package Content

½ GXP1610/1615 phone, handset with cord, base stand, universal power supply, network cable, Quick Installation Guide, brochure, GPL License

### Compliance

½ FCC: Part 15 (CFR 47) Class B CE : EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, EN60950-1 RCM: AS/ACIF S004; AS/NZS CISPR22/24; AS/NZS 60950; AS/NZS 60950.1

**Price: 38.42EUR**

Options available for Grandstream GXP1615 IP Phone :

### Need Product Setup / Training / Support?

Required - 1 Hour (+74.99EUR), Required - 30 minutes (+46.15EUR), Not Required.

### Compatible Headsets

Grandstream GUV3000 HD USB headset (+40.38EUR), JPL Connect-1 monaural headset and disconnect cord (+75.22EUR), Grandstream GUV3005 HD USB headset with busy-light (+78.45EUR), JPLConnect-2 binaural headset and disconnect cord (+87.97EUR), Not Required.

### Compatible Wireless Headsets

Jabra Pro 920 Mono with remote handset lifter (+158.98EUR), Plantronics CS540 EHS Wireless headset (+219.28EUR), Jabra GN1000 headset lifter (+20.77EUR), Plantronics CS520 Binaural wireless EHS headset (+272.15EUR), Not Required.