

## CyberData Singlewire InformaCast-enabled VoIP Indoor Intercom with Keypad (011307)



Product Name: CyberData Singlewire InformaCast-enabled VoIP Indoor Intercom with Keypad (011307) Manufacturer: -

Model Number: 011307

Please Note: This product has been discontinued. Please see the CyberData VoIP Intercom range.

CyberData Singlewire InformaCast-enabled VoIP Indoor Intercom with Keypad (011307) The CyberData Singlewire InformaCast-enabled VoIP Indoor Intercom with Keypad (011307) is a two-way communication and secure access device that delivers an adaptable, cost-efficient alternative to old analog Intercoms.

CyberData Singlewire InformaCast-enabled VoIP Indoor Intercom with Keypad Key Features

- ï¿1/2 InformaCast compliant
- ïزئ PoE 802.3af enabled (Powered-over-Ethernet)
- ï¿1/2 12-key keypad (with backlit keys)
- ï¿<sup>1</sup>/<sub>2</sub> Programmable speed dial
- ï¿1/2 SIP compliant
- ï¿1/2 Adaptive full-duplex voice operation
- ï¿1/2 Network web management
- � Network adjustable speaker volume and microphone sensitivity
- ï¿1/2 Network downloadable firmware
- i¿1/2 Doubles as a paging speaker: multicast and InformaCast
- ï¿1/2 Dry relay contact for auxiliary control (controls external power)
- ï¿<sup>1</sup>/<sub>2</sub> Door closure and tamper alert signal
- ï¿1/2 User downloadable alert, rings tones and call out messages.

This device is perfect for settings such as commercial/ residential facilities, schools and universities, retail establishments, warehouse and manufacturing plants, parking garages and shipyards, and so much more. It supports Singlewire InformaCast notification messaging as well as a true SIP endpoints.

CyberData Singlewire InformaCast-enabled VoIP Indoor Intercom with Keypad - Technical Specifications

Typical Applications

i¿½ Access control i¿½ Door entry phone i¿½ Emergency phone i¿½ Mass notification

General

ï¿1/2 Ethernet I/F 10/100 Mbps

- i¿1/2 Protocol SIP RFC 3261 Compatible and InformCast v4.0 and later
- ï¿1/2 Power Input PoE 802.3af compliant or 8 to 12 VDC at 1000 mA
- � Operating Temperature -10o C to 50o C (14o F to 122o F)
- ï¿1/2 Payload Types G711, A-law and µ-law
- ï¿1/2 Regulatory Compliance FCC Class A, UL 60950
- ï¿1/2 Dimensions 6.5" x 4.5" x 1.5" (H x W x D)
- ï¿1/2 Boxed Weight 2 lbs.
- ï¿1/2 Warranty 2 years limited



## CyberData Singlewire InformaCast-enabled VoIP Indoor Intercom with Keypad (011307)

ïزار Part Number011307, Wall-Mounted version011308, Flush-Mounted version

Price: £481.60