

CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom (011309)



Product Name: CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom (011309) Manufacturer: CyberData Model Number: 011309

CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom (011309) The CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom (011309) is perfect for settings requiring two-way communication and secure access. CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom Key Features

- ï¿1/2 InformaCast compliant
- ï¿1/2 InformaCast resiliency protocol
- ï¿1/2 IP rating of IP65
- ï¿1/2 Supports SRST (Survivable Remote Site Telephony)
- ï¿1/2 Streamlined case design
- ï¿1/2 Optional Weather Shroud (pictured) for even greater weather protection
- ï¿1/2 PoE 802.3af enabled (Powered-over-Ethernet)
- ï¿¹∕₂ SIP compliant
- ï¿1/2 Adaptive full-duplex voice operation
- i¿1/2 Doubles as a paging speaker: multicast and InformaCast
- i¿1/2 Dry relay contact for auxiliary control (controls external power)
- ï¿¹/₂ Door closure and tamper alert signal
- ï¿1/2 Optional Security Torx screws with driver kit

The new Weather Shroud (pictured) can be purchased separately for even greater weather protection. With InformaCast notification messaging and supported Fail-over redundancy, the Singlewire InformaCast-enabled Outdoor Intercom can be installed in nursing care facilities, schools and universities, daycare facilities, retail establishments, highway tolls, and more, proving this device is truly a versatile, cost-efficient alternative to old analog intercoms that has the added benefit of Singlewire InformaCast notifications.

It supports Singlewire InformaCast notification messaging as well as a true SIP endpoint. CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom - Technical Specifications General

ï¿1/2 Ethernet I/F 10/100 Mbps

- i¿1/2 Protocol SIP RFC 3261 Compatible and InformCast v4.0 and later
- ï¿1/2 Power Input PoE 802.3af compliant or 8 to 12 VDC at 1000 mA
- ï¿1/2 Operating Temperature -40° C to +55° C (-40° F to 131° F)
- ï¿1/2 Payload Types G711, A-law and µ-law
- ï¿¹/₂ Regulatory Compliance FCC Class A, UL 60950
- ï¿¹/₂ Dimensions 5” x 5” x 2.5” (H x W x D)
- ï¿1/2 Warranty 2 years limited
- ï¿1/2 Boxed Weight 2.0 lbs.
- ï¿¹/₂ Part Number 011309 011188 Weather Shroud (sold separately)

Network

ï¿1/2 Network web management

- i¿1/2 Network adjustable speaker volume and microphone sensitivity
- ï¿1/2 Network downloadable firmware



CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom (011309)

Price: \$816.50