

CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom (011309)



Product Name: CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom (011309)

Manufacturer: CyberData Model Number: 011309

CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom (011309)

The CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom (011309) is perfect for settings requiring two-way communication and secure access.

CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom Key Features

- � InformaCast compliant
- ï¿⅓ InformaCast resiliency protocol
- ï¿⅓ IP rating of IP65
- آذِيًا Supports SRST (Survivable Remote Site Telephony)
- � Streamlined case design
- าั¿½ Optional Weather Shroud (pictured) for even greater weather protection
- � PoE 802.3af enabled (Powered-over-Ethernet)
- � SIP compliant
- ï¿1/2 Adaptive full-duplex voice operation
- ī¿½ Doubles as a paging speaker: multicast and InformaCast
- � Dry relay contact for auxiliary control (controls external power)
- � Door closure and tamper alert signal
- 17.1/2 Optional Security Torx screws with driver kit

The new Weather Shroud (pictured) can be purchased separately for even greater weather protection. With InformaCast notification messaging and supported Fail-over redundancy, the Singlewire InformaCast-enabled Outdoor Intercom can be installed in nursing care facilities, schools and universities, daycare facilities, retail establishments, highway tolls, and more, proving this device is truly a versatile, cost-efficient alternative to old analog intercoms that has the added benefit of Singlewire InformaCast notifications.

It supports Singlewire InformaCast notification messaging as well as a true SIP endpoint. CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom - Technical Specifications General

- ï¿1/2 Ethernet I/F 10/100 Mbps
- าั¿½ Protocol SIP RFC 3261 Compatible and InformCast v4.0 and later
- าั¿½ Power Input PoE 802.3af compliant or 8 to 12 VDC at 1000 mA
- آذِرًا 2 Operating Temperature -40° C to +55° C (-40° F to 131° F)
- ï¿1/2 Payload Types G711, A-law and µ-law
- 17.1/2 Regulatory Compliance FCC Class A, UL 60950
- آذِيً Dimensions 5" x 5" x 2.5" (H x W x D)
- � Warranty 2 years limited
- ï¿1/2 Boxed Weight 2.0 lbs.
- i¿½ Part Number 011309 011188 Weather Shroud (sold separately)

Network

- � Network web management
- 12.1/2 Network adjustable speaker volume and microphone sensitivity
- � Network downloadable firmware



CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom (011309)

Price: £615.50