

## Akuvox SDP-R25 Door Phone



Product Name: Akuvox SDP-R25 Door Phone

Manufacturer: -

Model Number: SDP-R25

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

### Akuvox SDP-R25 Door Phone

The Akuvox SDP-R25 is the video door phone, that you can connect with your Akuvox IP Phones for remote unlock control and monitoring. You can operate the indoor handset to communicate with visitors via voice and video, and unlock the door if you wish. It's applicable in apartment, villas, office, building and so on.

### Akuvox SDP-R25 Door Phone Key Features

- Crystal Sound Quality
- Wide Angle Lens and IR LEDS for Night Vision
- Remote Door Opening
- Water Proof

### Akuvox SDP-R25 Door Phone - Technical Specifications

#### Phone Features

- Video Resolution: 320 \* 240, with 20pics per second
- Wide Angle Lens and IR LEDS for Night Vision Crystal Sound Quality
- Remote Door Opening
- Integrated Microphone and Speaker
- Water-proof Outdoor Unit: IP55
- Support all the VoIP Phones

#### IP-PBX Features

- Video Codec: H.264
- Audio Codec: PCMU
- VAD, CNG , Echo Cancellor

#### Security Features

- Support HTTPS (SSL)
- Support Login for Administration
- Sip Over TLS

#### Network Features

- SIP V1(RFC2543), V2(RFC3261)
- Static IP/DHCP for IP Configuration
- 3 DTMF Modes: In-Band, RFC2833, SIP INFO
- HTTP/HTTPS Web Server for Management
- NTP for Auto Time Setting
- TFTP/FTP/HTTP/HTTPS Protocols

#### Administration Features

- Auto Provisioning Using FTP/TFTP/HTTP/HTTPS/PnP

## Akuvox SDP-R25 Door Phone

- Dial through IP PBX Using Phone Number
- Dial through IP PBX Using URL Address
- Configuration Managements with Web, Keypad on the Phone, and Auto Provisioning

### Physical Features

- Camera: 2.0 Mega Pixels
- White Balance: Auto
- Lens: 4.0mm/F2.8
- Viewing Angle (Diagonal): 50
- Minimum Illumination: 1 LUX (without LED Illumination)
- LED: 6 LEDs
- Power Requirement: DC12V
- Operating Temperature: -30 ~ 40°C
- Weight: 180g
- Size (W×H×D): 185\*68\*50 mm

**Please Enquire**

---