

Akuvox SDP-R25 Door Phone



Product Name: Akuvox SDP-R25 Door Phone

Manufacturer: -

Model Number: SDP-R25

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

Akuvox SDP-R25 Door Phone

The Akuvox SDP-R25 is the video door phone, that you can connect with your Akuvox IP Phones for remote unlock control and monitoring. You can operate the indoor handset to communicate with visitors via voice and video, and unlock the door if you wish. It's applicable in apartment, villas, office, building and so on.

Akuvox SDP-R25 Door Phone Key Features

ï¿1/2 Crystal Sound Quality

า๊¿½ Wide Angle Lens and IR LEDS for Night Vision

� Remote Door Opening

آز½ Water Proof

Akuvox SDP-R25 Door Phone - Technical Specifications Phone Features

ï¿1/2 Video Resolution: 320 * 240, with 20pics per second

ī సైస్త Wide Angle Lens and IR LEDs for Night Vision Crystal Sound Quality

� Remote Door Opening

ï¿1/2 Integrated Microphone and Speaker

آذِ1/2 Water-proof Outdoor Unit: IP55

� Support all the VoIP Phones

IP-PBX Features

� Video Codec: H.264 � Audio Codec: PCMU

� VAD, CNG , Echo Canceller

Security Features

� Support HTTPS (SSL)

� Support Login for Administration

ï¿⅓ Sip Over TLS

Network Features

ï¿1/2 SIP V1(RFC2543), V2(RFC3261)

ï¿⅓ Static IP/DHCP for IP Configuration

ï¿1/2 3 DTMF Modes: In-Band, RFC2833, SIP INFO

آزا HTTP/HTTPS Web Server for Management

� NTP for Auto Time Setting

ï¿1/2 TFTP/FTP/HTTP/HTTPS Protocols

Administration Features

า๊¿½ Auto Provisioning Using FTP/TFTP/HTTPS/PnP



Akuvox SDP-R25 Door Phone

- � Dial through IP PBX Using Phone Number
- � Dial through IP PBX Using URL Address
- īപ് Confi guration Managements with Web, Keypad on the Phone, and Auto Provisioning

Physical Features

� Camera: 2.0 Mega Pixels � White Balance: Auto � Lens: 4.0mm/F2.8

آزٰ Viewing Angle (Diagonal): 50

าั¿½ Minimum Illumination: 1 LUX (without LED Illumination)

� LED: 6 LEDs

ï¿1/2 Power Requirement: DC12V

� Operating Temperature: -30 ~ 40ºC

� Weight: 180g

ï¿1/2 Size (W×H×D): 185*68*50 mm

Please Enquire