Akuvox SDP-R29 Door Phone

Product Name: Akuvox SDP-R29 Door Phone
Manufacturer: -
Model Number: SDP-R29

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

Akuvox SDP-R29 SIP Door Phone
The Akuvox SDP-R29 offers users the security that comes with being able to control who comes into a building, along with the ability to verbally and visually confirm their identity. The SDP-R29 enables users to easily monitor an entrance door or gate and offers the peace of mind knowing that the facility is more secure.
Akuvox SDP-R29 Door Phone Key Features

ï¿½ Enables audio and visual monitoring of doors/gates which increases security on residential or commercial premises
ï¿½ Uses the latest H.264 video and G.722 audio codec to provide the highest quality video image and audio clarity
ï¿½ Allows both audio and video communication to an IP phone, mobile client, or softphone
ï¿½ Enables the ability to remotely control the door/gate
ï¿½ Presents information and user navigation options unique to your business
ï¿½ Eliminates the need for personnel to be physically stationed at the door/gate which improves productivity and frees them up to work on other things
ï¿½ Speeds response time to visitors, delivery and service personnel that require access

Akuvox Video IntegrationThe SDP-R29 seamlessly integrates with Akuvox phones and its camera is ideal for working with Akuvox VP-R4X series. The real time video is streamed to the 7” TFT LCD of VP-R47P and VP-R49P and can be viewed at any time. There is no need for any 3rd party software or IP PBX support to view the video stream.
Akuvox SDP-R29 Door Phone - Technical Specifications
Physical & Power

ï¿½ Size: 317x130x23mm (HxWxD)
ï¿½ Weight: 1.34kg
ï¿½ Body material: all-aluminum
ï¿½ Display: 7” IPS LCD
ï¿½ Screen: 7” capacitive touch screen
ï¿½ Camera: 5 Mega pixels, automatic lighting
ï¿½ 12V DC connector
ï¿½ Water-proof & Dust-proof: IP65
ï¿½ Collision-proof: IK06

SIP Endpoint

ï¿½ SIP v1(RFC2543), SIP v2(RFC3261)
ï¿½ Audio codecs: G.711a, G.711μ, G.722
ï¿½ Video codecs: H.263, H.264
ï¿½ Echo Cancellation
ï¿½ Voice Activation Detection
ï¿½ Comfort Noise Generator

Video

Akuvox SDP-R29 Door Phone

ï¿½ Resolution: up to 1080p
ï¿½ Maximum image transfer rate: 1080p - 30fps
ï¿½ Video codecs: H.263, H.264
ï¿½ High intensity white LEDs for picture lighting during dark hours with internal light sensor

Networking

ï¿½ 10/100 Mbps Ethernet connection
ï¿½ DHCP Client or Static IP
ï¿½ Network-Time-Protocol

Door Entry Feature

ï¿½ Android OS for any 3rd party software or customization
ï¿½ Internal DPDT relay for controlling a door opener;
ï¿½ Relays controlled individually by DTMF tones or messages
ï¿½ Multi-way Unlock: IC Card, PassNumber, Guestures
ï¿½ G-sensor for self-defence alarm
ï¿½ Volume control for speaker
ï¿½ Gain control for microphone
ï¿½ Camera permanently optrational, not just during calls
ï¿½ White balance: auto
ï¿½ Viewing angle: 90 °
ï¿½ Auto-night mode with LED illumination
ï¿½ Minimum illumination: 1LUX (without LED illumination)
ï¿½ Max call length setting

Application Scenarios

ï¿½ Office door phone with on-site or hosted IP-PBX
ï¿½ Remote site entry over Internet
ï¿½ Apartment / flat intercom with door access control
ï¿½ Business information or a welcome experience for guests

Please Enquire