

Akuvox SC-R36 SIP IP Camera



Product Name: Akuvox SC-R36 SIP IP Camera

Manufacturer: -

Model Number: SC-R36

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

Akuvox SC-R36 SIP IP Camera

The Akuvox SC-R36 is suitable for military, finance, Electric Power, higher education, medical and other industries where the video surveillance sites require high-definition and low illumination environment.

Akuvox SC-R36 SIP IP Camera Key Features

� 1/3" Progressive Scan CMOS Sensor

ï¿1/2 1.3MP Real Time Video Output

ï¿⅓ HD 720P Video

تز½ Three Streams

آز½ Support PoE

ï¿⅓ 3D DNR

Xii⁄₂ ANR يُاخ

Akuvox SC-R36 SIP IP Camera - Technical Specifications

� 1.3MP Real Time Video Output

آزٰ Minimum Illumination: 0 Lux (IR ON)

آذِ1/2 White Balance: Auto/Indoor/ Outdoor/ ATW

ï¿⅓ Aperture Control: Auto/Menu

تز½ Electronic Shutter: 1s to 1/10,000s

ï¿1/2 AGC: Auto/Menu

ï¿⅓ Infrared Parameters: 15m

ï¿⅓ Support BLC

Features

ï¿1/2 Privacy Masks

ï¿⅓ Motion Detection

ī స్ట్రీ Day-night Convert: IR-CUT double filters with automatic switching

ï¿1/2 Picture Mirror: On/Off

ï¿1/2 Support 2D/3D Digital Noise Reduction

ï¿1/2 Video Codec: H.264

� Video Resolutions: 130W/720P/D1 � Frame Rate:

// /*

. //]]>

,

// /*

//]]>

--

� Three-stream Encoding: Support setting video parameters

 $\ddot{\imath}$ independently in each stream



Akuvox SC-R36 SIP IP Camera

� Audio Coding: G711
� Audio Stream: Bidirectional

Lens

تزر Interface: Manual Adjustment of Focus Lens

ï¿1/2 Focal Length: 2.8~12mm

Network

ï¿1/2 Supported Protocol:

IPv4,TCP/IP,UDP,RTP,RTSP,HTTP,ICMP,FTPS,MTP,DHCP,PPPoE,UPnP,IGMP，:ONVIF

� Security: User authentication and password protection

Interface

า๊¿½ Alarm: 1 channel alarm input/1 channel alarm output

� Local Output: BNC interface

� Micro SD Card

าั¿½ Audio Interface: 3.5" audio input interface and audio output interface

Physical Features

Ti₂½ Work Environment: Temp：-20°C～60°C；Humidity: &le:90%

ï¿1/2 RJ45 10M/100M, AUTOMDI-X EthP,

� Power Supply: DC12V/POE

� Power Consumption: 7W(MAX,IR ON) � Dimension: Φ145(OD)×106(L)mm

ï¿⅓ Weight: 1300g

Please Enquire