Snom D710 VoIP Phone



Product Name: Snom D710 VoIP Phone
Manufacturer: -
Model Number: D710

Please Note: The snom D710 has been discontinued and replaced by the snom D712 IP Phone.

Snom D710 VoIP Phone
The Snom D710 is built from the ground up for HD audio. Its ergonomically designed handset has an advanced speaker and microphone system. By supporting a broad range of codecs, the phone delivers superior, crystalclear call quality in both handset and handsfree use. Intuitive user interface.
Snom D710 Key Features

ï¿½ Wideband audio
ï¿½ 4-line backlit display
ï¿½ 4 context sensitive keys
ï¿½ 5 configurable function keys with LEDs
ï¿½ 4 SIP identities

The D710 features a four-line black and white graphical display. The four context-sensitive keys and an intuitive, user-friendly menu, makes using the D710 easy. Five programmable function keys with built-in LEDs for visual call indication can be configured for a variety of one-touch telephony functions such as speed dial, busy lamp field or presence indication.
Snom D710 - Technical Specifications
Benefits

ï¿½ Backlit graphical display, 4 lines
ï¿½ Dual-angle footstand: 46° and 28°
ï¿½ Wall mountable
ï¿½ Hands-free talking (speakerphone)
ï¿½ Digital Signal Processor (DSP) enhanced audio quality
ï¿½ 2-port 10/100 Mbps Ethernet switch (RJ45)
ï¿½ Power over Ethernet IEEE 802.3af, Class 1
ï¿½ Electronic Hook Switch (EHS)(1) support for wireless headsets

Features

ï¿½ 4 SIP identities / accounts
ï¿½ XML browser
ï¿½ Call lists for dialed, received, missed calls
ï¿½ Local directory with 1000 entries
ï¿½ Multiple language support
ï¿½ DTMF in-band / out-of-band / SIP-INFO
ï¿½ Interoperable with all major IP PBX platforms

Call Features

ï¿½ Speed dialing
ï¿½ URL dialing
ï¿½ Local dial plan
ï¿½ Automatic redial on busy
ï¿½ Call completion (busy/unreachable) (2)
ï¿½ Caller identification

Snom D710 VoIP Phone

ï¿½ Call waiting
ï¿½ Call blocking (deny list)
ï¿½ Auto answer
ï¿½ Hold
ï¿½ Music on hold(2)
ï¿½ Handling of up to 4 simultaneous calls
ï¿½ Blind and attended transfer
ï¿½ Call forwarding
ï¿½ 3-way conferencing on the phone
ï¿½ Extension monitoring, call pickup(2)
ï¿½ Call park, call unpark(2)
ï¿½ Multicast paging
ï¿½ DND mode (do not disturb)
ï¿½ Keyboard lock
ï¿½ Client matter code (CMC)(2)
ï¿½ Unified communications ready

Audio

ï¿½ Codecs:
ï¿½ G.711 A-law, µ-law
ï¿½ G.722 (wideband)
ï¿½ G.726, G.729AB, GSM 6.10 (FR)
ï¿½ Built-in assignable ringtonesComfort Noise Generator (CNG)Voice Activity Detection (VAD)

Setup

ï¿½ Configuration via web interface
ï¿½ Provisioning:Automatic loading of settings via HTTP/HTTPS/TFTPDHCP Options 66/67Snom Redirection ServiceRemote management via TR-069 / TR-111

Security

ï¿½ 802.1X Authentication and EAPOL
ï¿½ Transport layer security (TLS)
ï¿½ SRTP (RFC3711), SIPS, RTCP
ï¿½ HTTPS server/client
ï¿½ Password-protected web interface
ï¿½ VPN support
ï¿½ VLAN (IEEE 802.1Q)
ï¿½ LLDP-MED, RTCP-XR

Please Enquire

Options available for Snom D710 VoIP Phone :

Power Supply Required?

- Not Required -, 1 x UK Power Supply (+£10.00).