

Akuvox SP-R55P IP Phone



Product Name: Akuvox SP-R55P IP Phone

Manufacturer: -

Model Number: SP-R55P

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

Akuvox SP-R55P IP Phone

The Akuvox SP-R55P IP Phone is a high-quality, cost effective solution, ideal for front line staff handling moderate volume of calls through advanced telephony features. The intuitive user interface of the Akuvox SP-R55P makes navigation easy and requires minimal training. Akuvox SP-R55P IP Phone Features

- 1/2 HD Voice
- 1/2 Up to 3 SIP Accounts
- 1/2 Black Acrylic Cover
- 1/2 2.3" Graphical LCD with Backlight
- 1/2 Support 3-way Conference
- 1/2 Fully Compatible with Asterisk, BroadSoft Platform

Akuvox IP Phone SP-R55P - Technical Specifications

Phone Features:

- 1/2 3 Lines (support 3 SIP accounts)
- 1/2 Support Call Waiting, Call Forward, Call Transfer
- 1/2 Call on Hold, Mute, Auto-answer, Redial, DND
- 1/2 Local 3-Way Conference
- 1/2 Volume Adjustable, Ring tones Selectable
- 1/2 Speed Dial, Hotline
- 1/2 Daylight Saving Time
- 1/2 Network Packet Capture
- 1/2 Country Ringtone Signal
- 1/2 Direct IP call
- 1/2 Auto Redial, Call Return
- 1/2 Dial Plan
- 1/2 XML Browser
- 1/2 Hot Desking
- 1/2 Keypad Lock
- 1/2 Action URL/URI
- 1/2 Phonebook (500 entries), Blacklist (100 entries), Call logs (100 entries)
- 1/2 5 Remote Phone Book URL Supported
- 1/2 LDAP
- 1/2 Multi-Language Support

IP-PBX Features:

- 1/2 SMS.Voicemail.MWI Message Notification
- 1/2 Music on hold, Intercom
- 1/2 BLF (Busy Lamp Field)
- 1/2 Call Pickup, Group Call Pickup
- 1/2 Call Recording
- 1/2 Anonymous Call, Anonymous Call Rejection

Akuvox SP-R55P IP Phone

Audio Features:

- 1/2 HD Voice
- 1/2 Wideband Codec: G.722
- 1/2 Narrowband Codec: PCMA, PCMU, G.729, G723_53, G723_63, G726_16, G726_24, G726_32, G726_40
- 1/2 VAD, CNG, Echo Cancellor
- 1/2 Full-Duplex Speakerphone

Security Features:

- 1/2 Support HTTPS (SSL)
- 1/2 Support SRTP for Voice Data Encryption
- 1/2 Support Login for Administration
- 1/2 SIP Over TLS

Network Features:

- 1/2 SIP V1(RFC2543), V2(RFC3261)
- 1/2 Static IP/DHCP for IP configuration
- 1/2 3 DTMF modes: In-Band, RFC2833, SIP INFO
- 1/2 HTTP/HTTPS Web Server for Management
- 1/2 NTP for Auto Time Setting
- 1/2 TFTP/FTP/HTTP/HTTPS Protocols
- 1/2 802.1Q VLAN

Administration Features:

- 1/2 Auto provisioning using FTP/TFTP/HTTP/HTTPS/PnP
- 1/2 Dial through IP PBX Using Phone Number
- 1/2 Dial through IP PBX Using URL Address
- 1/2 Configuration Manamements with Web, Keypad onthe phone and Auto Provisioning
- 1/2 SNMP
- 1/2 TR069

Physical Features:

- 1/2 Audiocodes Chipset
- 1/2 2.3" 132*64 Graphical LCD with Backlight
- 1/2 34 Keys (13 Programmable keys)
- 1/2 4 LED Lights (1 Power Light, 3 Account Lights)
- 1/2 RJ9 Handset Jack and Headset Jack
- 1/2 2 RJ45 10/100M Ethernet Jacks
- 1/2 AC Power Adapter: Input: AC 100-240V; Output: DC 5V/1A
- 1/2 PoE: IEEE 802.3af
- 1/2 Gift Box Size: 248 x 204 x 107 (mm), weight: 1.19 kg

Please Enquire