

# Akuvox SP-R55P IP Phone



Product Name: Akuvox SP-R55P IP Phone

Manufacturer: -

Model Number: SP-R55P

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

#### Akuvox SP-R55P IP Phone

The Akuvox SP-R55P IP Phone is a high-quality, cost effective solution, ideal for front line staff handing moderate volume of calls through advanced telephony features. The intuitive user interface of the Akuvox SP-R55P makes navigation easy and requires minimal training. Akuvox SP-R55P IP Phone Features

ï¿⅓ HD Voice

ï¿1/2 Up to 3 SIP Accounts

ï¿⅓ Black Acrylic Cover

าั¿½ 2.3&Isquo;' 132\*64 Graphical LCD with Backlight

� Support 3-way Conference

าั¿½ Fully Compatible with Asterisk, BroadSoft Platform

Akuvox IP Phone SP-R55P - Technical Specifications Phone Features:

� 3 Lines (support 3 SIP accounts)

آزار Support Call Waiting, Call Forward, Call Transfer

تزار Call on Hold, Mute, Auto-answer, Redial, DND

� Local 3-Way Conference

� Volume Adjustable, Ring tones Selectable

ï¿1/2 Speed Dial, Hotline

� Daylight Saving Time

� Network Packet Capture

� Country Ringtone Signal

� Direct IP call

ï¿⅓ Auto Redial, Call Return

آز½ Dial Plan

ï¿⅓ XML Browser

ï¿1/2 Hot Desking

ï¿1/2 Keypad Lock

ï¿1/2 Action URL/URI

T¿½ Phonebook (500 entries), Blacklist (100 entries), Call logs (100 entries)

� 5 Remote Phone Book URL Supported

� LDAP

� Multi-Language Support

#### **IP-PBX Features:**

ï¿1/2 SMS. Voicemail. MWI Message Notification

ï¿1/2 Music on hold, Intercom

� BLF (Busy Lamp Field)

� Call Pickup, Group Call Pickup

ï¿1/2 Call Recording

� Anonymous Call, Anonymous Call Rejection



# Akuvox SP-R55P IP Phone

#### Audio Features:

� HD Voice

ï¿1/2 Wideband Codec: G.722

آذِ½ Narrowband Codec: PCMA, PCMU, G.729, G723\_53, G723\_63,G726\_16, G726\_24,

G726\_32, G726\_40

� VAD, CNG, Echo Canceller � Full-Duplex Speakerphone

### Security Features:

� Support HTTPS (SSL)

� Support SRTP for Voice Data Encryption

ï¿⅓ Support Login for Administration

ï¿⅓ SIP Over TLS

#### **Network Features:**

ï¿1/2 SIP V1(RFC2543), V2(RFC3261)

ï¿1/2 Static IP/DHCP for IP configuration

آزا 3 DTMF modes: In-Band, RFC2833, SIP INFO

าั¿½ HTTP/HTTPS Web Server for Management

� NTP for Auto Time Setting

� TFTP/FTP/HTTP/HTTPS Protocols

� 802.1Q VLAN

#### Administration Features:

Ti¿1/2 Auto provisioning using FTP/TFTP/HTTPS/PnP

� Dial through IP PBX Using Phone Number

آزٰ Dial through IP PBX Using URL Address

ī¿1/2 Configuration Manamements with Web, Keypad onthe phone and Auto Provisioning

۳¿⅓ SNMP

� TR069

## Physical Features:

ï¿⅓ Audiocodes Chipset

าั¿½ 2.3&Isquo;' 132\*64 Graphical LCD with Backlight

� 34 Keys (13 Programmable keys)

آزٰء 4 LED Lights (1 Power Light, 3 Account Lights)

12/2 RJ9 Handset Jack and Headset Jack

� 2 RJ45 10/100M Ethernet Jacks

i¿½ AC Power Adapter: Input: AC 100-240V; Output: DC 5V/1A

� PoE: IEEE 802.3af

ï¿1/2 Gift Box Size:248 x 204 x 107 (mm), weight: 1.19 kg

## **Please Enquire**