



Product Name: Grandstream GXP2010 IP Phone

Manufacturer: -

Model Number: GXP-2010-B

Please Note: The Grandstream GXP2010 is end of life. For an alternative model, please see the Grandstream GXP2110 IP Phone.

Grandstream GXP2010 IP Phone / VoIP Telephone

The Grandstream GXP2010 IP Phone, ideal as an enterprise IP Telephone.

The Grandstream GXP2010 IP Phone is a next generation 4-line key-system SIP phone that features a large backlit graphical LCD display, 3 XML programmable soft-keys, 18 programmable hard keys, integrated PoE and 4-way conferencing.

Features

12.1/2 Large backlit 240 x 120 pixel graphical LCD display

าั¿½ Up to 22 call appearances with dual-color LED (4 lines with 4 independent SIP accounts and 18 programmable hard keys)

าั¿½ 3 XML programmable context sensitive soft keys, 4-way conference, 2 position stands

าั¿½ High fidelity wideband audio, full duplex speakerphone with advanced acoustic echo cancellation

រ៉េះ/៉ូ Dual switched auto sensing 10/100Mbps network ports with integrated PoE

าั¿½ Automated provisioning for mass deployment, SRTP and TLS for security protection

The Grandstream GXP2010 IP Phone delivers superior audio quality, comprehensive telephony features, automated provisioning, security protection for privacy and broad interoperability with most 3rd party SIP devices and leading SIP telephony platforms.

It is a perfect choice for end users looking for an affordable key-system IP phone.

Grandstream GXP2010 IP Phone Technical Specifications

Protocols and Standards

� SIP RFC3261

� TCP/UDP/IP

� RTP/RTCP

HTTP ½';ï

ARP/RARP

ï¿⅓ ICMP

� DNS (A record and SRV)

ï¿⅓ DHCP

� PPPoE

آز½ TFTP

ï¿⅓ NTP

� STUN

آز½ SIMPLE

Network Interfaces

12.1/2 Dual switched 10/100Mbps ports with integrated PoE

Graphic Display

ï¿1/2 Back-lit 240 x 120 pixels graphical LCD display

Feature Keys



12/2 4 line indicators with dual-color LED and 4 independent SIP accounts

ï¿1/2 18 programmable hard keys with dual-color LED

ï¿1/2 3 XML dynamic context sensitive soft keys

� 5 navigation/menu/volume keys

تزير 11 dedicated function keys for Hold, Speakerphone, Send/Redial, Transfer, Conference,

Mute, Do-not-disturb, Headset, Intercom/Paging, Phonebook and Message (with message indicator)

Voice Codec

� Support for G.723.1 (6.3K), G.729A/B, G.711 u/a-law, G.726, G.722 (wide-band), GSM and iLBC. In-band and out-of-band DTMF (in audio, RFC2833, SIP INFO)

Telephony Features

Hold ⅓¿ï

آز½ Transfer

آز½ Forward

� 4-way conference

ï¿1/2 Bridged-Line-Appearance (BLA)

ï¿1/2 Busy-Lamp-Field (BLF)

آذِر Downloadable Phone Book (XML, LDAP, up to 200 items)

� XML Customization of Screen

ï¿1/2 Call Waiting

� Call Log

آزٰ Off-hook Auto Dial

آز½ Auto Answer

� Click-To-Dial

� Downloadable Ringtones

ï¿1/2 Server Redundancy

ï¿1/2 Fail-over Support

Headset Jack

ï¿1/2 Both RJ11 and 2.5mm jacks

Expansion Module

� Allow up to 2 externally attached expansion modules

QoS

ï¿1/2 Layer 2 (802.1Q, 802.1p)

ï¿1/2 Layer 3 (ToS, DiffServ, MPLS) QoS

Security

� User and administrator level passwords

� MD5 and MD5-sess based authentication

ï¿1/2 AES based secure configuration file

� SRTP

۲LS ½٪ TLS

Multi-language



تزير English, German, Italian, French, Spanish, etc.

Upgrades and Provisioning

ï¿1/2 Firmware upgrade via TFTP/HTTP

� Mass deployment using central secure provisioning file

Power

าั¿½ Universal power adapter (Input: 100-240VAC 50-60Hz; Output: +5VDC, 1.2A, UL certified) included

ï¿1/2 Integrated Power-over-Ethernet (802.3af)

Physical

� 251.5mm(w) x 201.7mm(l) x 77.5mm(h)

� 1.1kg (2.4lbs)

� 2 adjustable foot stands

� Wall mountable

Temperature and Humidity

 � 32 - 104°F / 0 - 40°C

 � 10 - 90% (non-condensing)

Compliance

FCC

CE ½٪ i

� C-Tick

Grandstream IP Phones Comparison Table

Phone

No. of Lines

Display

Prog. Hard Keys

Soft Keys

Ext. Module Support

PoE Support

Ethernet Cable Included

Grandstream GXP2124

4

240 x 120 pixel

24

4



Grandstream GXP2120 6 320 x 160 pixel 7 4

Grandstream GXP2110 4 240 x 120 pixel 18 3

```
Grandstream GXP2100
4
180 x 90 pixel
7
3
```

Grandstream GXP2020 6 320 x 160 pixel 7 4

Grandstream GXP2010 4 240 x 120 pixel 18 3

Grandstream GXP2000 4 130 x 64 pixel



7

Grandstream GXP1450 2 180 x 60 pixel

3

Grandstream GXP1405 2 128 x 40 pixel

3

Grandstream GXP1400 2 128 x 40 pixel

3

Grandstream GXP1200 2 128 x 32 pixel

3

Grandstream GXP285 1 128 x 32 pixel

3



Grandstream GXP280 1 128 x 32 pixel

3

Please Enquire