



Product Name: Yealink T40G IP Phone (SIP-T40G)

Manufacturer: -

Model Number: SIP-T40G

Please Note: Unfortunately the Ubiquiti Yealink T40G IP Phone have been discontinued. Please see Yealink VoIP Phone Range as an alternative.

Yealink T40G IP Phone (SIP-T40G)

Please Note: Yealink T40G IP Phones are PoE (Powered-Over-Ethernet) and do not include a mains Power Supply. If mains power is required, this can be added via the drop down menu above.

The Yealink T40G is an entry-level SIP desk phone with a host of features and advanced capabilities. Support for up to 3 SIP accounts and 2 x Gigabit Ethernet ports for high-speed connectivity are some of the main features business users can expect from this affordable VoIP Phone. Yealink T40G Key Features

ï¿1/2 Up to 3 SIP accounts

าั¿1/2 2.3" 132 x 64-pixel graphical LCD with backlight

� Opus Codec Support

� Dual-port Gigabit Ethernet

آذِرُ Local phone book up to 1000 entries (search/import/export features)

ī¿½ Intuitive user interface with icons and soft keys

าั¿½ 3 programmable line keys with dual-colour illuminated LEDs for line status information

� Paperless label design

� 3-way conference call

Featuring a backlit graphical LCD display and Opus codec support, the T40G has superb audio quality and a rich visual experience. Thanks to its paperless design, it has 3 programmable memory keys for your own customisation, plus 3-way conferencing, BLF's and an intuitive user interface.

Yealink T40G - Technical Specifications Audio Features

� HD voice: HD handset, HD speaker � Wideband codec: Opus, G.722

� Narrowband codec: G.711(A/μ), G.729AB, G.726 � DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO

12.1/2 Full-duplex hands-free speakerphone with AEC

� VAD, CNG, AEC, PLC, AJB, AGC

Phone Features

ï¿1/2 3 VoIP accounts

ï¿1/2 One-touch speed dial, redial

� Call forward, call waiting

ï¿1/2 Call transfer, call hold

i¿1/2 Call return, group listening, SMS

� Mute, auto answer, DND

ï¿1/2 3-way conference call

� Direct IP call without SIP proxy

ï¿1/2 Ring tone selection/import/delete



- 17.1/2 Hotline, emergency call
- ï¿1/2 Set date & amp; time manually or automatically
- آزِہُ Dial Plan
- ï¿⅓ XML Browser
- ï¿⅓ Action URL/URI
- آز½ RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
- ï¿1/2 Enhanced DSS Key

Directory

- � Local phonebook up to 1000 entries
- ï¿⅓ Black list
- � XML/LDAP remote phonebook
- � Smart dialing
- � Phonebook search/import/export
- า๊¿½ Call history: dialed/received/ missed/forwarded

IP-PBX Features

- � Busy Lamp Field (BLF)
- � Bridged Line Appearance(BLA)
- � Anonymous call, anonymous call rejection
- � Hot-desking, voice mail
- � Message Waiting Indicator (MWI)
- � Call park, call pickup
- � Intercom, paging, music on hold
- � Call recording
- ï¿⅓ Flexible seating
- � Executive and Assistant
- ï¿⅓ Centralised call recording
- ï¿⅓ Visual Voice Mail

Display and Indicator

- าั¿½ 2.3" 132x64-pixel graphical LCD with backlight
- � LED for call and message waiting indication
- าั¿½ Dual-color (red or green) illuminated LEDs for line status information
- � Intuitive user interface with icons and soft keys
- ï¿1/2 Multilingual user interface
- � Caller ID with name and number
- آز½ Power saving

Feature keys

- � 3 line keys with LED
- تزير 5 features keys: message, headset, mute, redial, hands-free speakerphone
- ï¿1/2 4 context-sensitive "soft" keys
- � 6 navigation keys
- � 2 volume control keys
- � Mute key
- � Headset key
- ï¿1/2 Hands-free speakerphone key

Interface



- � Dual-port Gigabit Ethernet
- � 1 x RJ9 (4P4C) handset port
- � 1 x RJ9 (4P4C) headset port
- � 1 x RJ12 (6P6C) EHS port
- آزار Power over Ethernet (IEEE 802.3af), Class 2

Other Physical Features

- ï¿1/2 Stand with 2 adjustable angles
- ï¿⅓ Wall mountable
- � External Yealink AC adapter (optional): AC 100~240V input and DC 5V/600mA output
- ï¿1/2 Power consumption (PSU): 0.9-1.3W
- � Power consumption (PoE): 1.1-1.6W
- � Dimension (W*D*H*T): 212mm*189mm*175mm*54mm
- � Operating humidity: 10~95%
- آذِ½ Operating temperature: -10~50°C (+14~122°C)

Management

- تز½ Configuration: browser/phone/ auto-provision
- រ៉េ្យ Auto provision via FTP/TFTP/HTTP/ HTTPS for mass deploy
- ï¿1/2 Auto-provision with PnP
- ï¿1/2 BroadSoft device management
- � Zero-sp-touch TR-069
- � Phone lock for personal privacy protection
- � Reset to factory, reboot
- � Package tracing export, system log

Network and Security

- ï¿1/2 SIP v1 (RFC2543), v2 (RFC3261)
- ï¿1/2 Call server redundancy supported
- � NAT traversal: STUN mode
- � Proxy mode and peer-to-peer SIP link mode
- ï¿1/2 IP assignment: static/DHCP
- ï¿⅓ HTTP/HTTPS web server
- � Time and date synchronization using SNTP
- � UDP/TCP/DNS-SRV(RFC 3263)
- � QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- ï¿⅓ SRTP for voice
- ï¿1/2 Transport Layer Security (TLS)
- ï¿⅓ HTTPS certificate manager
- ï¿1/2 AES encryption for configuration file
- ï¿1/2 Digest authentication using MD5/MD5-sess
- � OpenVPN, IEEE802.1X
- آ¿⅓ IPv6
- � LLDP/CDP/DHCP VLAN
- � ICE

Package Features

T¿½ Package content:- Yealink SIP-T40G IP phone- Handset with handset cord- Ethernet Cable-Stand- Quick Start Guide- Power Adapter (Optional)

� Qty/CTN: 5 PCS � N.W/CTN: 5.7 kg



ï¿⅓ G.W/CTN: 6.4 kg

� Giftbox size: 246mm*223mm*120mm � Carton Meas: 620mm*233mm*258mm

Please Enquire

Options available for Yealink T40G IP Phone (SIP-T40G):

Power Supply Required?

None - Using PoE, UK PSU required (+£7.10).

Compatible Headsets

JPL Connect-1 monaural headset and disconnect cord (+£65.20), Yealink YHS33 IP Headset (+£35.10), JPLConnect-2 binaural headset and disconnect cord (+£76.25), Not Required.

Compatible Wireless Headsets

Plantronics CS540 EHS Wireless headset and adapter (+£215.06), Not Required, Plantronics CS520 Binaural wireless EHS headset and adapter (+£260.89), Jabra Pro 920 Mono with remote handset lifter (+£137.80).

Headset Adapter

Not Required, Yealink EHS36 (+£36.70).

Wall Mount Bracket Required?

Not Required, Required (+£4.70).