# Yealink T40G IP Phone (SIP-T40G)



Product Name: Yealink T40G IP Phone (SIP-T40G)
Manufacturer: -
Model Number: SIP-T40G

Please Note: Unfortunately the Ubiquiti Yealink T40G IP Phone have been discontinued. Please see Yealink VoIP Phone Range as an alternative.

Yealink T40G IP Phone (SIP-T40G)

Please Note: Yealink T40G IP Phones are PoE (Powered-Over-Ethernet) and do not include a mains Power Supply. If mains power is required, this can be added via the drop down menu above.

The Yealink T40G is an entry-level SIP desk phone with a host of features and advanced capabilities. Support for up to 3 SIP accounts and 2 x Gigabit Ethernet ports for high-speed connectivity are some of the main features business users can expect from this affordable VoIP Phone.Yealink T40G Key Features

ï¿½ Up to 3 SIP accounts
ï¿½ 2.3" 132 x 64-pixel graphical LCD with backlight
ï¿½ Opus Codec Support
ï¿½ Dual-port Gigabit Ethernet
ï¿½ Local phone book up to 1000 entries (search/import/export features)
ï¿½ Intuitive user interface with icons and soft keys
ï¿½ 3 programmable line keys with dual-colour illuminated LEDs for line status information
ï¿½ Paperless label design
ï¿½ 3-way conference call

Featuring a backlit graphical LCD display and Opus codec support, the T40G has superb audio quality and a rich visual experience. Thanks to its paperless design, it has 3 programmable memory keys for your own customisation, plus 3-way conferencing, BLF's and an intuitive user interface.
Yealink T40G - Technical Specifications
Audio Features

ï¿½ HD voice: HD handset, HD speaker
ï¿½ Wideband codec: Opus, G.722
ï¿½ Narrowband codec: G.711(A/μ), G.729AB, G.726
ï¿½ DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
ï¿½ Full-duplex hands-free speakerphone with AEC
ï¿½ VAD, CNG, AEC, PLC, AJB, AGC

Phone Features

ï¿½ 3 VoIP accounts
ï¿½ One-touch speed dial, redial
ï¿½ Call forward, call waiting
ï¿½ Call transfer, call hold
ï¿½ Call return, group listening, SMS
ï¿½ Mute, auto answer, DND
ï¿½ 3-way conference call
ï¿½ Direct IP call without SIP proxy
ï¿½ Ring tone selection/import/delete

# Yealink T40G IP Phone (SIP-T40G)

ï¿½ Hotline, emergency call
ï¿½ Set date & time manually or automatically
ï¿½ Dial Plan
ï¿½ XML Browser
ï¿½ Action URL/URI
ï¿½ RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
ï¿½ Enhanced DSS Key

Directory

ï¿½ Local phonebook up to 1000 entries
ï¿½ Black list
ï¿½ XML/LDAP remote phonebook
ï¿½ Smart dialing
ï¿½ Phonebook search/import/export
ï¿½ Call history: dialed/received/ missed/forwarded

IP-PBX Features

ï¿½ Busy Lamp Field (BLF)
ï¿½ Bridged Line Appearance(BLA)
ï¿½ Anonymous call, anonymous call rejection
ï¿½ Hot-desking, voice mail
ï¿½ Message Waiting Indicator (MWI)
ï¿½ Call park, call pickup
ï¿½ Intercom, paging, music on hold
ï¿½ Call recording
ï¿½ Flexible seating
ï¿½ Executive and Assistant
ï¿½ Centralised call recording
ï¿½ Visual Voice Mail

Display and Indicator

ï¿½ 2.3” 132x64-pixel graphical LCD with backlight
ï¿½ LED for call and message waiting indication
ï¿½ Dual-color (red or green) illuminated LEDs for line status information
ï¿½ Intuitive user interface with icons and soft keys
ï¿½ Multilingual user interface
ï¿½ Caller ID with name and number
ï¿½ Power saving

Feature keys

ï¿½ 3 line keys with LED
ï¿½ 5 features keys: message, headset, mute, redial, hands-free speakerphone
ï¿½ 4 context-sensitive “soft” keys
ï¿½ 6 navigation keys
ï¿½ 2 volume control keys
ï¿½ Mute key
ï¿½ Headset key
ï¿½ Hands-free speakerphone key

Interface

# Yealink T40G IP Phone (SIP-T40G)

ï¿½ Dual-port Gigabit Ethernet
ï¿½ 1 x RJ9 (4P4C) handset port
ï¿½ 1 x RJ9 (4P4C) headset port
ï¿½ 1 x RJ12 (6P6C) EHS port
ï¿½ Power over Ethernet (IEEE 802.3af), Class 2

Other Physical Features

ï¿½ Stand with 2 adjustable angles
ï¿½ Wall mountable
ï¿½ External Yealink AC adapter (optional): AC 100~240V input and DC 5V/600mA output
ï¿½ Power consumption (PSU): 0.9-1.3W
ï¿½ Power consumption (PoE): 1.1-1.6W
ï¿½ Dimension (W*D*H*T): 212mm*189mm*175mm*54mm
ï¿½ Operating humidity: 10~95%
ï¿½ Operating temperature: -10~50°C (+14~122°C)

Management

ï¿½ Configuration: browser/phone/ auto-provision
ï¿½ Auto provision via FTP/TFTP/HTTP/ HTTPS for mass deploy
ï¿½ Auto-provision with PnP
ï¿½ BroadSoft device management
ï¿½ Zero-sp-touch TR-069
ï¿½ Phone lock for personal privacy protection
ï¿½ Reset to factory, reboot
ï¿½ Package tracing export, system log

Network and Security

ï¿½ SIP v1 (RFC2543), v2 (RFC3261)
ï¿½ Call server redundancy supported
ï¿½ NAT traversal: STUN mode
ï¿½ Proxy mode and peer-to-peer SIP link mode
ï¿½ IP assignment: static/DHCP
ï¿½ HTTP/HTTPS web server
ï¿½ Time and date synchronization using SNTP
ï¿½ UDP/TCP/DNS-SRV(RFC 3263)
ï¿½ QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
ï¿½ SRTP for voice
ï¿½ Transport Layer Security (TLS)
ï¿½ HTTPS certificate manager
ï¿½ AES encryption for configuration file
ï¿½ Digest authentication using MD5/MD5-sess
ï¿½ OpenVPN, IEEE802.1X
ï¿½ IPv6
ï¿½ LLDP/CDP/DHCP VLAN
ï¿½ ICE

Package Features

ï¿½ Package content:- Yealink SIP-T40G IP phone- Handset with handset cord- Ethernet Cable- Stand- Quick Start Guide- Power Adapter (Optional)
ï¿½ Qty/CTN: 5 PCS
ï¿½ N.W/CTN: 5.7 kg

# Yealink T40G IP Phone (SIP-T40G)

ï¿½ G.W/CTN: 6.4 kg
ï¿½ Giftbox size: 246mm*223mm*120mm
ï¿½ Carton Meas: 620mm*233mm*258mm

**Please Enquire**

Options available for Yealink T40G IP Phone (SIP-T40G) :

### Power Supply Required?

None - Using PoE,  UK PSU required (+£7.10).

### Compatible Headsets

Yealink YHS33 IP Headset (+£35.10),  JPLConnect-2 binaural headset and disconnect cord (+£76.25),  Not Required,  JPL Connect-1 monaural headset and disconnect cord (+£65.20).

### Compatible Wireless Headsets

Not Required,  Plantronics CS520 Binaural wireless EHS headset and adapter (+£260.89),  Jabra Pro 920 Mono with remote handset lifter (+£137.80),  Plantronics CS540 EHS Wireless headset and adapter (+£215.06).

### Headset Adapter

Not Required,  Yealink EHS36 (+£36.70).

### Wall Mount Bracket Required?

Not Required,  Required (+£4.70).