

Akuvox SP-R67G IP Phone



Product Name: Akuvox SP-R67G IP Phone

Manufacturer: -

Model Number: SP-R67G

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

Akuvox SP-R67G IP Phone

The Akuvox SP-R67G is Akuvox latest Gigabit Ethernet IP Phone for executives and busy professionals. The new design is based on flagship product Akuvox R59P, with high resolution TFT colour display, delivering a rich visual experience. Akuvox's Optima HD technology enables rich, clear, life-like voice communications.

Akuvox SP-R67G Key Features

ï¿⅓ HD Voice

� Dual-port Gigabit Ethernet, PoE

� Up to 6 SIP accounts

تز½ 4.3" 480*272 pixel colour display with backlight

� Supports Expansion Modules

17.1/2 Full Compatible with Asterisk, BroadSoft Platform

Akuvox SP-R67G - Technical Specifications Phone Features

� 6 Lines (Support 6 SIP accounts)

تزار Support Call Waiting, Call Forward, Call Transfer

تز½ Call on Hold, Mute, Auto-answer, Redial, DND

ï¿1/2 Local 3-Way Conference

آذِيً Volume Adjustable, Ring tones Selectable/Import/Delete

ï¿1/2 Speed Dial, Hotline

� Daylight Saving Time

� Network Packet Capture

� Country Ringtone Signal

� Direct IP call

ï¿⅓ Auto Redial, Call Return

آز½ Dial Plan

تز½ XML Browser

ï¿⅓ Hot Desking

ï¿1/2 Keypad Lock

� Action URL/URI

آذِا Phonebook (1000 groups), Blacklist (200 groups), Call logs (200 entries)

า๊¿½ 5 Remote Phone Book URL Supported

� LDAP

� Multi-Languages Support

� Support up to 6 Expansion Modules

ï¿1/2 Support Wireless Headset Adapter

IP-PBX Features

17.1/2 SMS. Voicemail. MWI Message Noti cation

تزاره Music on hold, Intercom, Paging

� BLF (Busy Lamp Field)

� Call Pickup, Group Call Pickup



Akuvox SP-R67G IP Phone

- آز½ Call Recording
- � Call Completion
- آزار Anonymous Call, Anonymous Call Rejection

Audio Features

- ï¿1/2 HD Voice: HD Handset, HD Speaker
- � Wideband Codec: G.722
- � Narrowband Codec: PCMA, PCMU, G.729, G723_53, G723_63, G726_16, G726_24,
- G726_32, G726_40, iLBC
- � VAD, CNG , Echo Canceller
- � PLC, AJB, AGC
- ii. 1/2 Full-duplex Hands-free Speakerphone with AEC

Network Features

- ï¿1/2 SIP V1(RFC2543), V2(RFC3261)
- ï¿1/2 NAT Transverse: STUN Mode
- ï¿1/2 Static IP/DHCP for IP Configuration
- าั¿1/2 3 DTMF modes: In-Band, RFC2833, SIP INFO
- 17:1/2 HTTP/HTTPS Web Server for Management
- � Proxy Mode and Peer-to-peer SIP Link Mode
- � NTP for Auto Time Setting
- � UDP/TCP/DNS-SRV(RFC 3263)
- ϊ¿½ TFTP/FTP/HTTP/HTTPS Protocols
- ۱ز½ 802.1 VLAN ئjï

Administration Features

- � Auto provisioning using FTP/TFTP/HTTPS/PnP
- าั¿½ Dial through IP PBX Using Phone Number
- آزٰ Dial through IP PBX Using URL Address
- ī¿½ Configuration Managements with web, keypad on the phone,and Auto Provisioning
- ï¿⅓ SNMP
- 73½ TR069 الأخ
- � Package Tracing Export, System Log

Security Features

- � Support HTTPS (SSL)
- � Support SRTP for Voice Data Encryption
- ï¿⅓ Support Login for Administration
- ï¿1/2 OpenVPN, IEEE802.1X
- � Digest Authentication Using MD5/MD5-sess
- 121/2 AES Encryption for Configuration file
- آذِ SIP Over TLS

Physical Features

- � Audiocodes Chipset
- � 16M Flash Memory
- � 4.3" 480*272 pixel color display with backlight, 16 bit depth color;
- ï¿1/2 Acrylic Cover
- � 8 Line Keys with LED
- 49 Keys (with 4 Soft Keys)



Akuvox SP-R67G IP Phone

าั¿½ 19 LED Lights (1 Power Light, 8 Line LEDs, 10 dual-color(red and green) LEDs for Extended key

ï¿1/2 2*RJ45 10/100/1000Mbps Ethernet Ports

� 1*RJ9 (4P4C) Handset port

� 1*RJ9 (4P4C) Headset port

� 1*RJ12 (6P6C) EXT port:

ī స్ట్రీ AC Power Adapter: Input: AC 100-240V; Output: DC 5V/1A

� PoE: IEEE 802.3af, Class 3 � Operating Humidity: 10~95%

� Storage Temperature: -10~50°C

រី¿½ Giftbox Size: :285.5*224*96.2 (mm),weight: 1.23kg

Please Enquire