

Akuvox SP-R67G IP Phone



Product Name: Akuvox SP-R67G IP Phone

Manufacturer: -

Model Number: SP-R67G

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

Akuvox SP-R67G IP Phone

The Akuvox SP-R67G is Akuvox latest Gigabit Ethernet IP Phone for executives and busy professionals. The new design is based on flagship product Akuvox R59P, with high resolution TFT colour display, delivering a rich visual experience. Akuvox's Optima HD technology enables rich, clear, life-like voice communications.

Akuvox SP-R67G Key Features

- 1/2 HD Voice
- 1/2 Dual-port Gigabit Ethernet, PoE
- 1/2 Up to 6 SIP accounts
- 1/2 4.3" 480*272 pixel colour display with backlight
- 1/2 Supports Expansion Modules
- 1/2 Full Compatible with Asterisk, BroadSoft Platform

Akuvox SP-R67G - Technical Specifications

Phone Features

- 1/2 6 Lines (Support 6 SIP accounts)
- 1/2 Support Call Waiting, Call Forward, Call Transfer
- 1/2 Call on Hold, Mute, Auto-answer, Redial, DND
- 1/2 Local 3-Way Conference
- 1/2 Volume Adjustable, Ring tones Selectable/Import/Delete
- 1/2 Speed Dial, Hotline
- 1/2 Daylight Saving Time
- 1/2 Network Packet Capture
- 1/2 Country Ringtone Signal
- 1/2 Direct IP call
- 1/2 Auto Redial, Call Return
- 1/2 Dial Plan
- 1/2 XML Browser
- 1/2 Hot Desking
- 1/2 Keypad Lock
- 1/2 Action URL/URI
- 1/2 Phonebook (1000 groups), Blacklist (200 groups), Call logs (200 entries)
- 1/2 5 Remote Phone Book URL Supported
- 1/2 LDAP
- 1/2 Multi-Languages Support
- 1/2 Support up to 6 Expansion Modules
- 1/2 Support Wireless Headset Adapter

IP-PBX Features

- 1/2 SMS.Voicemail.MWI Message Notification
- 1/2 Music on hold, Intercom, Paging
- 1/2 BLF (Busy Lamp Field)
- 1/2 Call Pickup, Group Call Pickup

Akuvox SP-R67G IP Phone

• Call Recording
• Call Completion
• Anonymous Call, Anonymous Call Rejection

Audio Features

• HD Voice: HD Handset, HD Speaker
• Wideband Codec: G.722
• Narrowband Codec: PCMA, PCMU, G.729, G.723_53, G.723_63, G.726_16, G.726_24, G.726_32, G.726_40, iLBC
• VAD, CNG, Echo Canceller
• PLC, AEB, AGC
• Full-duplex Hands-free Speakerphone with AEC

Network Features

• SIP V1(RFC2543), V2(RFC3261)
• NAT Traversal: STUN Mode
• Static IP/DHCP for IP Configuration
• 3 DTMF modes: In-Band, RFC2833, SIP INFO
• HTTP/HTTPS Web Server for Management
• Proxy Mode and Peer-to-peer SIP Link Mode
• NTP for Auto Time Setting
• UDP/TCP/DNS-SRV(RFC 3263)
• TFTP/FTP/HTTP/HTTPS Protocols
• 802.1 VLAN

Administration Features

• Auto provisioning using FTP/TFTP/HTTP/HTTPS/PnP
• Dial through IP PBX Using Phone Number
• Dial through IP PBX Using URL Address
• Configuration Managements with web, keypad on the phone, and Auto Provisioning
• SNMP
• TR069
• Package Tracing Export, System Log

Security Features

• Support HTTPS (SSL)
• Support SRTP for Voice Data Encryption
• Support Login for Administration
• OpenVPN, IEEE802.1X
• Digest Authentication Using MD5/MD5-session
• AES Encryption for Configuration file
• SIP Over TLS

Physical Features

• Audiocodes Chipset
• 16M Flash Memory
• 4.3" 480*272 pixel color display with backlight, 16 bit depth color;
• Acrylic Cover
• 8 Line Keys with LED
• 49 Keys (with 4 Soft Keys)

Akuvox SP-R67G IP Phone

1/2 19 LED Lights (1 Power Light, 8 Line LEDs, 10 dual-color(red and green) LEDs for Extended key

1/2 2*RJ45 10/100/1000Mbps Ethernet Ports

1/2 1*RJ9 (4P4C) Handset port

1/2 1*RJ9 (4P4C) Headset port

1/2 1*RJ12 (6P6C) EXT port:

1/2 AC Power Adapter: Input: AC 100-240V; Output: DC 5V/1A

1/2 PoE: IEEE 802.3af, Class 3

1/2 Operating Humidity: 10~95%

1/2 Storage Temperature: -10~50°C

1/2 Giftbox Size: :285.5*224*96.2 (mm),weight: 1.23kg

Please Enquire
