

## Akuvox SP-R67G IP Phone



Product Name: Akuvox SP-R67G IP Phone

Manufacturer: -

Model Number: SP-R67G

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

### Akuvox SP-R67G IP Phone

The Akuvox SP-R67G is Akuvox latest Gigabit Ethernet IP Phone for executives and busy professionals. The new design is based on flagship product Akuvox R59P, with high resolution TFT colour display, delivering a rich visual experience. Akuvox's Optima HD technology enables rich, clear, life-like voice communications.

### Akuvox SP-R67G Key Features

- HD Voice
- Dual-port Gigabit Ethernet, PoE
- Up to 6 SIP accounts
- 4.3" 480\*272 pixel colour display with backlight
- Supports Expansion Modules
- Full Compatible with Asterisk, BroadSoft Platform

### Akuvox SP-R67G - Technical Specifications

#### Phone Features

- 6 Lines (Support 6 SIP accounts)
- Support Call Waiting, Call Forward, Call Transfer
- Call on Hold, Mute, Auto-answer, Redial, DND
- Local 3-Way Conference
- Volume Adjustable, Ring tones Selectable/Import/Delete
- Speed Dial, Hotline
- Daylight Saving Time
- Network Packet Capture
- Country Ringtone Signal
- Direct IP call
- Auto Redial, Call Return
- Dial Plan
- XML Browser
- Hot Desking
- Keypad Lock
- Action URL/URI
- Phonebook (1000 groups), Blacklist (200 groups), Call logs (200 entries)
- 5 Remote Phone Book URL Supported
- LDAP
- Multi-Languages Support
- Support up to 6 Expansion Modules
- Support Wireless Headset Adapter

#### IP-PBX Features

- SMS.Voicemail.MWI Message Notification
- Music on hold, Intercom, Paging
- BLF (Busy Lamp Field)
- Call Pickup, Group Call Pickup

## Akuvox SP-R67G IP Phone

• Call Recording  
• Call Completion  
• Anonymous Call, Anonymous Call Rejection

### Audio Features

• HD Voice: HD Handset, HD Speaker  
• Wideband Codec: G.722  
• Narrowband Codec: PCMA, PCMU, G.729, G723\_53, G723\_63, G726\_16, G726\_24, G726\_32, G726\_40, iLBC  
• VAD, CNG, Echo Canceller  
• PLC, AJB, AGC  
• Full-duplex Hands-free Speakerphone with AEC

### Network Features

• SIP V1(RFC2543), V2(RFC3261)  
• NAT Transverse: STUN Mode  
• Static IP/DHCP for IP Configuration  
• 3 DTMF modes: In-Band, RFC2833, SIP INFO  
• HTTP/HTTPS Web Server for Management  
• Proxy Mode and Peer-to-peer SIP Link Mode  
• NTP for Auto Time Setting  
• UDP/TCP/DNS-SRV(RFC 3263)  
• TFTP/FTP/HTTP/HTTPS Protocols  
• 802.1 VLAN

### Administration Features

• Auto provisioning using FTP/TFTP/HTTP/HTTPS/PnP  
• Dial through IP PBX Using Phone Number  
• Dial through IP PBX Using URL Address  
• Configuration Managements with web, keypad on the phone, and Auto Provisioning  
• SNMP  
• TR069  
• Package Tracing Export, System Log

### Security Features

• Support HTTPS (SSL)  
• Support SRTP for Voice Data Encryption  
• Support Login for Administration  
• OpenVPN, IEEE802.1X  
• Digest Authentication Using MD5/MD5-sess  
• AES Encryption for Configuration file  
• SIP Over TLS

### Physical Features

• Audiocodes Chipset  
• 16M Flash Memory  
• 4.3" 480\*272 pixel color display with backlight, 16 bit depth color;  
• Acrylic Cover  
• 8 Line Keys with LED  
• 49 Keys (with 4 Soft Keys)

## Akuvox SP-R67G IP Phone

1/2 19 LED Lights (1 Power Light, 8 Line LEDs, 10 dual-color(red and green) LEDs for Extended key

1/2 2\*RJ45 10/100/1000Mbps Ethernet Ports

1/2 1\*RJ9 (4P4C) Handset port

1/2 1\*RJ9 (4P4C) Headset port

1/2 1\*RJ12 (6P6C) EXT port:

1/2 AC Power Adapter: Input: AC 100-240V; Output: DC 5V/1A

1/2 PoE: IEEE 802.3af, Class 3

1/2 Operating Humidity: 10~95%

1/2 Storage Temperature: -10~50&deg;C

1/2 Giftbox Size: :285.5\*224\*96.2 (mm),weight: 1.23kg

**Please Enquire**

---