

## Akuvox SP-R63G IP Phone



Product Name: Akuvox SP-R63G IP Phone

Manufacturer: -

Model Number: SP-R63G

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

### Akuvox SP-R63G IP Phone

The Akuvox SP-R63G is a VoIP phone for executives and busy professionals, featuring 3 SIP lines and dual Gigabit Ethernet support. The new design has an acrylic cover and a high resolution TFT colour display, that delivers a rich visual experience. Akuvox's Optima HD technology enables rich, clear, life-like voice communications.

### Akuvox SP-R63G Key Features

- HD Voice
- Dual-port Gigabit Ethernet, PoE
- Up to 3 SIP accounts
- 2.8" 320 \*240 pixel colour display with backlight
- Supports Expansion Modules
- Full Compatible with Asterisk, BroadSoft Platform

### Akuvox SP-R63G - Technical Specifications

#### Phone Features

- 3 Lines (Support 3 SIP accounts)
- Support Call Waiting, Call Forward, Call Transfer
- Call on Hold, Mute, Auto-answer, Redial, DND
- Local 3-Way Conference
- Volume Adjustable, Ring tones Selectable/Import/Delete
- Speed Dial, Hotline
- Daylight Saving Time
- Network Packet Capture
- Country Ringtone Signal
- Direct IP call
- Auto Redial, Call Return
- Dial Plan
- XML Browser
- Hot Desking
- Keypad Lock
- Action URL/URI
- Phonebook (1000 groups), Blacklist (200 groups), Call logs (200 entries)
- 5 Remote Phone Book URL Supported
- LDAP
- Multi-Languages Support
- Support up to 6 Expansion Modules
- Support Wireless Headset Adapter

#### IP-PBX Features

- SMS.Voicemail.MWI Message Notification
- Music on hold, Intercom, Paging
- BLF (Busy Lamp Field)
- Call Pickup, Group Call Pickup

## Akuvox SP-R63G IP Phone

• Call Recording  
• Call Completion  
• Anonymous Call, Anonymous Call Rejection

### Audio Features

• HD Voice: HD Handset, HD Speaker  
• Wideband Codec: G.722  
• Narrowband Codec: PCMA, PCMU, G.729, G.723\_53, G.723\_63, G.726\_16, G.726\_24, G.726\_32, G.726\_40, iLBC  
• VAD, CNG, Echo Canceller  
• PLC, AJB, AGC  
• Full-duplex Hands-free Speakerphone with AEC

### Network Features

• SIP V1(RFC2543), V2(RFC3261)  
• NAT Traversal: STUN Mode  
• Static IP/DHCP for IP Configuration  
• 3 DTMF modes: In-Band, RFC2833, SIP INFO  
• HTTP/HTTPS Web Server for Management  
• Proxy Mode and Peer-to-peer SIP Link Mode  
• NTP for Auto Time Setting  
• UDP/TCP/DNS-SRV(RFC 3263)  
• TFTP/FTP/HTTP/HTTPS Protocols  
• 802.1 VLAN

### Administration Features

• Auto provisioning using FTP/TFTP/HTTP/HTTPS/PnP  
• Dial through IP PBX Using Phone Number  
• Dial through IP PBX Using URL Address  
• Configuration Managements with web, keypad on the phone, and Auto Provisioning  
• SNMP  
• TR069  
• Package Tracing Export, System Log

### Security Features

• Support HTTPS (SSL)  
• Support SRTP for Voice Data Encryption  
• Support Login for Administration  
• OpenVPN, IEEE802.1X  
• Digest Authentication Using MD5/MD5-session  
• AES Encryption for Configuration file  
• SIP Over TLS

### Physical Features

• Audiocodes Chipset  
• 16M Flash Memory  
• 2.8" 320 \*240 pixel color display with backlight, 16 bit depth color;  
• Acrylic Cover  
• 8 Line Keys with LED  
• 39 Keys (with 4 Soft Keys)

## Akuvox SP-R63G IP Phone

• 9 LED Lights (1 Power Light, 8 dual-color (red or green) illuminated LEDs for line status information )

• 2 RJ45 10/100/1000Mbps Ethernet Ports

• 1 RJ9 (4P4C) Handset port

• 1 RJ9 (4P4C) Headset port

• 1 RJ12 (6P6C) EXT port:

• AC Power Adapter: Input: AC 100-240V; Output: DC 5V/1A

• PoE: IEEE 802.3af, Class 3

• Operating Humidity: 10~95%

• Storage Temperature: -10~50°C

• Giftbox Size: 274mm\*258mm\*142mm, weight: 1.6kg

**Please Enquire**

---