

Akuvox SP-R55G IP Phone



Product Name: Akuvox SP-R55G IP Phone

Manufacturer: -

Model Number: SP-R55G

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

Akuvox SP-R55G IP Phone

The Akuvox SP-R55G brings high-quality, cost effective solution to front line staff handling moderate volume of calls through advanced telephony features. The intuitive user interface of the Akuvox SP-R55G makes navigation easy and requires minimal training.

Akuvox SP-R55G Key Features

- 1/2 HD Voice
- 1/2 Up to 3 SIP Accounts
- 1/2 2.3" 132*64 Graphical LCD with Backlight
- 1/2 Support 3-way Conference
- 1/2 Support PoE
- 1/2 2 Gigabit Ethernet Ports
- 1/2 Full Compatible with Asterisk, BroadSoft Platform

Akuvox SP-R55G - Technical Specifications

Phone Features

- 1/2 3 Lines (support 3 SIP accounts)
- 1/2 Support Call Waiting, Call Forward, Call Transfer
- 1/2 Call on Hold, Mute, Auto-answer, Redial, DND
- 1/2 Local 3-Way Conference
- 1/2 Volume Adjustable, Ring tones Selectable
- 1/2 Speed Dial, Hotline
- 1/2 Daylight Saving Time
- 1/2 Network Packet Capture
- 1/2 Country Ringtone Signal
- 1/2 Direct IP call
- 1/2 Auto Redial, Call Return
- 1/2 Dial Plan
- 1/2 XML Browser
- 1/2 Hot Desking
- 1/2 Keypad Lock
- 1/2 Action URL/URI
- 1/2 Phonebook (500 groups), Blacklist (100 groups), Call logs (100 entries)
- 1/2 5 Remote Phone Book URL Supported
- 1/2 LDAP
- 1/2 Multi-Languages Support

IP-PBX Features

- 1/2 SMS.Voicemail.MWI Message Notification
- 1/2 Music on hold, Intercom
- 1/2 BLF (Busy Lamp Field)
- 1/2 Call Pickup, Group Call Pickup
- 1/2 Call Recording
- 1/2 Anonymous Call, Anonymous Call Rejection

Akuvox SP-R55G IP Phone

Audio Features

- HD Voice
- Wideband Codec: G.722
- Narrowband Codec: PCMA, PCMU, G.729, G723_53, G723_63, G726_16, G726_24, G726_32, G726_40
- VAD, CNG, Echo Cancellor
- Full-Duplex Speakerphone

Security Features

- Support HTTPS (SSL)
- Support SRTP for Voice Data Encryption
- Support Login for Administration
- SIP Over TLS

Network Features

- SIP V1(RFC2543), V2(RFC3261)
- Static IP/DHCP for IP configuration
- 3 DTMF modes: In-Band, RFC2833, SIP INFO
- HTTP/HTTPS Web Server for Management
- NTP for Auto Time Setting
- TFTP/FTP/HTTP/HTTPS Protocols
- 802.1Q VLAN

Administration Features

- POWER
- POE 802.3af/802.3at
- 48VDC input

PHYSICAL CHARACTERISTICS

- Auto provisioning using FTP/TFTP/HTTP/HTTPS/PnP
- Dial through IP PBX Using Phone Number
- Dial through IP PBX Using URL Address
- Configuration Manamements with web, keypad on the phone, and Auto Provisioning
- SNMP
- TR069

Physical Features

- Audiocodes Chipset
- 2.3" 132*64 Graphical LCD with Backlight
- 34 Keys (with 4 Soft Keys)
- 4 LED Lights (1 Power Light, 3 Account Lights)
- RJ9 Handset Jack and Headset Jack
- 2 RJ45 10/100/1000M Ethernet Jacks
- RJ12 Expansion Socket
- AC Power Adapter: Input: AC 100-240V; Output: DC 5V/1A
- PoE: IEEE 802.3af
- Giftbox Size: 202*239.5*102.5 (mm), weight: 1.19 kg

Akuvox SP-R55G IP Phone

Please Enquire
