

Panasonic KX-HDV130 IP Phone



Product Name: Panasonic KX-HDV130 IP Phone

Manufacturer: Panasonic Model Number: KX-HDV130B

Panasonic KX-HDV130 IP Phone

The Panasonic KX-HDV130 IP Phone delivers the ideal balance of high quality and sleek design, alongside a range of value-adding features. Designed to suit business buyers who demand technology that provides the reliable, flexible performance their businesses require, the KX-HDV130 makes professional-grade communications more accessible than ever. Panasonic KX-HDV130 Key Features

� 2 SIP accounts

ï¿1/2 132 x 64 pixel 2.3 inch graphical LCD with backlight

� HD Voice (G.722)

� Up to 500 phonebook

ï¿⅓ 3-way conference call support

� Compatible with Broadsoft UC one

� 2 x 10/100M ports, PoE

� Low standby power consumption

� XML Application Interface

� 2 Programmable keys / Line keys

� Plug and Play configuration

� Changeable angle stand

� Wall mounting (Optional)

Panasonic KX-HDV130 - Technical Specifications Display

� LCD Display Monochrome Graphical

آذِرُ LCD Size 132 × 64 pixel 2.3 inch Graphical LCD

� LCD Contrast 6 levels

ï¿1/2 LCD Backlight On/Auto/Off

Install Options

ï¿1/2 Desk Mount Tilt Yes – 2 positions

� Wall Mount KX-A440 (optional)

ï¿1/2 Power Adaptor KX-A423 (optional)

Audio Features

آذِا Handset, Speaker, Headset Volume 8 levels (includes echo cancellation and distortion prevention)

ï¿1/2 Ringtones 32

� Ringer Volume 8 levels + Off

ï¿1/2 Headset Port RJ9 jack

ï¿1/2 Electronic Hook Switch Control Port -

آزا Audio Codec G.711a-law / G.711µ-law / G.722 (wideband) / G.729a

آزار HD Voice Yes

ï¿1/2 Speaker Phone Yes

Keys

� Programmable Keys 2



Panasonic KX-HDV130 IP Phone

Software Features

- ï¿1/2 Phone Book (Local) 500
- ï¿1/2 LDAP Remote Phonebook Yes
- ï¿⅓ XML Remote Phonebook Yes
- ī¿½ Call Log Entries 30 incoming calls + 30 outgoing calls
- � Conferencing 3 parties (within terminal multi-party dependent on server)
- ï¿1/2 XML Application Yes
- آذًا Music on Hold Supplied by Host Service (PBX / SIP Server)

IP Features

آزٰ SIP Accounts 2

าั¿½ SIP Compatibility RFC 3261 Standard SIP Server, Asterisk, Broadsoft, CommuniGate Pro, Panasonic IP PBX

ï¿1/2 IP Version IPv6 / IPv4

- � DHCP Client Yes
- ï¿⅓ DNS Yes
- HTTP Yes
- � HTTPS Yes
- ï¿⅓ SNTP Client Yes
- � VLAN (802.1q) Yes
- � QoS (DiffServ) Yes

Configuration

- 121/2 Plug & Play Configuration Server based configuration, TR-069
- าั¿½ Manual Configuration Internal web Configurator, Local (LCD based) network configuration

Interface

- � Ethernet Ports 2
- ï¿1/2 Ethernet Interface 10/100 Mbps
- $\ddot{\imath} \dot{\imath} \frac{1}{2}$ PoE (Power over Ethernet) Yes
- � Power Consumption
- � PoEStand-by: approx. 2.2 W (ECO mode off), 1.9 W (ECO mode on)Talking: 2.3 W (ECO mode off), 2.0 W (ECO mode on)Max: 2.8 WAC AdaptorStand-by: 2.0 W (ECO mode off), 1.3 W (ECO mode on)Talking: 2.1 W (ECO mode off), 1.4 W (ECO mode on)Max: 2.8 W
- T¿½ Operating Environment 0 °C 40 °C (32 °F 104 °F)
- تزاري Dimensions (Width x Depth x Height; excluding the handset, stand attached)
- ī¿½ Colour: Black. Also available in white.High position: 167 mm x 165 mm x 148 mmLow position: 167 mm x 173 mm x 115 mm
- ī స్ట్రి Weight (with handset, handset cord and stand) 691 g

Price: £37.50

Options available for Panasonic KX-HDV130 IP Phone:

UK PSU

Required (+£3.80),



Panasonic KX-HDV130 IP Phone

Not Required.