

## Polycom VVX D60 DECT Wireless Phone (VVXD60)



Product Name: Polycom VVX D60 DECT Wireless Phone (VVXD60)

Manufacturer: -

Model Number: 2200-17825-015

Please Note: This item has been discontinued. See the VVX D230 for an alternative.

### Polycom VVX D60 DECT Wireless Handset (VVXD60)

The Polycom VVX D60 Wireless Handset combines the freedom of wireless communications with other useful business features. The VVX D60 offers the same SIP features as the VVX desk phones, making it incredibly practical for any business.

### Polycom VVX D60 Wireless Handset Key Features

- High-resolution colour display with HD voice quality
- PoE connection
- Hands-free speakerphone
- Voice Range: 50m (165ft) indoor/ 300m (980ft) outdoor
- 10 hours talk time, 100 hours standby
- Belt clip available
- 2.5 mm headset port (external 2.5mm to 3.5mm adapter)

Whether it is deployed in a business environment that requires workers to move around, or in a small office with no dedicated receptionist, the Polycom VVX D60 additional wireless handset helps teams communicate with ease, whether talking to customers or with each other.

### Polycom VVX D60 Wireless Handset - Technical Specifications Included

- Handset
- Charger
- 2.5 mm to 3.5mm headset adapter
- Quick start guide
- Power adapter

### Handset User Interface Features

- 2 in color TFT LCD display (resolution 178 x 220 pixel)
- Voicemail support
- Unicode UTF-8 character support.
- Multilingual user interface including: Chinese, Danish, Dutch, English (Canada/US/UK), French, German, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Slovenian, Spanish and Swedish

### Handset Audio Features

- Full-duplex conversations, acoustic echo cancellation and background noise suppression
- Frequency response &ndash; 150 Hz &ndash; 7 kHz for handset, optional headset and handsfree speakerphone models
- Narrowband Codecs: G.711 (A-law and &mu;-law), G.729AB
- Wideband Codec: G.722
- Individual volume settings with visual feedback for each audio path
- Voice activity detection
- Comfort noise generation
- DTMF tone generation (RFC2833, in-band and SIP INFO)
- Low-delay audio packet transmission

## Polycom VVX D60 DECT Wireless Phone (VVXD60)

- Adaptive jitter buffers
- Packet loss concealment

### Handset Call Handling Features

- Multiple Lines Support for Handsets (5 lines per HS)
- Up to 4 simultaneous calls
- Up to 5 handsets
- Shared call/ bridged line appearance
- Distinctive incoming call treatment/call waiting
- Call timer and call waiting
- Call transfer, hold, divert (forward), pickup
- Called, calling, connected party information
- Local 3-way audio conferencing
- 1-touch speed dial, redial
- Remote missed call notification
- Do not disturb function
- Intercom

### Headset and Handset Compatibility

- Dedicated 2.5 mm headset port
- External 2.5 mm to 3.5 mm headset adapter
- Compliant with ADA Section 508 Subpart B1194.23 (all)
- Hearing aid compatible handset for magnetic coupling to hearing aids

### Handset Power

- External universal AC adapter (5V 6W DC)

### Handset Battery

- 1 Ni-MH 800 mAh (2.4V) AAA battery (rechargeable)
- 10 hours talk time
- 120 hours standby time

### Range

- Indoor: 165ft (50m)
- Outdoor: 980ft (300m)

### Security

- 802.1X authentication and EAPOL
- Media encryption via SRTP
- Transport layer security
- Encrypted configuration files
- Digest authentication
- Password login
- Support for URL syntax with password for boot server address
- HTTPS secure provisioning
- Support for signed software executables

### Frequency

## Polycom VVX D60 DECT Wireless Phone (VVXD60)

• 1920-1930 MHz

• 1880-1900 MHz

• 1880-1895 MHz

• 1896-1903 MHz

• 1910-1920 MHz (post FCS)

• 1921-1930 MHz (post FCS)

• 1786-1791 MHz (post FCS) investments&mdash;deploy VVX D60 business media phones on your existing network without needing to upgrade your call control platform

### Size

• Handset size: 2 x 6.7 x 1 in (5 x 17 x 2.5 cm) (W x H x D)

• Handset charger size: 3.75 x 2.20 x 3.35 in (9.5 x 5.5 x 8.5 cm) (W x H x D)

**Price: £111.60**

---