

Spectralink 7202 DECT Handset



Product Name: Spectralink 7202 DECT Handset

Manufacturer: Spectralink Model Number: 02600000

Please Note: This product has been discontinued.

Spectralink 7202 DECT Handset

The Spectralink 7202 is a wireless DECT phone designed for long-term dependability and increased mobility in specialised working environments. The functionalities of the robust and feature rich handset make it a valuable working tool for personnel within industries such as retail and healthcare. Moreover, the flexible menu structure allows the handsets to be customised to specific vertical markets.

Spectralink 7202 Key Features

- � Colour display
- � Date and time in display*
- ï¿⅓ Auto key lock
- า๊¿½ 12 different ringtones and adjustable ring volume
- ï¿1/2 Special ring tones for noisy environments
- ī స్ట్రి Auto login roaming between two different installations
- � Auto-answer (B-answer)
- � Alarm key ready for alarm application**
- � Alarm key speed dial
- CLIP ½ CLIP
- � Telephone book with 50 entries
- ï¿1/2 Call list of incoming/missed/received calls (up to 40 calls)
- � Text message
- า๊¿½ LED indication of incoming and unanswered calls
- ï¿⅓ Full Slot DECT radio
- � Software Update Over The Air (SUOTA)
- آذِ½ 14 menu languages (UK, FR, DE, ES, IT, NL, CZ,PL, DK, NO, SV, FI, PT, RU)

The Spectralink 7202 is a robust, well-designed, feature rich, and price competitive handset. It meets the demands for mobility and is built for long-term dependability in harsh environments. The Spectralink 7202 Technical Specification

APPROVALS

� EMC: – EN 301 489-1 – EN 301 489-6

SIZE AND WEIGHT

� Size: 149 x 50 x 28 mm (5.9 x 2.0 x 1.1 in.) � Weight: 123 g incl. battery (4.3 oz incl. battery)

SPEECH / STANDBY TIME

า๊¿1/2 Speech time: up to 23 (27 hours in economy mode)

ï¿1/2 Standby time: up to 118 hours

BATTERY

� Battery: NiMH battery

ī¿½ Easily removable battery with option to use in shiftoperation environments



Spectralink 7202 DECT Handset

T¿½ Battery lifetime under proper charge and discharge conditions: two years or 500 charging cycles

TEMPERATURE

� Operating temperature: 0 - 40º C (32º - 104º F) � Charging temperature: 0 - 25º C (32º - 77º F)

IP RATING

7212: IP 54 آز

TESTS

ï¿1/2 Bump test: IEC 68-2-29

Please Enquire

Options available for Spectralink 7202 DECT Handset:

Spectralink Charger for 72 & 76 Series

Required (+£13.00), Not Required.

Spectralink UK PSU for Charger

Required (+£13.90), Not Required.

Spectralink Dual Charger & slot for spare battery

Required (+£54.00), Not Required.