

## Spectralink 7202 DECT Handset



Product Name: Spectralink 7202 DECT Handset

Manufacturer: Spectralink

Model Number: 02600000

**Please Note:** This product has been discontinued.

### Spectralink 7202 DECT Handset

The Spectralink 7202 is a wireless DECT phone designed for long-term dependability and increased mobility in specialised working environments. The functionalities of the robust and feature rich handset make it a valuable working tool for personnel within industries such as retail and healthcare. Moreover, the flexible menu structure allows the handsets to be customised to specific vertical markets.

#### Spectralink 7202 Key Features

- Colour display
- Date and time in display\*
- Auto key lock
- 12 different ringtones and adjustable ring volume
- Special ring tones for noisy environments
- Auto login & roaming between two different installations
- Auto-answer (B-answer)
- Alarm key & ready for alarm application\*\*
- Alarm key speed dial
- CLIP
- Telephone book with 50 entries
- Call list of incoming/missed/received calls (up to 40 calls)
- Text message
- LED indication of incoming and unanswered calls
- Full Slot DECT radio
- Software Update Over The Air (SUOTA)
- 14 menu languages (UK, FR, DE, ES, IT, NL, CZ, PL, DK, NO, SV, FI, PT, RU)

The Spectralink 7202 is a robust, well-designed, feature rich, and price competitive handset. It meets the demands for mobility and is built for long-term dependability in harsh environments.

#### The Spectralink 7202 Technical Specification

#### APPROVALS

- EMC: & EN 301 489-1 & EN 301 489-6

#### SIZE AND WEIGHT

- Size: 149 x 50 x 28 mm (5.9 x 2.0 x 1.1 in.)
- Weight: 123 g incl. battery (4.3 oz incl. battery)

#### SPEECH / STANDBY TIME

- Speech time: up to 23 (27 hours in economy mode)
- Standby time: up to 118 hours

#### BATTERY

- Battery: NiMH battery
- Easily removable battery with option to use in shiftoperation environments

## Spectralink 7202 DECT Handset

• Battery lifetime under proper charge and discharge conditions: two years or 500 charging cycles

### TEMPERATURE

• Operating temperature: 0 - 40°C (32°F - 104°F)  
• Charging temperature: 0 - 25°C (32°F - 77°F)

### IP RATING

• 7212: IP 54

### TESTS

• Bump test: IEC 68-2-29

### Please Enquire

---

Options available for Spectralink 7202 DECT Handset :

#### **Spectralink Charger for 72 & 76 Series**

Not Required, Required (+£13.00).

#### **Spectralink UK PSU for Charger**

Not Required, Required (+£13.90).

#### **Spectralink Dual Charger & slot for spare battery**

Not Required, Required (+£54.00).