

## Spectralink 7202 DECT Handset



Product Name: Spectralink 7202 DECT Handset

Manufacturer: Spectralink

Model Number: 02600000

Please Note: This product has been discontinued.

### Spectralink 7202 DECT Handset

The Spectralink 7202 is a wireless DECT phone designed for long-term dependability and increased mobility in specialised working environments. The functionalities of the robust and feature rich handset make it a valuable working tool for personnel within industries such as retail and healthcare. Moreover, the flexible menu structure allows the handsets to be customised to specific vertical markets.

### Spectralink 7202 Key Features

- 1/2 Colour display
- 1/2 Date and time in display\*
- 1/2 Auto key lock
- 1/2 12 different ringtones and adjustable ring volume
- 1/2 Special ring tones for noisy environments
- 1/2 Auto login &ndash; roaming between two different installations
- 1/2 Auto-answer (B-answer)
- 1/2 Alarm key &ndash; ready for alarm application\*\*
- 1/2 Alarm key speed dial
- 1/2 CLIP
- 1/2 Telephone book with 50 entries
- 1/2 Call list of incoming/missed/received calls (up to 40 calls)
- 1/2 Text message
- 1/2 LED indication of incoming and unanswered calls
- 1/2 Full Slot DECT radio
- 1/2 Software Update Over The Air (SUOTA)
- 1/2 14 menu languages (UK, FR, DE, ES, IT, NL, CZ, PL, DK, NO, SV, FI, PT, RU)

The Spectralink 7202 is a robust, well-designed, feature rich, and price competitive handset. It meets the demands for mobility and is built for long-term dependability in harsh environments.

### The Spectralink 7202 Technical Specification

#### APPROVALS

- 1/2 EMC: &ndash; EN 301 489-1 &ndash; EN 301 489-6

#### SIZE AND WEIGHT

- 1/2 Size: 149 x 50 x 28 mm (5.9 x 2.0 x 1.1 in.)
- 1/2 Weight: 123 g incl. battery (4.3 oz incl. battery)

#### SPEECH / STANDBY TIME

- 1/2 Speech time: up to 23 (27 hours in economy mode)
- 1/2 Standby time: up to 118 hours

#### BATTERY

- 1/2 Battery: NiMH battery
- 1/2 Easily removable battery with option to use in shiftoperation environments

## Spectralink 7202 DECT Handset

• Battery lifetime under proper charge and discharge conditions: two years or 500 charging cycles

### TEMPERATURE

• Operating temperature: 0 - 40°C (32°F - 104°F)

• Charging temperature: 0 - 25°C (32°F - 77°F)

### IP RATING

• IP 54

### TESTS

• Bump test: IEC 68-2-29

**Please Enquire**

---

Options available for Spectralink 7202 DECT Handset :

**Spectralink Charger for 72 & 76 Series**

Not Required, [Required \(+£13.00\)](#).

**Spectralink UK PSU for Charger**

Not Required, [Required \(+£13.90\)](#).

**Spectralink Dual Charger & slot for spare battery**

Not Required, [Required \(+£54.00\)](#).