



Product Name: Spectralink 7202 DECT Handset

Manufacturer: Spectralink Model Number: 02600000

Please Note: Spectralink Dect Handsets require a charging station and PSU which are not included with the handset. These can be added to your order via the drop down menu above. If you require other options please see the Spectralink Accessories sections.

## Spectralink 7202 DECT Handset

The Spectralink 7202 is a wireless DECT phone designed for long-term dependability and increased mobility in specialised working environments. The functionalities of the robust and feature rich handset make it a valuable working tool for personnel within industries such as retail and healthcare. Moreover, the flexible menu structure allows the handsets to be customised to specific vertical markets.

Spectralink 7202 Key Features

- � Colour display
- � Date and time in display\*
- � Auto key lock
- 12.1/2 12 different ringtones and adjustable ring volume
- � Special ring tones for noisy environments
- าั¿½ Auto login roaming between two different installations
- � Auto-answer (B-answer)
- � Alarm key ready for alarm application\*\*
- � Alarm key speed dial
- � CLIP
- � Telephone book with 50 entries
- Ti21/2 Call list of incoming/missed/received calls (up to 40 calls)
- � Text message
- าั¿1/2 LED indication of incoming and unanswered calls
- ï¿⅓ Full Slot DECT radio
- i¿½ Software Update Over The Air (SUOTA)
- آذِ½ 14 menu languages (UK, FR, DE, ES, IT, NL, CZ,PL, DK, NO, SV, FI, PT, RU)

The Spectralink 7202 is a robust, well-designed, feature rich, and price competitive handset. It meets the demands for mobility and is built for long-term dependability in harsh environments. The Spectralink 7202 Technical Specification

**APPROVALS** 

� EMC: – EN 301 489-1 – EN 301 489-6

SIZE AND WEIGHT

� Size: 149 x 50 x 28 mm (5.9 x 2.0 x 1.1 in.) آذِيً Weight: 123 g incl. battery (4.3 oz incl. battery)

SPEECH / STANDBY TIME

12.1/2 Speech time: up to 23 (27 hours in economy mode)

ï¿1/2 Standby time: up to 118 hours

**BATTERY** 



## Spectralink 7202 DECT Handset

ï¿1/2 Battery: NiMH battery

ī సైస్ట్ Easily removable battery with option to use in shiftoperation environments

า๊¿½ Battery lifetime under proper charge and discharge conditions: two years or 500 charging cycles

## **TEMPERATURE**

� Operating temperature: 0 - 40º C (32º - 104º F) � Charging temperature: 0 - 25º C (32º - 77º F)

**IP RATING** 

تز½ 7212: IP 54

**TESTS** 

ï¿1/2 Bump test: IEC 68-2-29

Price: £144.30

Options available for Spectralink 7202 DECT Handset:

Spectralink Charger for 72 & 76 Series

Not Required, Required (+£13.00).

Spectralink UK PSU for Charger

Not Required, Required (+£13.90).

Spectralink Dual Charger & slot for spare battery

Not Required, Required (+£54.00).