

## Escene IV750 Video IP Door Phone



Product Name: Escene IV750 Video IP Door Phone

Manufacturer: Escene

Model Number: IV750

Please Note: This product is no longer available. For alternatives, we recommend looking at the Fanvil or 2N range.

### Escene IV750 Video IP Door Phone

The Escene IV750 is an IP65 certified VoIP intercom. The redesigned case is more secure and has a more streamlined look with increased tamper resistance. The IV750 meets the requirements of industry users and is compatible with different platforms, offering users a convenient service. The IV750 intercom has been installed in offices, airports, schools and libraries etc.

#### Escene IV750 Key Features

- Support embedded or wall-mounted installation.
- High-quality audio and video communication.
- WEB supports multi-language: Chinese, Russian, French, etc.
- 1 SIP accounts, support 3-way conferencing;
- 1\*RJ45 standard Ethernet Ports(LAN), Support PoE;
- Indoor open-door interface and external power supply interface;

### Escene IV750 - Technical Specifications

#### Phone Features

- WEB Support Multi-language
- Support 1 Lines Talking
- DND, Hot line
- Auto-answer, 3-way conferencing
- Direct IP call without SIP proxy
- Custom DSS Key(Speed Dial / Intercom,etc)
- Time setting(SNTP/SIP Server/Manual)
- Full-duplex Talking, Dial with digital keypad
- Support switching SIP server & Second server
- WEB Volume control

#### Advanced Features

- Built-in Indoor-open interface
- Built-in External Power interface
- Built-in Relay

#### IP PBX System Integration

- DND&Call Transfer

#### Codes and Voice Features

- Wideband Codec: G.722
- Narrowband codec: G.711&mu;/A, G.723.1
- G.726, G.729AB,VAD, CNG, AEC, AGC
- Full-duplex

## Escene IV750 Video IP Door Phone

### Network Features

- SIP v1 (RFC2543), v2 (RFC3261)
- SIP connection: Proxy mode & Peering Points mode, DNS SRV (RFC3263)
- Redundant server support
- NAT Traversal: STUN mode
- DTMF: In-Band, RFC2833, SIP Info, Auto
- HTTP/HTTPS Web Management
- IP Assignment: Static/DHCP/PPPoE
- Bridge/Router mode for PC port
- Telnet/HTTP/HTTPS server
- DNS client, NAT/DHCP server

### Physical Features

- 1\*Speaker Key or DSS key
- 1\*RJ-45 10/100M(LAN)
- Support PoE: IEEE802.3af class 0
- Embedded or wall-mounted installation
- Power: 12V/1A DC
- Minimized Power:4W
- Maximum Power: 6W
- Operating humidity: -30~60℃
- Storage temperature: up to 60℃
- Relative Humidity:10-90%

### Package Features

- Qty/CTN:
- N.W/CTN:
- G.W/CTN:
- Measurement:
- Dimension:
- Carton Meas:

**Please Enquire**